

SEWING MACHINERY

WEALE'S RUDIMENTARY SCIENTIFIC
AND EDUCATIONAL SERIES.

FRANKLIN INSTITUTE LIBRARY
PHILADELPHIA

Class 687 Book Ur 64 Accession 5434

ARTICLE V.—The Library shall be divided into TWO CLASSES; the first comprising such works as, from their rarity or value, should not be lent out, all unbound periodicals, and such text books as ought to be found in a library of reference except when required by Committees of the Institute, or by members or holders of second class stock, who have obtained the sanction of the Committee. The second class shall include those books intended for circulation.

ARTICLE VI.—The Secretary shall have authority to loan to Members and to holders of second class stock, any work belonging to the SECOND CLASS, subject to the following regulations:

Section 1.—No individual shall be permitted to have more than *two books* out at one time, without a written permission, signed by at least two members of the Library Committee; nor shall a book be kept out more than TWO WEEKS; but if no one has applied for it, the former borrower may renew the loan. Should any person have applied for it, the latter shall have the preference.

Section 2.—A FINE OF TEN CENTS PER WEEK shall be exacted for the detention of a book beyond the limited time; and if a book be not returned within three months it shall be deemed lost, and the borrower shall, in addition to his fines, forfeit its value.

Section 3.—Should any book be returned injured, the borrower shall pay for the injury, or replace the book, as the Library Committee may direct; and if one or more books, belonging to a set or sets, be lost, the borrower shall replace them or make full restitution.

ARTICLE VII.—Any person removing from the Hall, without permission from the proper authorities, any book, newspaper or other property in charge of the Library Committee, shall be reported to the Committee, who may inflict any fine not exceeding twenty-five dollars.

ARTICLE VIII.—No member or holder of second class stock, whose annual contribution for the current year shall be unpaid or who is in arrears for fines, shall be entitled to the privileges of the Library or Reading Room.

ARTICLE IX.—If any member or holder of second class stock, shall refuse or neglect to comply with the foregoing rules, it shall be the duty of the Secretary to report him to the Committee on the Library.

ARTICLE X.—Any Member or holder of second class stock, detected in mutilating the newspapers, pamphlets or books belonging to the Institute shall be deprived of his right of membership, and the name of the offender shall be made public.

5434

687, Ur 64

SANITARY WORK IN THE SMALLER TOWNS

AND IN VILLAGES. Comprising:—1. Some of the more Common Forms of Nuisance and their Remedies; 2. Drainage; 3. Water Supply. A useful book for Members of Local Boards and Rural Sanitary Authorities, Health Officers, Engineers, Surveyors, Builders, and Contractors. By CHARLES SLAGG, A.I.C.E. 2s. 6d.; cloth boards, 3s.

WELL-DIGGING, BORING, AND PUMP WORK.

By JOHN GEORGE SWINDELL, R.I.B.A. New Edition, revised by G. R. BURNELL, C.E. Illustrated. 1s. 6d.

TUBULAR & OTHER IRON GIRDER BRIDGES.

Particularly describing the BRITANNIA and CONWAY TUBULAR BRIDGES. With a Sketch of Iron Bridges, and Illustrations of the Application of Malleable Iron to the Art of Bridge Building. By G. D. DEMPSEY, C.E. New Edition, with Illustrations. 1s. 6d.

THE CONSTRUCTION OF ROADS AND STREETS.

In Two Parts. I. The Art of Constructing Common Roads. By HENRY LAW, C.E. II. Recent Practice in the Construction of Roads and Streets: including Pavements of Stone, Wood, and Asphalte. By D. KINNAR CLARK, M.I.C.E. With numerous Illustrations. 4s. 6d.; cloth boards, 5s.

THE SLIDE RULE, AND HOW TO USE IT;

containing full and easy Instructions, by C. HOARE, C.E. With a Slide Rule in Tuck of Cover. 3s.; cloth boards, 3s. 6d.

DICTIONARY OF TERMS used in Architecture,

Building, and Engineering; Mining, Surveying, and Construction; Early and Ecclesiastical Art; the Fine Arts, &c. New Edition, revised and enlarged by ROBERT HUNT, F.R.S. 5s.; cloth boards, 6s.

DRAWING AND MEASURING INSTRUMENTS.

Including—I. Instruments employed in Geometrical and Mechanical Drawing, and in the Construction, Copying, and Measurement of Maps and Plans. II. Instruments used for the purposes of Accurate Measurement, and for Arithmetical Computations. By J. F. HEATHER, M.A., late of the Royal Military Academy, Woolwich, Author of "Descriptive Geometry," &c., &c. Illustrated. 1s. 6d.

OPTICAL INSTRUMENTS. Including (more especially)

Telescopes, Microscopes, and Apparatus for producing copies of Maps and Plans by Photography. By J. F. HEATHER, M.A. Illustrated. 1s. 6d.


SURVEYING AND ASTRONOMICAL INSTRUMENTS.

Including—I. Instruments used for Determining the Geometrical Features of a portion of Ground. II. Instruments employed in Astronomical Observations. By J. F. HEATHER, M.A. Illustrated. 1s. 6d.


MATHEMATICAL INSTRUMENTS. By J. F.

HEATHER, M.A. Enlarged Edition, for the most part entirely re-written. The 3 Parts, as above, in One thick Volume. With numerous Illustrations. 4s. 6d.; cloth boards, 5s.

CROSBY LOCKWOOD & CO., 7, STATIONERS' HALL COURT, E.C.



FRANKLIN
INSTITUTE
LIBRARY



THE FIRST SEWING MACHINE.

(See pp. 4 and 26.)

SEWING MACHINERY

BEING

A PRACTICAL MANUAL

OF

THE SEWING MACHINE

COMPRISING
ITS HISTORY AND DETAILS OF ITS CONSTRUCTION, WITH FULL
TECHNICAL DIRECTIONS FOR THE ADJUSTING
OF SEWING MACHINES

By J. W. URQUHART, C.E.

AUTHOR OF "ELECTRO-PLATING: A PRACTICAL HANDBOOK;" "ELECTRIC LIGHT :
ITS PRODUCTION AND USE"

WITH NUMEROUS ILLUSTRATIONS



LONDON

CROSBY LOCKWOOD AND CO.

7, STATIONERS' HALL COURT, LUDGATE HILL

1881

[All rights reserved]

CONS
TJ
1510
477
1881

STUTTGART M.D. 1881
A. 1881. 1881

LONDON:
PRINTED BY VIRTUE AND CO., LIMITED,
CITY ROAD.

PREFACE.

THE aim of the Author in preparing this little treatise was to confine himself within the limits of such a production as might be read with advantage by that numerous portion of the community engaged in selling and adjusting sewing machines, as well as by the general public using or interested in stitching mechanism.

The work is intended to give a concise but accurate and readable account of the invention of sewing machines, with descriptions of the chief types of stitching mechanism in use, and also technical directions for the adjustment of specific types of machine. It is hoped that the latter feature of the work will meet a want long felt of a work of reference in cases of difficulties as regards inefficient operation of sewing machines. The book is divided into two sections, and those in turn are arranged in chapters. The first section treats of the history, and gives elementary principles upon which sewing machines work, with descriptions of the machine. The second section is entirely devoted to practical instructions to users, adjusters, and sellers of sewing machines.

The Author has necessarily, owing to the limited

space at his command, not attempted to include descriptions of any but types of the machine now in use; his aim has been to review essential and leading facts, and to produce a handbook that might prove of actual service in the business of daily life.

He has to acknowledge, with thanks, the able assistance, during the preparation of the work, of the Wheeler and Wilson Manufacturing Company, the Howe Machine Company, and the Willcox and Gibbs Company.

LONDON, *August*, 1880.

CONTENTS.

SECTION I.

HISTORY AND DESCRIPTION OF THE SEWING MACHINE.

CHAPTER I.

INVENTION OF THE SEWING MACHINE: AN HISTORICAL SKETCH	PAGE 1
---	-----------

CHAPTER II.

THE ELEMENTS OF STITCHING MECHANISM.	19
--	----

CHAPTER III.

SHUTTLE SEWING MACHINES	26
-----------------------------------	----

CHAPTER IV.

DESCRIPTIONS OF ROTATING-HOOK MACHINES	37
--	----

CHAPTER V.

SINGLE-THREAD SEWING MACHINES	74
---	----

CHAPTER VI.

PROPORTIONS OF NEEDLES AND THREAD TO WORK	90
---	----

SECTION II.

DIRECTIONS FOR ADJUSTING THE VARIOUS
TYPES OF SEWING MACHINERY.

CHAPTER VII.

WHEELER AND WILSON MACHINES	PAGE 94
---------------------------------------	------------

CHAPTER VIII.

SINGER MACHINES	129
---------------------------	-----

CHAPTER IX.

GROVER AND BAKER MACHINES	152
-------------------------------------	-----

CHAPTER X.

"LITTLE WANZER" MACHINES	161
------------------------------------	-----

CHAPTER XI.

WEIR MACHINES	163
-------------------------	-----

LIST OF ILLUSTRATIONS.

FIG.		PAGE
	THE FIRST SEWING MACHINE <i>Frontispiece</i>	
	PORTRAIT OF ELIAS HOWE	8
	PORTRAIT OF ALLEN B. WILSON	12
1.	THE LOCK STITCH	21
2.	HOWE MACHINE—UNDER PARTS	28
3.	HOWE MACHINE IN WORKING POSITION	29
4.	"THREADING THE TENSION"	31
5.	TENSION WHEEL APART	32
6.	UPPER EXTREMITY OF NEEDLE AND PRESSER BARS	32
7.	HOWE MACHINE: THE LOOP MADE	33
8.	HOWE SHUTTLE—PLAIN HEEL	34
9.	WINDING THE BOBBIN	35
10.	HIGH BED ROTATING-HOOK MACHINE	38
11.	CLOTH PLATE REMOVED	39
12.	THE HINGED BOBBIN HOLDER	40
13.	UNDER SIDE OF CLOTH PLATE	40
14.	OLD STYLE OF FEED BAR	41
15.	DITTO REMOVED FROM MACHINE	41
16.	DRAW FEED MOTION	42
17.	DRAW FEED BAR	43
	PLATE I.	45
18.	ROTATING HOOK	46
19.	STRAIGHT-NEEDLE MACHINE	48
20.	NO. 6 MACHINE	49
21.	DITTO CLOTH PLATE REMOVED	51
22.	UNDER PARTS	52
23.	THE CAMS	53
24.	VARIABLE MOTION	53
25.	SECTION OF DITTO	54
26.	NEW HOOK	55
27.	BOBBIN AND CASE	55

FIG.		PAGE
	PLATE II.	56
28.	BOBBIN HOLDER	57
29.	UNDER TENSION	58
30.	NEW FEED BAR	58
31.	ROLLING PRESSER	59
32.	NO. 7 MACHINE	60
33.	DITTO PLATE REMOVED	61
34.	NO. 8 MACHINE	62
	PLATE III.	64
35.	WILLCOX AND GIBBS' MACHINE	75
36.	STITCH INDICATOR	82
37.	OILWAYS OF FEED MECHANISM	83
38.	OILWAYS OF UPPER PARTS	84
39.	PLACING THE NEEDLE	85
40.	SETTING THE NEEDLE	85
41.	SCREWING UP THE NEEDLE	86
42.	THREAD WAYS	87

SEWING MACHINERY.

SECTION I.

HISTORY AND DESCRIPTION OF THE SEWING MACHINE.

CHAPTER I.

INVENTION OF THE SEWING MACHINE: AN HISTORICAL SKETCH.

THE invention of what is known as the lock stitch, and of the mechanism by which it is produced, is due to America, and dates from about 1844.

Elias Howe, the inventor of the shuttle sewing machine, was born in 1819, in Spencer, Massachusetts. When the idea of a sewing machine entered his mind he was twenty years old, and a "machinist" in the shop of an ingenious mechanic in Boston. Young Howe overheard a capitalist remark to his employer that an independent fortune would be insured to the inventor of a sewing machine, and forthwith the idea seized him that a stitching machine was practicable. But the only immediate effect upon him of the conversation in the shop of Mr. Davis was to induce a habit of reflecting upon the art of sewing, watching the operation as performed by hand, and wondering

whether it was within the compass of the mechanical arts to do it by machinery. His uppermost thought was, what a waste of power to employ the ponderous human arm, and all the intricate machinery of the process, in performing an operation so simple, and for which a robin's strength would suffice! Why not draw twelve threads through at once, or fifty? And sometimes, while visiting a shop where army and navy clothing was made, he would look at the heaps of unsewed garments, all cut alike, all requiring the same stitch, the same number of stitches, and the same kind of seam, and say to himself, "What a pity this cannot be done by machinery! It is the very work for a machine to do."

It was not until Howe was four years older, and married, with a family to support upon nine dollars a week, that the pressure of poverty, and the extreme fatigue he suffered by reason of his daily work being too heavy for him, caused his mind to again concentrate itself upon the idea of a sewing machine, which he had heard, four years before, would be an "independent fortune" to the inventor. He wasted many months on a false scent. When he began to experiment, his only thought was to invent a machine which would do what he saw his wife doing when she sewed. He took it for granted that all sewing must be done in this way, and his first device was a needle pointed at both ends, with the eye in the middle, that should be caused to work up and down through the cloth, and carry the thread with it at each thrust.

Howe brooded over this impracticable conception for some time, and cut many a basket of chips in his endeavour to make something that would work such a needle so as to form the common hand stitch, but he

could not accomplish it. One day, in 1844, the thought flashed upon him: Is it necessary that a machine should imitate the performance of the hand; may there not be *another* stitch? This was the crisis of the invention. The idea of using two threads, and forming a stitch by the aid of a shuttle and reciprocating needle, with the eye near the point, soon occurred to him, and he felt that he had invented a sewing machine. It was in the month of October, 1844, that he was able to convince himself, by a rough model of wood and wire, that such a machine as he projected would sew.


The practicability of the invention could not be exhibited or tested except by a machine of steel and iron, with the exactness and finish of a clock, and Howe, who was reduced about this time to the greatest hardships, could not provide even the raw material for such a machine. Fortunately for the poor inventor, however, there was living at Cambridge (U.S.A.) a young friend and schoolmate of former days, a wood and coal merchant, named George Fisher, who had recently inherited some property, and was not disinclined to speculate with some of it. The two friends had been in the habit of conversing together upon the project of a sewing machine. When, therefore, the inventor had reached his final conception in 1844, he succeeded in convincing George Fisher of its feasibility, which led to a kind of partnership between them for bringing the invention out. The terms of this partnership were these:—George Fisher was to receive into his house Elias Howe and his family, board them while Elias was making the machine, give up his garret for a workshop, and provide money for material and tools to the extent of five hundred dollars; in return for which he was to become the proprietor of one-half the

patent, if the machine proved to be worth patenting. Early in December, 1844, Elias Howe moved into the house of George Fisher, set up his shop in the garret, gathered materials about him, and went to work. It was a very small, low garret, but it sufficed for one zealous, brooding workman, who did not wish for gossiping visitors.

All the winter of 1844-45 Howe worked at his machine. His conception of what he intended to produce was so clear and complete that he was little delayed by failures, but worked on with almost as much certainty and steadiness as though he had a model before him. In April he sewed a seam with his machine. In the middle of May, 1845, he had completed his work. In July he sewed by his machine all the seams of two suits of woollen clothes, one suit for Mr. Fisher, and the other for himself, and this sewing outlasted the cloth. This, Howe's original machine, may still be seen at 28, Union Square, New York, and is represented in the frontispiece to this work.

Mr. Howe, like many other inventors, found that when he had completed his machine his difficulties had but begun. After he had brought the machine to the point of making stitches, he went to Boston to get a tailor to come to Cambridge, and arrange some cloth for sewing, and give his opinion as to the quality of the work done by the machine. The comrades of the man to whom he first applied dissuaded him from going, alleging that a sewing machine, if it worked well, must necessarily reduce the whole fraternity of tailors to beggary; and this further proved to be the unchangeable conviction of the tailors for the next ten years. It is quite probable that the machines first made would have been destroyed by violence, but for another fixed

HOWE'S FIRST MACHINE.



opinion of the tailors, which was that no machine could be made that would really answer the purpose.

This machine was then publicly exhibited, and at the Quincy Hall Clothing Manufactory, Mr. Howe challenged five of the swiftest sewers in the establishment to a race with his machine. Ten seams of equal length were prepared, five of which were given to the girls, and the other five were taken in hand by Mr. Howe. The result was that the machine had run up the five seams when the hand sewers were little more than half through with their five. Upon reading testimony like this the wonder is that manufacturers did not at once set Howe at work making sewing machines, but not one was ordered. Not a tailor encouraged him by word or deed. Some objected that the machine did not make the whole garment; others dreaded to encounter the fierce opposition of the journeymen; while not a few really thought it would beggar all hand sewers, and refrained from using it on principle. It was the old story: "We are doing well as we are, and fear to make such a change."

But the inventor was not disheartened by the result of the introduction of the machine. The next step was to get the invention patented; and Howe again shut himself up in George Fisher's garret for three or four months, and made another machine for deposit in the Patent Office. Late in the summer of 1846, the model and documents being ready for the Patent Office, the two partners went to Washington, when the sewing machine was exhibited at a fair, with no result except to amuse the crowd. On September 10th, 1846, the patent was issued, and soon after the young men returned to Cambridge.

George Fisher was now totally discouraged; he had

risked in all about two thousand dollars, and he saw not the remotest probability of the invention becoming profitable. Elias Howe moved back to his father's house, and George Fisher considered his advance in the light of a dead loss.

It now occurred to Howe that since America had rejected the invention, he should offer it to England. In October, 1846, his brother, Amasa B. Howe, with the assistance of their father, took passage in the steerage of a sailing packet, and conveyed one of the machines to London. An Englishman was found who had faith enough in the American sewing machine to invest money in it. In Cheapside, Amasa Howe came upon the shop of a manufacturer of corsets, umbrellas, valises, carpet bags, and shoes, who examined and approved of the machine. But the bargain made on this occasion, through the agency of Amasa B. Howe, was signally bad for the inventor. He sold for two hundred and fifty pounds sterling the machine he had brought with him, and with it the right for the purchaser to use as many others in his own business as he desired. There was also a verbal understanding that this manufacturer was to patent the invention in England, and, if the machine came into use there, he was to pay the inventor three pounds on every machine sold; he further proposed to engage the inventor to adapt the machine to the making of corsets, offering him a salary of three pounds a week, and to defray expenses of material.

Amasa B. Howe returned to Cambridge with this proposal, and America being still insensible to the charms of the sewing machine, Elias Howe accepted the offer, and the brothers set sail for London on February 5th, 1847, where they were soon after joined

by the inventor's wife and family. After eight months of labour Howe succeeded in adapting his machine to the work required, and when this was done his employer required him to do the various repairs, an insult which the American naturally resented, and he was in consequence discharged.

The most painful part of the story of poor Howe now commences. From a chance acquaintance, Charles Inglis, a coachmaker, who proved to be a true friend, he leased a small room for a workshop, in which, after borrowing a few tools, he began to construct his fourth sewing machine. Long before it was completed he saw that he must reduce his expenses or leave the machine unfinished. From three rooms he removed his family to one, and that a small one, in the cheapest part of Surrey. Nor did that economy suffice; and he resolved to send his family home while he could, and trust to the machine on hand for the means to follow them. "Before his wife left London," testifies Mr. Inglis, "he had frequently borrowed money from me in sums of five pounds, and requested me to find him credit for provisions. On the evening of Mrs. Howe's departure, the night was very wet and stormy, and her health being delicate, she was unable to walk to the ship. Howe had no money to pay the cab hire, and he borrowed a few shillings from me to pay it, which he repaid by pledging some of his clothing. Some linen came home from his washerwoman for his wife and children on the day of her departure, but she could not take it with her on account of not having money to pay the woman."

After the departure of his family the solitary inventor was still more severely pinched, but at the expiration of three or four months the machine was finished.



ELIAS HOWE, JUNIOR.

It was worth fifty pounds. The only customer he could find was a working man, who offered five pounds for it if he were granted sufficient time to pay it in. The inventor was obliged to accept this offer. The purchaser gave his note for the five pounds, which Charles Inglis succeeded in selling to another mechanic for four pounds. To pay his debts and his expenses home, Mr. Howe pawned his precious first machine and his letters patent, and again took passage to America, along with his English friend, Charles Inglis.

In April, 1849, Elias Howe, with half-a-crown in his pocket, landed in New York, after an absence of two years. He was obliged to seek employment in the machine shops, which he luckily found without delay. He had no sooner settled to work, however, than the news came to him from Cambridge that his wife was dying of consumption, but he had not the money wherewith to visit her. A few dollars afterwards came from his father, and Howe had time to reach his wife and to see her during her last moments.

The natural gaiety of poor Howe's disposition was now quite quenched by the severity of his many trials, and he appeared exceedingly downcast and worn. Soon after this, as a crowning misfortune, came the intelligence that the ship in which he had embarked all his household goods had been wrecked off Cape Cod, and was a total loss.

From this point, which may be considered the lowest depth of Howe's misfortunes, he received help from his friends, and he soon discovered that his first machine on the shuttle principle was being imitated and sold about America, and that while he resided in London several ingenious mechanics had turned their attention to the making of sewing machines.

Howe now prevailed upon a capitalist to join him in defending his rights, and many lawsuits followed, the outcome of which was that Howe was acknowledged to be the first inventor of the shuttle sewing machine. Shortly afterwards he was established in New York as a manufacturer of sewing machines, and in a few years, having bought up the remainder of his patent, was the worthy recipient of a princely revenue derived from their sale. In the year 1867 he was decorated with the Cross of the Legion of Honour by France, but he did not long enjoy the honours and rewards which his invention had brought him, for on the 3rd of October, 1867, Elias Howe died at Brooklyn, New York, to the deep regret of his innumerable friends, who not only honoured him as the inventor of the sewing machine, but also for the many excellent personal characteristics he possessed.

Allen B. Wilson, the inventor of the rotating hook lock-stitch machine, was born in the year 1827, and became, at twenty years of age, a journeyman cabinet-maker in Adrian, Michigan. In 1847 Wilson conceived the notion of a sewing machine, and had some definite ideas as to the means by which the apparatus should work. The inventor's own words graphically describe his position at this time, and the difficulties under which he laboured.

"I was in needy circumstances, earning but little more than enough to board and clothe me. I was taken sick early in the spring of 1847, with fever and ague, which greatly reduced me; I have never fully recovered from it." The inventor then goes on to describe his difficulties in attempting to put his ideas into the form of a sewing machine, and after enduring great privation we find him at Willitt,

Courtland Co., New York. "I remained there until May, 1848, working while able, and giving much thought to my sewing machine, which I was then very desirous of building. I then went to work in a cotton-mill at Homer, and got money enough to reach New York City on the 15th of June, 1848, destitute and a stranger. . . . Not being able to do hard work, and being destitute of the means of living, I hired out as a cook on a coasting sloop running on the Long Island Sound. . . . I left the sloop at Providence, and worked there a few weeks. I then went to Boston, where I worked a few weeks more, by which I was enabled to save about twelve dollars. I went to Pittsfield the last of August, 1848, and hired out the same day to Barnes and Goodrich, cabinet-makers. As the fall was approaching, it occurred to me that as the evenings became longer, if I could only get the evenings to myself, I would have time to make the sewing machine, the plan of which I had so long in my mind.

"No favourable opportunity occurred until I went to work for Mr. Barnes individually, which was about Feb. 1st, 1849, when it was specially agreed that I should have the evenings to myself, and a right to work in the shop in the evenings for myself. I had previously, as early as November, 1848, made full drawings of all the parts of my projected sewing machine, and shown them to two or three of my most intimate friends. . . . They laughed at me, and I concluded not to say anything more about it until it was done. I began the construction of a working machine almost the first evening I worked for Mr. Barnes, and completed it about the 1st of April, 1849.

"Not being a machinist by trade, and having no means wherewith to procure the assistance of machinists,

it was necessarily of rude and imperfect construction,



ALLEN B. WILSON, INVENTOR OF ROTATING-HOOK SEWING MACHINES.

and did not illustrate in the best manner the principle and mode of operation involved in my invention ; but,

notwithstanding its imperfections, it had made garments of various kinds, and had been exhibited to many persons.

“Up to this time I had never seen or heard of a sewing machine other than my own. In May, 1849, I moved to North Adams, Mass., and built a second and better machine of the same kind. I received no encouragement or assistance, however, but, on the contrary, discouragement and ridicule; and as I had no money, it became a serious question how I should obtain letters patent for my invention. At last I induced Joseph N. Chapin, of North Adams, to purchase one-half interest in the invention for two hundred dollars. This was the best I could do. I spent all that, and about two hundred dollars more, in procuring the patent, which was dated November 12th, 1850.”

Mr. Wilson then records how he and Mr. Chapin fell into the hands of New York swindlers, who, pretending to have a right to some parts of the invention, induced the partners to make over to them half the patent, to avoid ruinous legal proceedings. This was done, but the hollowness of the claims of the persons mentioned became in a month or two so obvious, that Messrs. Wilson and Chapin were enabled to free their property, which was, after much trouble, put into the hands of a small party of commercial men, who ultimately did Mr. Wilson justice, and founded the Wheeler and Wilson Sewing Machine Company.

The first machine brought out by Wilson operated by means of a two-pointed shuttle, and a feeding device of the most ingenious description. The Howe machine at first operated by means of a “baster plate,” in which were inserted a series of pins, upon the points of which the cloth was fastened. This plate was moved forward

at each stitch to form the feed, as shown in the frontispiece. (See description, p. 27.) Mr. Wilson arranged his machine so that the material could be pressed upon the cloth plate by a spring foot, and added to the stitching mechanism a feeding apparatus which has four motions, and carries the cloth in any required direction, so that the seam may be straight or curved at will. The basis of all modern feeding mechanism, upon which so much depends, is thus due to Allen B. Wilson.

But by far the most wonderful invention in the construction of sewing machines is Wilson's Rotating Hook, which he applied to his machine shortly after its introduction. This device, which is explained at p. 46, performs the functions of a shuttle by seizing the upper thread, and throwing its loop over a circular bobbin containing the under thread. The motion is continually in one direction, and the reciprocating movements of the shuttle entirely avoided. A further development of the same invention, which is exhibited and explained at p. 55, has been made by Mr. House, in the employment of the Wheeler and Wilson Company.

James E. A. Gibbs, the inventor of the *Single-thread Rotating-Hook Machine*, has kindly furnished the author with the following account of this ingenious invention:—"My attention was first called to the subject of sewing machines in the year 1855, by seeing a plain woodcut of a Grover and Baker machine in a newspaper advertisement, and being of a mechanical turn of mind, it at once excited my curiosity to know how it could possibly sew. As I was then living in a very out-of-the-way place (Pocahontas Co., Virginia, U.S.), far from railroads and public conveyances of all kinds, modern improvements seldom reached our locality, and not being likely to have my curiosity satisfied other-

wise, I set to work to see what I could learn from the woodcut, which was not accompanied by any description.

"I first discovered that the needle was attached to a needle arm, and consequently could not pass entirely through the material, but must retreat through the same hole by which it entered. From this I saw that it could not make a stitch similar to hand work, but must have some other mode of fastening the thread underneath, and among other possible modes of doing this, the chain stitch occurred to me as a likely means of accomplishing the end.

"I next endeavoured to discover how this stitch was or could be made, and from the woodcut I saw that the driving shaft, which had the driving wheel on the outer end, passed along under the cloth plate of the machine. I knew that the mechanism which operated on the stitch must be connected with, and actuated by, this driving shaft. After studying the position and relations of the needle and shaft with each other, I conceived the idea of a revolving hook on the end of the shaft, which might take hold of the thread, and manipulate it into a chain stitch. My ideas were, of course, very rude and indefinite, but it will be seen that I then had the correct conception of the invention afterwards embodied in my machine.

"Having no further interest in view than to satisfy my curiosity how sewing by machinery could be done, and caring little whether I had the correct idea or not, I gave the matter no further attention or thought until during the month of January, 1856. At this time, while on a visit to my father in Rockbridge Co., Virginia, I happened to go into a tailor's shop where there was a Singer's sewing machine working on the lock-stitch shuttle principle. I was very favourably impressed

with its utility, which was far beyond my previous impressions of the development of the art, but at the same time I considered the machine entirely too heavy, complicated, and cumbersome, and also that the price was exorbitant. These considerations led me to apply myself to inventing and producing a more simple, cheap, and useful machine. As soon as I reached home in Pocahontas Co. I began to apply my mind to this subject. I first made a small imperfect hook on the end of a piece of wire, by which I demonstrated that the chain stitch could be made by a hook revolving on the end of a driving shaft, and first thought of making a machine in this way, but after producing some samples of a chain stitch and testing them, I became dissatisfied with the stitch, and also still labouring under the delusion that probably the Grover and Baker machine was constructed in that way, I concluded to turn my attention to the lock stitch, and made a rude model out of wood of a shuttle lock-stitch machine. My family was at this time dependent upon my daily labour for support, so that I had very little time to spare for my experiments, working only at nights and in bad weather. I also laboured under great disadvantages for want of tools and materials, having to make my own needles, and constructing my shuttles of wood, as I was then a carpenter only. By the 1st of April, 1856, I had completed my model, and succeeded in interesting my employers in my invention so far as to induce them to furnish the capital wherewith to take out letters patent and develop the machine. During the month of August of the same year I came to Washington to take out my letters patent, and while there I examined the models in the office, and also some of the machines then in the market.

"I ultimately fell back upon my old idea of a single-thread machine with greater confidence in its success, but while making the first one, the idea occurred to me to make the hook stationary, and to vibrate the needle instead. This needle, however, I found to be already in use by others, and I finally produced a sewing machine with a rotating hook or looper, and a needle having a vertical motion only." With the assistance of Mr. Ruckman, this machine was at first manufactured by the firm of Emory, Haughton & Co., of Boston.

Mr. Gibbs is the inventor of several improvements in sewing machines, but the final outcome has been the Willcox and Gibbs machine, described at p. 74.

Several other kinds of stitches form the subjects of independent inventions, but the limits of this treatise preclude the giving of fuller historical particulars. Those mentioned may be accepted as the only stitches used for general purposes—the double-chain stitch, mentioned at p. 152, being now almost obsolete. We have, therefore, two distinct stitches, one of which is formed by means of interlooping a single thread beneath the fabric, and the other by interweaving with a second thread, also beneath the cloth.

Each of these stitches possesses certain advantages for given kinds of work. The single-thread, or, as it is generally termed, the chain stitch, is elastic, and seldom gives way when the fabric is wetted; when made with a good and suitable class of thread, it lies close to the under side of the fabric, and is not liable to injury by friction. When the seam is worked with the thread at a considerable tension, it does not tend to unravel, even if broken at several points. In addition to these advantages a single-thread seam is pre-eminently suited to those classes of goods which ladies

frequently take to pieces for reshaping or other purposes, because the seams are readily removed by releasing the finishing end and drawing out the thread in one continuous length. The lock stitch, made by the shuttle or by the rotating hook, is essentially an elastic stitch, and, like the chain stitch, withstands the contracting effects of water when the tension has been properly adjusted. It lies close to the fabric upon either side, and possesses great strength. The tendency to unravel when broken at several points of a seam depends to a considerable extent upon the kind of fabric; an inelastic fabric, in which the needle-holes exhibit no tendency to close, brings out all the defects of this and every other system of sewing. A great deal depends upon the accuracy with which the interlocking point has been adjusted to fall in the centre of the goods. In a woollen fabric the lock stitch does not tend to unravel even if broken at several points.

It is difficult to draw a comparison between machine and hand-stitching. Hand work is always irregular, no matter how well performed, and is constantly subjected to strains at particular points, while the machine work, being regular, receives the strain upon larger portions of the seam and suffers less. Lock-stitching is undoubtedly better adapted for ordinary work than hand-stitching, but good hand work stands wear and tear better than the single-thread stitch made by machine, and usually wears better than lock-stitching carelessly and loosely performed. These stitches are described more fully in the following chapter.

CHAPTER II.

THE ELEMENTS OF STITCHING MECHANISM.

THE essential elements of a sewing machine, judging from the modern types of construction, consist of—

1st. A needle, having its eye near to its point, carrying a bight of thread into and through the cloth.

2nd. A mechanical device beneath the cloth by means of which the thread may, while under the material, be manipulated so as to make a chain, loop, or stitch, or interwoven with a second and under thread to form what is known as the lock stitch.

3rd. A mechanical device above or beneath the fabric known as a “feeder,” by means of which the cloth may be moved forward the required distance on the completion of each stitch.

In addition to these indispensable elementary conditions, a flat horizontal cloth plate is provided, through an aperture in which the needle works vertically, while through a second aperture the feeder, if an under one, must act upon the fabric being sewn.

Formation of Machine Stitches.—To form the single-thread or chain stitch referred to, a “looper” is employed, the action of which may be vibrations in a given arc, or rotation continuously in one direction.

To form the double-thread or lock stitch as above,

a shuttle charged with thread is employed, or a rotating hook is designed to take its place by throwing the upper thread in a loop over a bobbin of the under thread.

In the single-thread chain stitch the action is as nearly as possible as follows:—The needle descends through the fabric, carrying a bight of the thread with it, and the point of the looper begins to vibrate or revolve towards the descending needle. When the needle has reached the extremity of its down stroke it begins to rise, and the immediate result is that a loop of the previously tight thread bight is thrown out from the side of the needle, sufficiently large to allow the rapidly approaching looper to enter it. The needle now rises up through the fabric, beneath which the looper detains the upper thread. If the looper be of the vibrating kind, its action is simply to retain the loop, and to expand it over the path of the needle when it next descends. In this way a fresh loop is secured while the eye of the needle is below the preceding loop; the usual chain is the result, the first loop being tightly drawn up to the cloth while the looper is in the act of expanding its successor. If the looper be of the rotating description, its action is substantially the same, but a complete twist is given to the loop in the process of expanding. This twisted loop possesses certain advantages over the untwisted loop just mentioned.

To form a lock stitch, the needle descends as before, and in rising throws out from its side a slack loop in the same way. If, now, the machine be a shuttle one, the shuttle, which has a reciprocating motion imparted to it across the path of the needle, approaches its point, enters the loop referred to, and expands it while

the needle rises, passing quite through it, by reason of its being virtually disconnected with its carriage. The stitch is complete when the needle has risen to its highest point, and the upper thread is locked with the under thread in the centre of the cloth (Fig. 1). If the machine be a rotating-hook one, the same loop is thrown out and seized by the point of a peculiarly shaped hook, which in the progress of its revolution carries it over and around a cymbal-shaped bobbin containing the under thread. In the most recent form of this machine the loop is cast off the hook and pulled up into the material, completing the stitch.

The chain stitch has a plain regular appearance on the upper side of the fabric, while it resembles a chain on the under side.



Fig. 1.—THE LOCK STITCH.

The lock stitch has a plain and regular appearance alike on both sides of the fabric, the interlocking point being in the body of the goods.

Machine Needles.—Thus the action of all sewing machines depends entirely upon the loop thrown out by the needle when it begins to rise from its lowest point. To facilitate the formation of this loop on one side of the needle only, the latter, on the side turned away from the shuttle, has a long and deep groove, wherein the thread lies almost free from friction, and the loop side is plain excepting a short groove made near to the eye. All sewing-machine needles have necessarily a shank or stout stem by which they are secured in the movable arm of the machine, and are made pointed with a uniform thickness throughout the portion passed through the cloth. For ordinary sewing the needles are pointed as in hand needles, but for leather they

are given a chisel-shaped point, the more readily to cut their way through it: the same points are frequently turned at an angle to the line of the eye, which has certain advantages for some classes of work. Machine needles are either straight or curved; the curved needles are used in needle arms vibrating in arcs.

Feeding Mechanism.—The automatic feeding of the material comes next in importance to the making of the stitch.

In the first forms of the sewing machine (*see frontispiece*) the cloth was fastened upon pointed pins projecting from a "baster plate" or feeder, which was moved forward after each stitch, carrying the cloth with it under the needle. As this movement was quite positive, the fabric could not be turned about to any considerable extent to form curved seams of stitching, and the device necessarily impeded the progress of the sewing machine when first introduced. Later on the idea of feeding by means of a vibrating needle was tried, and finally the present form of feed was invented.

In some of the first machines fitted with the "four-motion" feed, as it is termed, the material was moved forward by a serrated spring foot pressing upon it from above. This foot had four motions, two of which were positive. It first fell upon the fabric with pressure, and then pulled it away from the operator the required distance at each stitch; the other two motions were given by springs. This is called a "top feed," and is even yet applied to more than one type of sewing machine.

The four-motion feed is, however, more advantageously applied to work the fabric forward from

underneath the cloth plate, pressure being continuously applied from above. Two of the motions are always positive, and in most instances the fall and draw-back motions are given by springs. The feed, in operation, first rises and sets its teeth into or against the fabric pressed against the cloth plate from above. It then moves forward from or to the right of the operator, carrying the cloth with it, when the teeth fall below the level of the plate and the feed bar finally draws back for a fresh stitch. The length of the stitch can be regulated to a nicety by extending or curtailing the backward movement of the feeding surface.

By means of this most ingenious device (Historical Sketch, p. 14), the cloth is free to be turned upon the needle as a centre to any required angle, and the work may with the utmost ease be sewed in curved or straight lines while the machine is in motion. In addition to these advantages of the four-motion feeder, its progressive motion is in a straight line, and work may therefore be sewed in perfectly straight lines without much guidance from the hand, while it is at the same time quite free to receive other motions at will.

In some forms of the sewing machine a feed wheel, with serrated periphery, is employed. This edge projects slightly above the level of the cloth plate from beneath, and the fabric is kept pressed upon it as usual by a spring foot. The wheel feeder is then caused to revolve a given distance at each stitch. This device is well suited for leather stitching, although the four-motion feed has to a great extent taken its place in this application.

Minor Parts of the Sewing Machine.—Among the minor devices used in conjunction with the sewing machine spoken of, may be mentioned the *tension*

wheel, which is so arranged that the upper thread may by its movements be kept in the strained condition necessary for tight stitching. Tension may be, and is, put upon the upper thread in a variety of different ways, and is usually adjustable at will. The *take-up* is a device applied to most lock-stitch machines. Its function is to pull up the loop as soon as it has been passed over the under thread receptacle—shuttle or spool.

The *presser* foot is merely a device for keeping a constant or intermittent elastic pressure upon the fabric while being sewn. It usually covers about a square inch, and the needle in most instances plays through it. The presser is placed so as to cover the area occupied by the feed surface when moving the stitch forward. The degree of pressure is usually adjustable at pleasure, and the foot may be raised when required to commence or finish stitching. The main overhanging arm of the sewing machine, from which the needle operates vertically upon the fabric, carries also the presser bar, spring, and foot. In the machine illustrated at p. 38 the needle arm is separate from the presser arm, and vibrates as a whole.

The *upper thread* is usually wound off the ordinary wooden spool, which is placed upon a pin where it revolves freely, or the thread is wound off the spool without causing the latter to rotate.

The *under thread*, on the other hand, as used in lock-stitch machines, is in most instances wound off the ordinary wooden spool on to a small metallic reel to be fixed in the shuttle, or into a disc-like spool for use in hook machines. Ready-wound "copes" of under thread are sometimes used in shuttles. Motion is given to all the parts of the machine from one point. The

power is usually treadle or hand motion, and steam in manufacturing houses where great numbers of machines are at work at once. All the parts of the machine are usually actuated off one shaft, and one revolution of the shaft generally completes one stitch.

Stands and Treadles.—These are so common, and their construction so easily comprehended, that no space need be devoted to a consideration of them here.

CHAPTER III.

SHUTTLE SEWING MACHINES.

THE sewing machine in its first form, as invented by Elias Howe, made the lock stitch by means of a shuttle, as explained in the chapter treating of the elements of stitching mechanism. The Howe machine of to-day is, however, only one of the numerous developments of the original invention. A great number of makers produce shuttle machines differing in construction from Howe's, but as the principle upon which all these machines work is the same, and as the Howe is a noteworthy example of a first-class powerful sewing machine, possessing all advantages, the section on Shuttle Machines is almost exclusively confined to a description of it. This manner of treating the subject is also in accordance with the history of the sewing machine.

The Howe Shuttle Machine.—In the frontispiece to this volume the reader is presented with a general view of the first sewing machine, as invented and made by Elias Howe (History, p. 6). The shuttle machine of to-day has a very different appearance, and varies in construction; but a short description of the first sewing machine may not be uninteresting, as exhibiting the progress which has been made of late years in stitching mechanism. Referring to the frontispiece, it will be

observed that the machine is built upon a firm base, A, which carries a strong angular overhanging arm, B. Through the side and free extremity of this arm works a shaft, c, to which is attached the fly-wheel, D, driven by hand at E. The thread for the top stitch is taken continuously from the reel, F, and fed to the curved needle, a, through a spring, b. The needle works through the cloth at c. The latter is carried upon pins, d. The needle arm, g, and the baster or feed plate, H, work so that the plate moves the cloth forward one stage at the completion of each stitch. The shuttle is driven by a driving rod, J, which is caused to vibrate backwards and forwards by means of the cam, L. The cam, l, screwed upon the sleeve, q, actuates the lever, P, which action gives a rocking motion to the short shaft, o, and the needle arm, on being connected to this, vibrates, carrying the needle into and out of the cloth at each revolution of the hand wheel.

Such is the sewing machine produced by Elias Howe when he lodged in the house of George Fisher (History, p. 5). The construction and arrangement of the various parts bear a very strong resemblance to the shuttle machine of to-day, but the inconvenient position of the needle arm is, of course, changed. The model as it stands shows that Howe had in his mind all the essential elements of a sewing machine.

A Howe machine of approved construction, to which the following description refers, is built upon a firm cast-iron base. To this base the overhanging arm of the machine is bolted. The under parts claim attention first, because they give motion to the needle arm, which is above the base, and to the shuttle arm, which is beneath the base, as exhibited in Fig. 2, which shows the machine tilted up so as to expose the

working arrangements. Two castings, or hangers, are carried down from the base, in which works




Fig. 2.—THE HOWE MACHINE—UNDER PARTS.

the main shaft, upon the end of which is fixed the driving wheel as shown. The actuating cams, of peculiar shape, which revolve with the shaft, and give a

reciprocating motion to the needle and shuttle levers respectively, are shown screwed to the shaft. The needle lever is pivoted at the angle of the fixed arm as shown, and upon its extremity, revolving in the right-hand cam, a steel friction roller works.

The shuttle lever is pivoted upon a stud, and kept




Fig. 3.—HOWE MACHINE—IN WORKING POSITION.

in position by a washer and pin. Its shorter arm is also fitted with a friction roller; its longest end engages with and drives the shuttle carrier through the angle link shown behind the feed wheel.

The form of feeding apparatus employed consists, as

will be observed, of a wheel with serrated periphery, marked 162. This wheel feeder is actuated by a pair of clutches, 172, hinged upon the hub, and acting against the antagonistic spring, 173. A lever, 159, rides upon the feed cam, 182, and communicates motion to the feed clutches. The feed wheel, which projects slightly above the cloth plate, is thus caused to move forward a short distance during each revolution of the shaft. The cam, 182, is tapered in form, for the purpose of adjusting the stitch, or throw, to the length required. This is effected by screwing or unscrewing the thumb nut, 184, which causes the cam to advance to, or recede from, the rider, 159. The rider is constantly urged against the cam by the antagonistic spring, 170.

A great number of the Howe machines are fitted with the four-motion feeder, modified from the original invention referred to in Chapter I.

The disposition of the various parts will be understood by reference to Fig. 3. The needle arm, as will be seen, engages with the needle bar, 40, behind the head of the fixed arm. The serrated surface of the feed is shown at 92, and the presser foot, turned aside out of the way, at 102. Nos. 112 and 113 show slide plates, which cover the shuttle race and shuttle, to be further explained. The tension wheel, 119, is of peculiar construction. It is shown full size in Fig. 4, where the thread is first observed to be passed into a spring thread guide, 124, where it is gently clasped to make it retain hold upon the pulley. The projection, 118, serves the same purpose.

Fig. 5 exhibits the tension wheel removed from its stud, 126. Behind the wheel, at 126, is placed a thick felt washer, and over it and under the metallic washer,

122, another felt disc. The thumb nut, 128, serves to adjust the pressure upon the wheel, and consequently the degree of tension put upon the thread.

Returning now to Fig. 3, the course of the upper thread may be noted. A is a spool of thread, placed so as to run freely upon the spool pin, 5. The thread




Fig. 4.—“THREADING THE TENSION.”

is then passed around the tension wheel and under the thread controller, 19, over the top of the needle bar, 40, and in the catch of the take-up lever, 32, which is constantly pulled against the thread by an antagonistic spring. It next passes through the groove, 42, and the lower thread guide, 44, to the needle eye as shown.

A back view of the top of the needle and presser

bars is given in Fig. 6. The lever projecting to the right is the presser raising and swivel handle, which,




Fig. 5.—TENSION WHEEL APART.

by means of a cam acting upon the lifter plate, 58, raises the bar against a spring. The steel plate, 17, adjustable by the screw, 18, serves to take up any wear




Fig. 6.—UPPER EXTREMITY OF NEEDLE AND PRESSER BARS.

of the plate, 58, and to prevent the presser foot from swerving.

Fig. 7 exhibits the shuttle race and the shuttle, 61,




Fig. 7.—HOWE MACHINE—THE LOOP MADE.

in position when about to enter the loop made by the rise of the needle.

The motion given by the cam to the needle bar is not simply an up and down movement. When the needle descends to its lowest point, it rises a little way, sufficient to throw out the loop shown, and then *pauses* until the shuttle has passed through the loop, when it ascends.

The shuttle driver, 85, is screwed to the driver slide, 84. The race in which the shuttle moves is planed out, and the contact faces are quite flat and smooth. 25 shows a screw by means of which the pressure upon the presser foot may be increased or diminished at will; 27 and 28 are respectively an adjusting cam and a set nut. It is necessary that the needle should play as near




Fig. 8.—HOWE SHUTTLE—PLAIN HEEL.

as possible to the shuttle without touching it, and for this purpose the small cam, 27, may be turned so as to bring the needle out into the race, or cause it to recede into its groove.

The actual appearance of the needle and the end of the needle bar is shown to the left of Fig. 7, where 41 is the needle-set screw, and 45 the set screw of the thread guide, 44.

Fig. 8 exhibits the shuttle, without the driving heel, removed from the race, with the bobbin latch raised to admit a wound reel of the under thread. From the bobbin, when in its place and the latch closed down upon it, the thread is passed into the catch cut in the

latch, and from this point is threaded around and under the tension plate, and out by the hole nearest to the point. All parts of the shuttle and driver are made very smooth, so as not to chafe the thread in passing over them. The driver fits the heel of the shuttle very loosely, to allow the thread to escape easily. Shuttle




Fig. 9.—WINDING THE BOBBIN.

drivers are made to act in a great many different ways, but the result is the same. The way in which the stitch is made is explained in the Elements, at p. 20.

Shuttles are made of different forms to suit the construction of the machine. They are usually of steel, highly polished. The face must be quite flat. Shuttle reels

are sometimes dispensed with in Singer machines by using ready-wound "copes" of under thread. A reel winder is attached to the treadle-wheel motion or table of every shuttle machine, by which the thread may be regularly wound on the bobbins as exhibited in Fig. 9. When the bobbin does not play easily in the shuttle, its steel spindle is pointed at either end, and revolves between a spring centre and the heel of the shuttle. In the Singer machine a "loose wheel" arrangement is employed, by which the machine itself is inactive when winding the reels for bobbins.

The work in most shuttle machines is fed *from* the operator. Wheel feeds are common. A great number of attachments, enabling the machine to do every description of sewing, are applicable to the machine, but cannot be mentioned in detail here. The more important are Hemmers, Tuckers, Binders, Braiders, Corders, Trimmers, Kilters, and guides of various kinds.

CHAPTER IV.

DESCRIPTIONS OF ROTATING-HOOK MACHINES.

THE machines introduced and manufactured by the Wheeler and Wilson Sewing Machine Company present the best examples of the rotary-hook lock-stitch type. The rotating hook has of late been applied to machines of various patterns, but the action is the same throughout.

Fig. 10 exhibits a No. 1 Wheeler and Wilson machine of approved construction for the lighter classes of work, details of which are given further on. The various parts included in this general view are indicated by numbers. 1 is the cloth plate, forming a platform upon which the work is fed under the presser foot, 2. This presser foot is provided with a glass body, through which the progress of fine stitching may be observed. The pressure is adjusted by a spiral spring upon its piston, which is fastened in position by the thumb screw, 3. 4 is the lifting lever used when the presser is to be raised. 9 exhibits the clamp by which the curved needle is made fast to the extremity of the needle arm, and through which is pierced an eyelet, 5, for the thread, as shown. 11 shows the tension pulley, and 13 the volute spring. The former is a metallic wheel with a narrow groove, around which

the upper thread takes one turn: the pulley is thus caused to revolve by the thread, and the tension upon the latter depends upon the pressure applied to the spring, 13, by the thumb nut. 12 is a spring thread guide, through which the thread passes. It contains a pair of steel discs clamping the thread, and pressed together by a small spiral spring. Motion is communicated, from an eccentric beneath, to the needle




Fig. 10.—HIGH BED ROTATING-HOOK MACHINE.

arm through the joint, called the hinge, bolted to the rocking bar, which plays between a pair of pivots as shown. The hook spindle, 10, is used for the purpose of revolving the metallic spools for the under cotton in the operation of winding. The whole machine is built upon a firm casting, which is screwed to the table of the stand, and driven from the treadle power by a strap as usual.

Fig. 11 is a general view of the same machine with

the cloth plate removed. 3 is the leather-covered pulley, or "drum," through which motion is given to the feed hook and needle arm. 5 shows the feed frame in position in the main frame, and 6 its point and teeth, which feed the cloth under the presser foot. At 7 is a spiral spring continuously pulling the feed points towards the cam cut upon the pulley, 3. 8 is the edge of the rotating hook, in the cavity of which is revolved the under thread bobbin or spool, 1. 2 is




Fig. 11.—THE CLOTH PLATE REMOVED.

the brush segment, the office of which is to hold a small brush loop check against the side of the revolving hook. At 10 is shown the ring slide or "spool ring," which serves to retain the spool loosely in its place. This ring slide is adjustable, and is fastened to the frame by the set screw, 11. In the engraving before us the slide ring is of the hinged type, which is more fully illustrated by Fig. 12. The ring, *a*, is hinged as shown to an adjustable seat, set by the

screw, *c*. The ring, when in position for sewing, as in Fig. 11, is retained by a snap spring, which is pressed




Fig. 12.—THE HINGED BOBBIN HOLDER.

out of action when it is required to remove the spool by a finger lever, *b*, Fig. 12.

Fig. 13 exhibits the cloth plate removed and




Fig. 13.—UNDER SIDE OF CLOTH PLATE.

reversed. 35 shows the needle plate, through which also work the feed teeth. This small plate is removable by drawing it out longitudinally. Two sizes of needle

plate are used, one for fine and the other for coarse work. 57 is a wire under which the spool thread is usually passed in commencing work, which prevents the end from getting entangled in the hook. 54 is an eccentric cam, working upon the stud, 55. Its function is to




Fig. 14.—Old Style of Feed Bar—in Machine.

regulate the length of the stitch by butting against the feed bar, the old style of which is shown in Figs. 14 and 15.

Fig. 14 explains the under motion of the eccentric and feed cam. 8 is the eccentric band giving motion



Fig. 15.—Feed Bar removed from Machine.

to the needle arm. 7 is the driving strap. 6 shows the feed cam, which actuates the feed bar, 10, by bearing upon the abutment, 11. The spiral spring pressing the feed up to the cam is shown in position at 12. The feed bar works freely in seats cut in the main frame. The feed tongue, 13, Fig. 15, is hinged to

the bars, and works up and down freely between them. The teeth are cut upon the free end, 14. This feed tongue is raised by the same cam block used for giving the feed movement, but the necessary eccentric form is cut upon the periphery of the casting.

This feed is a most ingenious one, and has four motions. First, the feed tongue rises and presses its points into the cloth, then the whole feed frame moves forward the length required, carrying the cloth with




Fig. 16.—DRAW FEED MOTION.

it; the tongue then drops, and the feed bar finally draws back for a fresh movement. All these motions are repeated for every stitch taken by the machine. The points, 14, are hardened to withstand wear and tear.

Fig. 16 illustrates the more modern feed, known as the "draw feed." In this form the frame is square, and has no drop tongue. The entire frame moves at the forward end with the four changes necessary. At

122 is shown a spiral spring, which not only pulls the feed back, but tends to press its rear end upwards against the plate: at the point where the feed touches the plate we may imagine a kind of fulcrum or hinge action when the feed point is raised or depressed.

At Fig. 17 is shown the feed removed from the frame. At 11 is exhibited an improved feed point of fine steel, which is so made as to surround the needle and give great power and accuracy in feeding; it is screwed to the end, 14, of the feed frame by one screw. Two screws are here shown; the use of the second screw is to raise the feed point as the bearing piece, hinged below, wears away. This form of feed bears




Fig. 17.—DRAW FEED BAR.

upon the throw cam with a pad of leather to reduce noise; a similar pad is used at the regulation end of all these feeds. The motion of this "draw feed" is the same in effect as that of the bar feed. It is better adapted for feeding thin and soft goods, and works with less noise.

In the newer form of feed cam, as shown at 6, Fig. 16, the feed is raised, not by a cam cut at 6, but upon the hub, marked 4 in Fig. 13.

Before proceeding to an explanation of the action of this machine in making stitches, reference to Plate I. will render clear the form of the different parts of which the machine is made up. The brush used in checking the loops, and the action of which has

yet to be explained, is shown at 3 *d*, and its "segment," or holder, at 3 *a*. At 14 is exhibited the eccentric cut upon the main pulley; 21 shows the corresponding eccentric ring and rod for transmitting motion to the needle arm, which is exhibited at 45. The hook, 42, passes its spindle through the pulley. The thread bobbin, or spool, 4, lies in the cavity of the hook, and is controlled by the slide ring, 5. 1 shows the presser arm, which is screwed firmly to the frame, and through the end of which works the presser-foot piston, 54 *b*, actuated by the spiral spring, 56. The hinge lever, 64, connects the end of the eccentric rod and the rocking bar of the needle arm together. 27 is the feed frame, as already described, with its point, 32, removed; 28 and 33 are the leather stops previously referred to; 30 the bearing block, against which the raising cam acts in raising the feed. This part is hinged at the end of the feed, and is adjusted by the screw, 35, while the screw, 34, serves to fasten down the point. At 29 is exhibited the spiral spring which draws back and regulates the motion of the feed. 48 is the needle yoke, with its nut, 49; this part clamps the curved needle, 50, to the arm. 19 and 55 are the presser lifter and raising collet respectively; the collet is screwed upon the upper end of the presser spindle by the thumb screw, 57. At 71 is shown the tension pulley, which runs upon the stud, 72. 76 is the volute spring, which is regulated by the nut, 73. 77 shows the spring thread guide, previously referred to, removed from the needle arm. At 46 is shown the shape of the pivot or needle-arm screw, upon which the arm moves; this screw is locked in position by the lock nut, 47. The spool wire, upon which the reel of thread is placed, is shown at 68. The disc




PLATE I.

marked 15 screws to the end of the eccentric after it has been passed through its ring, to prevent shifting. 38 indicates the shape of the glass foot used in these machines. The various screws are also shown.

Having thus far paved the way towards an intelligent understanding of the construction of these machines, we may pass on to an examination of the action of that beautiful piece of sewing mechanism, the rotating hook.

Fig. 18 is a view of the face of the hook used in this




Fig. 18.—THE ROTATING HOOK.

form of machine. The needle is represented as passed downwards through the cloth. Let us suppose the needle to be at its highest point, and the thread placed upon the machine and passed through the needle eye, which is pierced near to its point. The disc-like spool containing the under thread is to be in position in the hook cavity, and the ring placed in front of it to keep it there, although loosely.

Pulling a little thread from the under spool, we move the machine slowly forward. The needle descends, carrying the upper thread with it, and passes through the cloth down to the rotating hook. After it reaches its lowest point it begins to rise again, and in doing so, the thread stretched upon its side next to the hook point slackens and begins to form a "loop," 5, as shown in the engraving. The hook, meantime, has been revolving to meet the needle, and when the latter has risen to the extent shown, the hook point is ready to enter the loop. Further rotation causes the needle to rise, and the hook to pull out and expand upon itself the loop; in doing this it draws the left side of the loop behind the spool, and a little further motion causes the loop to slip off the hook at the chamfered portion, shown at the bottom of the engraving. The result is that the loop is now passed fully over the spool, and is pulled forward with the friction until it is checked by the brush, 3, in its holder, 36. At this point the loop remains until the hook has seized a new loop, when further rotation brings the chamfered part referred to opposite to the brush, and the loop is both relieved and drawn up into the cloth by the expansion of its successor. When the loop slips off the hook, to pass over the spool, the needle eye is just entering the cloth, so that the strain upon the upper thread is lessened at this point.

The motion of the hook is accurately timed to that of the needle, and the loop referred to is always formed before the hook point moves past the needle. The under thread is, of course, caught up at each stitch by the spool being encircled, and is pulled up into the cloth to make the lock stitch. There is always a gentle tension on the under thread, due to its holder revolving

in a direction opposite to the movement of the rotating hook. During these motions the feed moves the cloth forward the length of one stitch at every rise of the needle. The action of the rotating hook is, practically, throwing the upper thread over the under one, which is analogous to the passage of a shuttle through the loop. The hook is made from steel, and is very highly and smoothly finished off, to prevent injury to the thread by cutting or chafing.

The action of Wilson's rotating hook is somewhat




Fig. 19.—THE STRAIGHT-NEEDLE MACHINE.

difficult to render clear by word description. The point seizes each loop with unerring accuracy at lightning speed, whirls it over the spool, leaves it upon the brush, and pulls it into the cloth with inconceivable rapidity, and yet not even the finest threads are chafed or broken by it. Even at the prodigious speed of 2,500 revolutions a minute, when the time occupied in making one stitch is a mere fraction of a second, the resulting stitches are perfect, and no break

or miss is apparent in a run of any length. The feed likewise acts to perfection, and so accurate is the stroke that all the stitches are of the same length.

In the later forms of the rotating hook its cavity is




FIG. 20.—THE NO. 6 MACHINE.

made much deeper, to accommodate a wider spool containing a large supply of under thread. The brush check is also done away with in the larger machines,

and an automatic "take-up," to be described further on, completes one stitch before another is begun.

Fig. 19 represents the same type of sewing machine, but fitted with a straight instead of a curved needle. The positions of all the parts are the same as in the machine just described, and the additions consist of a needle bar and a link to connect the needle arm to it. This machine is adapted for heavier work than the curved-needle machine of the earlier form, and serves, as it were, as a link to connect the older machines with the new types described hereafter.


THE WHEELER AND WILSON Nos. 6, 7, & 8 MACHINES.

As these machines are all constructed upon essentially one plan, a description of No. 6 will suffice to illustrate their peculiarities of mechanism.

Fig. 20 is a general view of the machine with a rolling presser foot, suitable for leather work, fitted to it. As will be at once apparent, the plan of the machine is essentially different from that of the earlier forms, giving greater strength and perfection of work upon thick and heavy materials. The pulley, 11, has two speeds, so that the machine may be driven fast or slow to suit the material: motion is communicated from this wheel to the under parts by mechanism, which will be explained at length further on. 8 shows the needle bar, which is hollow, to give lightness combined with strength. Both this bar and the presser spindle, 3, work in stuffing boxes, packed with felt washers, and provided with oil recesses. This excellent idea effectually prevents oil from running down the needle bar and soiling the goods, while it allows of the efficient lubrication of the rods, with less wear than

usual. The pressure is adjustable at will by the screw, 53, and is released when required by the lifting lever, 29. The reel of upper thread is placed upon the spool pin, 10, and is carried on its way to the needle over

Fig. 21.—THE CLOTH PLATE REMOVED.



the end of an automatic take-up lever, 71, actuated by a cam from beneath. At 31 the needle plate is screwed in position, and the plate, 33, serves to cover the working parts underneath. As in the first machine, the bobbin holder or slide ring, 34, is fixed by a thumb screw, 63.

Fig. 21 is a view of the same machine in position for working, and with its plate covers removed to show the working parts. The needle arm, 17, is pivoted to the main arm, 6, and is actuated from beneath by a cam, to be explained subsequently. It is hinged to the needle bar by a link as shown. The thread is passed from the reel under the arm, over and in the slot of the thread guide, 69; then around the tension pulley, 75; thence, leading from the top of the pulley, over the top of the controller screw and in the controlling




Fig. 22.—THE UNDER PARTS.

finger; then under the thread jack wire, 67, and over the end of the take-up lever, down through the guide on the needle bar to the needle. The controller referred to is an ingenious device of a spring and eyelet, by which any slack found upon the upper thread, when entering thin goods, may be taken up, to produce a perfectly formed stitch.

By reference to Fig. 22 it will be observed that the cams which actuate the needle lever and the take-up are cut upon the same cylinder, 4, the one upon its face, and the other upon its end, 73. This double cam is fixed

upon the driving shaft, which is connected with the hand wheel, 11. Fig. 23 will further elucidate the construction of this double cam. Between the driving




Fig. 23.—THE CAMS.

shaft, 12, Fig. 24, and the hook shaft is a device for producing a variable motion, so that while the velocity of rotation of the former is uniform, the motion of the




Fig. 24.—THE VARIABLE MOTION.

latter shall be alternately accelerated and retarded. This end is attained by the use of a circular disc, 81, revolving in a fixed yoke, 80, and eccentric to the axis of the driving and hook shafts, which lie, however, in

the same line. On opposite sides of the centre of this disc, and along the same diametrical line, are two slots. A pin, 35, from the flange, 82, of the driving shaft, 12, works in one of these slots, giving a variable motion to the disc, due to the latter being eccentric to the axis of the shaft.

The other slot receives a pin, 36, from the flange, 15, of the hook shaft, 18, which is thus given alternately a quick and slow motion in a greater degree than the variable motion of the disc itself. The pins being at equal distances from the axis of the driving and hook shafts, the hook moves twice as fast through two-




Fig. 25.—SECTIONAL VIEW OF VARIABLE MOTION.

thirds of its revolution as through the remaining third. The amount of variation of motion depends, of course, upon the eccentricity of the disc, and the distances of the pins from the centres of the flanges. Fig. 25 is a longitudinal section of the same ingenious motion.

In the later construction of the machine this beautiful idea has been carried out in a much simpler manner, by the employment of the two discs, 82 and 15, connected together by a link, acting sometimes eccentrically and sometimes concentrically to the hook disc, the result being a hook motion which is alternately accelerated and retarded according to the position of the link

pin in relation to the hook shaft. This improvement is an important one, and reduces the friction to a minimum.

The rotating hook, which is illustrated in Fig. 26, is of peculiar and improved construction, the tail or guard overlapping the point, so that the under thread from the bobbin cannot interfere with the loop thrown out by the needle. The cavity of the hook is very deep, so as to admit a bobbin holding much more thread than usual, and more than can be received in an ordinary shuttle. This bobbin is contained by a case, as shown, called the shield, which is open on the side




Fig. 26.

Fig. 27.

THE NEW ROTATING HOOK AND BOBBIN, WITH CASE.

next to the hook, and kept in position by the spool ring. This case permits the loop of upper thread to be carried around the lower thread without disturbing the position of the bobbin, and further prevents the loop from being cast off the hook into the wide mouth of the bobbin, instead of passing over it, Fig. 27.

Fig. 28 exhibits a peculiar form of bobbin holder employed in some of the larger sizes of this machine. Instead of slipping the holder back, it is hinged as exhibited, and as explained at p. 40, Fig. 12. The catch spring is shown at *b*, where a finger lever is provided to release it when required. The forked drop piece, *a*, taking the place of the ring previously mentioned, is




PLATE II.

fitted with a steel spring, the face of which bears upon the bobbin case, and presses it gently into position. This bobbin holder is adjustable by means of the screw, *c*, and may be wholly removed, without withdrawing this screw, by the expanded end of the slot, as exhibited.

In Plate II. is given a complete collection of all the parts in miniature, by which the construction of this most excellent machine will be rendered still more intelligible.

The machine being threaded and put in slow motion, the needle descends, carrying a bight of thread through the goods and into the cavity of the hook, the take-up lever letting down thread enough for this purpose. As the needle passes the lower dead point, and begins to rise, a loop is thrown out, which is immediately entered by the point of the hook, the under thread from the bobbin being held clear of the loop by the tail of the hook. The needle, having risen clear of the hook, pauses with its eye still below the fabric, while the take-up lever descends and gives out thread enough to complete the loop, which is expanded by the hook, and carried over the bobbin. This part of the revolution of the hook is in its faster motion. The loop having been carried around the bobbin and cast off the hook, and the needle having risen entirely out of the cloth, the take-up draws up the loop and completes the stitch. While the stitch is being drawn up, during




Fig. 28.—THE BOBBIN HOLDER.

the interval between the casting off of one loop and the entering of the next, the hook is on its slower motion. At the moment of drawing up the stitch, an under tension apparatus, which is illustrated in Fig. 29, comes into play. 1 is the hook washer, also shown in Fig. 26; 2, the projecting pad, which, when in



Fig. 29.—THE UNDER TENSION.

position, outlies the periphery of the hook; 4 is a plate which is screwed to the frame of the machine; 3, a perforated finger held in proper position on the plate by dowel pins, which leave it free to be lifted from the plate. The needle, at each descent, passes through the hole in the tension finger, and through it also passes the under thread. 5 is a horizontally




Fig. 30.—THE NEW FEED BAR.

movable lever, one extremity of which bears on the tension finger. At each revolution of the hook the pad, 2, collides with the tension finger, 3, and clamps the lower thread just as the take-up is completing the drawing up of the loop and the tightening of the stitch. The under tension is varied by moving the lever, 5,

and bringing it to bear upon one or other point of the finger, and causing the latter to press more or less upon the pad. When the stitch is completed the pad moves from the finger, and entirely releases the under thread from tension. Knots or loops do not interfere with its action.

By means of these most valuable improvements the stitches are produced with a uniformity and beauty of appearance scarcely to be credited.

The feed used in these machines, exhibited in Fig. 30, is of the four-motion kind previously explained, but provided with an additional bearing for heavier work. The presser lever is adapted to receive flat or rolling pressers or trimmers and other attachments, and by an ingenious joint the foot may be thrown aside, to have a clear way when threading the needle, as in Fig. 31. The work is fed from the operator, but the arm may be either to the left or right, at the option of the purchaser. This machine (No. 6) is turned forward—the top of the pulley from the operator.




Fig. 31.—ROLLING PRESSER.

Fig. 32 is a general view of the No. 7 size of Wheeler and Wilson machine. The arm is longer to accommodate heavier work, for which all the parts are specially adapted. Fig. 33 represents the same machine reversed, and with its plate covers removed to show the under parts. The arm of this machine is to the right, and its pulley is turned towards the operator, from the top. The rotary hook being precisely the same as in the No. 6 size, but lying in the opposite direction, there is necessarily a slight difference in the feeding mechanism, due to the feed cam being





Fig. 32.—THE NO. 7 MACHINE.

turned with the book towards the operator, while the

feed is constructed to act in the opposite direction. This

Fig. 33.—THE PLATES REMOVED.



machine is also fitted with the new variable-motion

link, mentioned at p. 54. The friction roller, which runs in the cam actuating the needle arm, is made in two parts, adjustable for wear, so that play may be taken up when required.

Fig. 34 represents the No. 8 machine, which is constructed with a view to give great speed, and to run very lightly, for domestic use and the lighter kinds of manufacturing. The chief points of difference between




Fig. 34.—THE NO. 8 MACHINE.

it and the No. 6 or 7 machine are almost obvious on glancing at the engraving.

The needle arm is moved by an eccentric and connecting rod. The take-up is pivoted at the base of the fixed arm, and moved by a cam, 25. The upper tension apparatus is situated above the arm, as shown. Running from the reel, the upper thread passes from the take-up over a roller attached to the fixed arm, and

thence directly to the needle, the thread controller being dispensed with. The feed mechanism is of the four-motion kind, as in the other sizes of this machine, and the hook and under spool are also the same. This size is especially suitable as a hand machine, and is light and portable. To render it suitable for this purpose, a hand wheel, gearing in a pinion upon the spindle, is fixed to the arm, and the machine is mounted in a wooden base, which, when not in use, is enclosed by a case.

The stitch is regulated as to length by a thumb screw placed near to the base of the arm, as shown at 24 in Fig. 34. This screw communicates with the butt-end of the feed by a rod fixed under the frame. A stitch index is provided, by which the length of stitch may be determined previous to commencing to sew. The glass presser foot is usually employed with this machine, and is capable of being drawn out when required. Plate III. contains the No. 8 machine dissected, showing the difference between its parts and those of the No. 6 and 7 types.

Instructions for using Rotating-Hook Machines.—The following directions and suggestions should be carefully observed by persons desiring to operate the machines mentioned.

THE NOS. 1, 2, & 3 WHEELER AND WILSON MACHINES.

To thread the Machine.—Place the reel of cotton on the wire at the back of the machine. Pass the thread through the thread guide, pressing it as far back as possible, then upwards in front of the tension pulley, once round the latter, thence through the eyelets in the needle arm, and finally through the needle eye, from left to right, drawing it four or five




PLATE III.

inches to the right and back of the cloth presser. This thread may be held loosely between the thumb and the finger. To wind the under thread, raise the cloth presser and unthread the needle; place the reel of thread upon the pin on the table, and the metallic bobbin upon the spindle; wind the end of the thread two or three times around the inside of the metal bobbin; then work the treadle as when sewing, holding the thread between the finger and thumb to guide it into the bobbin. Use the under thread slightly finer than the upper. Put the metallic bobbin in the cavity of the hook, with the thread flowing from its top towards the front of the machine. Place at its right the slide ring upon the slide bar, close it in, and secure this part by the thumb screw. Draw the end of the lower thread forward between hook and slide ring, leave it in the thread catch, beneath the edge of the plate, until two or three stitches have been taken, and then liberate it.

To change the Needle Plate.—Two needle plates are furnished, one with a small needle hole for fine work, and another with a large hole for coarse work. They are held in place by a small screw, and may be changed by removing the screw and drawing out the slide by the point on the needle wrench.

The Feed.—The work is moved forward under the needle by the teeth of the feed. At each revolution of the leather-covered pulley the teeth are pushed forward above the face of the cloth plate, carrying the work ahead of the needle the distance required for each stitch. If the feed require cleaning, remove the crystal from the cloth presser, take out the feed bar, wipe all the parts clean, and set it back in position. If the teeth do not catch the cloth strongly

enough, turn the screw used to raise the draw feed point (page 43) down a very little. This will raise the teeth above the cloth plate. The feed points propel the fabric; the operator has only to guide it. To make a long stitch, push the lever of the feed stop from the front of the machine. To make a short stitch, draw it forward towards the front of the machine. Be careful not to pull the lever so far forward as to stop the feed bar from working.

To lace the Band.—Remove the cloth plate by taking out the screws by which it is fastened to the frame. Remove also the feed frame and the bobbin. Pass the band around the band wheel below the table, through the holes in the latter, and around the leather-covered pulley below the feed bar. Cut the ends carefully, and after piercing them each with four equidistant holes, lace them with a fine cord. Draw the ends together, being careful not to overlap them, or make the belt thicker by lacing. The band having been adjusted to run pretty tightly, press down any high portions of the joint, and replace the feed bar and the feed spring. Replace also the cloth plate.

To set the Needle.—Place the needle with head or shank in the needle yoke, with its eye ranging from left to right, and the curve outwards, or to the front of the machine; the flat part of the shank of the needle will then be to the left hand. Secure it by screwing up the nut to the right of the needle yoke; for which purpose use the needle wrench. Set the needle so that in its descent it may pass through the centre of the needle hole, as close as possible to the left of the point of the rotating hook without touching it, and its eye about one-sixth of an inch below the point of the hook, or level with the edge of the shield behind the hook

point, so that the point of the hook may enter the loop made on the right side of the needle as it begins to rise. If set too low, the needle will scratch the hook, and its point become turned.

The Brush Loop Check.—This brush should press snugly upon the circumference of the rotating hook, but not on the chamfered part. The function of this brush is to retain the upper thread until the point of the rotating hook takes the succeeding loop formed by the needle; it ought to liberate the thread when the point of the hook has fair hold of the next loop. Should this check brush become worn, so as not to check the loop of thread, adjust it with the fingers by unscrewing the brush screw.

To place the Bobbin in Machines fitted with the New Hinged Slide.—Press the finger lever to the right of the slide ring, and turn back the drop. Place the bobbin upon the drop or ring with its lower edge within the cavity of the rotating hook, and the thread winding from the top of the bobbin towards you. Turn up the drop until secured by the catch.

Broken Under Thread.—If the thread should break in the metallic bobbin, its end can be found with the thread hook supplied with the machine. Never use any other point for this purpose.

Regulating the Tension.—The tension is regulated by turning the nut at the end of the volute spring; a proper stitch is obtained when the upper and under threads interlock in the centre of the fabric, showing both sides of the seam alike. If the lower thread lies upon the lower surface of the work, the tension is too light; increase it by turning the nut towards you. If the work puckers, or the upper thread lies upon the upper surface of the work, the tension is too

great ; diminish it by turning the nut backwards. If loops occur on the under side of the work, examine the tension pulley, and see that the thread passes properly around it, and that it is not clogged by accumulation of dust or broken cotton.

To Sew.—Be seated before the machine ; place one or both feet upon the sandals, with the toes under the sandal straps. Start the machine by raising or depressing the toes ; or, if necessary, turn the balance wheel with the hand upwards to assist ; never turn backwards, but move the hand always in the direction indicated by the arrow at Fig. 14. In sewing keep gentle hold upon the free ends of the threads until a few stitches have been taken.

To Gather.—Make a long stitch with loose tension, relax the tension by turning the nut at the end of the volute spring from you, so that the lower thread will not be drawn into the fabric, but be upon the lower surface. Gather by drawing up the lower thread, which should be a size or two coarser than the upper thread. When stitching fabrics to be gathered, place the right side of the material downwards.

The Large Gauge.—This gauge is used for wide tuck-ing, quilting, and plaiting shirt bosoms. It is fastened by the thumb screw to the under side of the stationary arm, and can be moved forward or backwards, according to the width of tuck or plait desired. To adjust the same gauge for quilting, loosen the screw which connects its parts, and raise the lower part to allow the goods to pass between it and the cloth plate ; then tighten the screw. The last seam sewn should pass directly under the gauge, and the next seam will be parallel to it.

The Plate Gauge.—This gauge, for sewing close to

an edge, or for tucking, is attached to the cloth plate at the same hole, using the thumb screw. For very narrow tucks the plain crystal must be removed, and the one with the side cut away placed in its stead. The two gauges are not used in conjunction.

To adjust the Old Style Hemmer.—Loosen the fixed arm by starting out the screw by which it is fastened to the standard. Remove the cloth presser by unscrewing the screw. Put the hemmer in place of the cloth presser. Secure it by the thumb screw, and fasten the arm to the standard, as before.

To adjust the New Style Hemmer.—Remove the crystal from the cloth presser with the point on the small end of the needle wrench, and substitute the hemmer.

To change the Spiral Spring.—Remove the presser by unscrewing the fixed arm; unscrew, draw out, then place the spiral spring round the presser, and readjust.

To Hem with the Hemmer.—To make a narrow hem, roll the corner of the cloth slightly, enter it in the convolution of the hemmer, and draw it along to the needle. The hem is then turned, and stitched as in ordinary sewing. To make a wide hem, fold the cloth the width of the hem, and pass the edge through the hemmer. Use the light cloth presser spring for hemming and light work. If the needle is bent so that it does not catch the edge of the hem, spring it a little to make it descend in the proper place.

To Fell with the Hemmer.—Join the two edges of the fabric together as if it were going to be felled by hand, leaving the edge that is to be turned down the width of this line (—); then open out the fabric, put the widest edge into the hemmer, and proceed to sew. Be careful that the edge is even, and of the proper distance to produce a neat fell.

Braiding with the Machine.—Wind the braid upon an ordinary reel without twisting it. Attach the arm for holding the braiding reel by the thumb screw to the fixed arm of the machine, in a position to bring the reel containing the braid directly over the needle hole in crystal. Insert the two-hole crystal, pass the end of the braid from the reel through the hole in the crystal, bringing it under the point of the needle, and proceed as in ordinary stitching.

The Thread Oiler.—The oiler is a useful contrivance for lubricating *linen* threads, and it may be used when stitching dressed calicoes. Attach by slipping it on the needle arm at the smaller part, and slide it up towards the tension. Saturate the sponge with oil, place the upper thread in the slit, and proceed to sew.

Emery Stone for Sharpening Needles.—To sharpen needles when their points are dulled or turned, place the circular hone on the spindle, and work the treadle as in filling metal bobbins; place the point of the needle slantingly against the hone, turning the needle with the thumb and fingers as the point requires.

To set the Needle in No. 4 Machine.—Raise the needle bar to its highest point, loosen the set screw at its lower end, push the needle into the socket as far as it will go, with the long groove to the left, and secure it by turning the set screw.

To thread up No. 4 Machine.—Pass the thread through the thread guide, once round the tension pulley, thence through the thread leader, the small eyelet at the end of the needle bar, and the eye of needle, and finally draw it through four or five inches to the right. In all other respects follow the instructions herein given for No. 1, 2, and 3 machines.

Cleaning and Oiling.—Remove the cloth plate, and

clean well about the rotating hook, the feed bar, and the feed points. Put a drop of oil on each of the following points: the hole in arbor, at each bearing in each standard, upon the cam, the hole in the eccentric ring, also the bearing of the feed bar, and on the top of the same, the pivots at each end of the rocking bar and the hinge, and occasionally on the top of the cloth presser piston where it passes through the fixed arm, and on the bearings under the table. Use sperm oil thinned with paraffine or petroleum.

General Directions.—Set the needle properly. Keep the machine clean and well oiled, and the brush check in proper order, according to directions. If the upper thread should break, it is probably owing to one of three causes:—1st, the tension, or friction, is too great upon the upper thread. 2nd, the loop check does not press the hook sufficiently to restrain the loop which is passing over the lower spool until the point of the hook takes hold of the succeeding loop at the needle. 3rd, the metallic bobbin has become roughened on the edge, and wears off the thread in passing over it. If the thread should hang in loops on the under side of the work, increase the tension on the upper thread sufficiently to draw the lower thread up into the goods, and see that the thread passes properly around the tension pulley. Should the thread break by increasing the tension on the upper thread, and still not make a perfect stitch on the under side, examine the metallic bobbin, and see if there is any roughness on it or on the hook, so as to prevent the thread from passing freely over it. Also be careful not to break the cotton in the tension pulley, or allow it to become clogged with dirt.

GIBBS'S ROTATING-HOOK LOCK-STITCH MACHINE.

This machine bears a certain resemblance in its lock-stitch mechanism to the Wheeler and Wilson type, but the hook has also some of the peculiarities of the Willcox and Gibbs single-thread looper. In general appearance the machine resembles the single-thread machine, but the bed is larger and gives more cloth space.

The improved hook invented by Mr. Gibbs is designed to be rigidly mounted upon a revolving shaft, for which purpose it is provided with a central stem which can be inserted and fixed in the end of the shaft. It is a bobbin embodying a hook; that is to say, one formed as is usual in rotating-hook lock-stitch machines, with a recess in one face to receive the bobbin. It is characterized by a certain form of construction, whereby the loop taken by it from the needle is carried over the face and rear of the body of the hook. The position to which the loop is carried by the hook as it rotates is one diametrically, or nearly so, across the body in front and rear of the latter, which position the loop maintains until released by and upon completion of the revolution of the hook. The body of the hook consists of a segment, one extremity of which forms the hook proper, and between this and the heel or opposite end of the body of the hook is cut away or recessed nearly down to the central stem, so as to form a flat edge or surface. Upon the rear side of the hook is formed an inclined surface which leads to an undercut groove or notch formed in the body of the hook, and extending radially, or thereabouts, from the centre of the stem to the circumference of the hook. In this groove the

portion of the loop which is on the rear of the hook is retained until it is released from the hook.

The improved bobbin holder intended to work in conjunction with this hook is pivoted, and capable of oscillating on the pivot in a plane parallel with the face of the bobbin ; it is also capable of moving bodily in a direction at right angles with its plane of oscillation. The former movement is for the purpose of bringing it in front of the bobbin when required ; the latter, for causing it to press towards, or retire from, the bobbin.

In a further development of this device, an arrangement is adopted by which tension can be put upon the under thread while the machine is in motion by means of an external independent yielding presser, which bears with more or less force upon the bobbin case.

A take-up arm, having a length equal to that of the needle arm, is also employed, and is actuated by an eccentric upon the main shaft.

The feed mechanism in this machine consists of a rocking shaft, actuated by an eccentric, which carries the power for the feed point under the bed of the machine. The feed itself is of the usual form, working upwards and forwards against the antagonistic spring.

The upper tension has the intermittent motion given to it by a lever on the main shaft, by which means it clamps the thread firmly and keeps it rigid until released when the needle approaches the upper extremity of its stroke. This arrangement is, however, more fully described at p. 80, in the particulars given of the Willcox and Gibbs single-thread machine.

CHAPTER V.

SINGLE-THREAD SEWING MACHINES.

THE so-called single-thread or loop chain stitch is formed by throwing one bight of thread over another in succession, the result being the well-known chain of loops produced by various hand needles.

All single-thread machines make this stitch, but in some forms of the manipulative mechanism the loops are so twisted that the result is a seam of singular utility in many classes of work, possessing great elasticity, strength, and beauty, with the additional advantage that it can be withdrawn from the fabric when required, without injury to thread or material.

A simple form of looper for making the chain stitch consists of a hook, which enters the bight of thread carried through the cloth by the needle, and so spreads it out in the path of the needle, that at the succeeding descent the bight of thread is caught by the hook through the first loop, while the latter is being pulled up into the cloth. Thus one loop is thrown over its successor, to form a line of stitching which is plain on the upper side and chained beneath the fabric. The required tightness is obtained by putting a certain amount of strain on the thread. Sometimes this tension is obtained by fixing the thread reel between

a pair of adjustable cones, which are prevented from revolving too freely by an antagonistic spring.

The form of looper and the tension arrangement spoken of are embodied in the single-thread machine of James Weir.

The machine invented by James E. A. Gibbs, which




Fig. 35.—THE WILLCOX AND GIBBS MACHINE.

is now the special manufacture of the Willcox and Gibbs Sewing Machine Company, claims attention as a beautiful development of the first crude ideas in chain-stitch machine construction.

Fig. 35 is a general view of this machine, with the

later improvements. The driving power is taken from the small hand wheel, driven by a band as usual, through a shaft under the cloth plate to the feeder and rotating hook, the form of which, with its point advancing to the needle, is shown under the cloth plate.

This *Rotating Hook* is of peculiar shape, and twists the loops in a fashion which gives to the Willcox and Gibbs machine its well-known superiority. When the loop is seized, the needle begins to ascend, and, as the hook continues its revolution, the loop is *twisted* once across the path of the needle—that is to say, the front part of the loop is turned to the back, and *vice versa*. The loop is now held spread out under the needle hole until the needle descends and the hook is enabled to catch another loop, which is twisted similarly to the former one. The hook, by expanding out loop No. 2, assists in pulling loop No. 1 into the cloth. Gibbs's looper is made in hardened steel, and is highly polished at every part. It is provided with a stem, which, as it fits and is screwed into a hole in the extremity of the shaft, permits of the hook being easily set in time in relation to the motions of the needle.

The *Feeder* is provided with three sets of teeth, cut in its feeding tongue, as shown. An eccentric is cut on the end of the horizontal shaft immediately behind the hook itself, and from this eccentric or cam the feed is caused to give four motions at each stitch. The feed teeth first rise into the cloth, and, to give the required displacement of the fabric, move forward under the pressure of the foot, as shown; the feed point then falls and returns to its first position, completing the four motions. In the improved spring feed bar, which is shown in Fig. 35, the yielding pres-

sure contact with the single eccentric, which produces both the vertical and horizontal movements of the feed bar, is maintained during both the up and down and back and forth movements of the teeth. The eccentric imparts to the spring feed bar, by direct contact with it, the up and down motion, whilst a link connected at one end with the feed bar at a point below its axis of vibration, and at the other with the stitch-regulating cam, bearing with yielding pressure on an upright rocker or vibrating arm operated by the eccentric before mentioned, imparts the back and forth motion to the feed bar, so that the feed is quite noiseless at all adjustments of the stitch-regulating cam shown. That portion of the upright rocker or vibrating arm which is in contact with the eccentric is bevelled, or equivalently inclined, so that the feeding surface may continue its forward movement until after it shall have receded below the plate out of contact with the cloth. The proper adjustment of the feeding surface in the cloth plate is effected by making the bearing screw or pin of the link, which acts as the upright rocker, adjustable in the link, and the stitch-regulating cam is connected by a pin with the grooved end of the link, so as to cause the latter to rise or fall when the cam is adjusted, and then bear on the rocker at the proper distance from the centre of oscillation of the latter, according to the length of stitch required. The groove or slot in the end of the link, in which the pin of the stitch regulator works, is of a curvilinear form, so that the portion of the slot which has its play on the cam pin shall be parallel with the cloth plate, or nearly so, at all positions of the cam. The stitch-regulating cam is provided on its concentric peripheral portion, on the upper half,

with certain figures, indicating the number of stitches to an inch, and is arranged so as to present the portion mentioned tangentially to the cloth plate, so that the number which is upon the tangential portion of the cam may show through an opening made for that purpose in the cloth plate, as exhibited in Fig. 36, which is a view of part of the cloth plate. To the right is stamped a useful table for the guidance of the operator in the selection of the most suitable sizes of needles and threads.

Referring again to Fig. 35, a stop pin is fixed into the frame of the machine in order to limit the play or movement of the stitch-regulating cam within the compass of the series of numbers on the periphery of the cam. This pin engages in a curved slot or recess in the cam.

Passing upwards to the cloth plate itself, three slots are cut through the plate, in which work the serrated surfaces of the feed, which is so formed as to almost surround the needle hole. In addition to this, the upper surface of the cloth plate, in the immediate neighbourhood of the feed space, is serrated, so that the cloth may be prevented by the forward-set teeth from receding from under the bevelled end of the foot when the feed releases its hold on the cloth. This device greatly facilitates the operation of feeding seams or thick portions of the cloth through the machine. The needle hole is elongated, a form found to be best suited to the formation of a good loop stitch. In addition to the plate being serrated on its upper surface, it has been found advantageous to cut teeth also on the under side, immediately over the feed points; by this means the fluff or other offcast from the fabric or thread, which often chokes up the feed teeth and

stem, is worked off the plate and thrown into the cap, shown in Fig. 35. The cloth plate is screwed to the frame, and is easily movable for the purpose of cleaning.

The *Needle Arm* is jointed to the frame by the lever stud (Fig. 35), and is free to move thereon in a vertical arc. Its short end, to the right of the stud, is grasped by a joint, working upon a ball stud. The motion is taken from the horizontal shaft by an eccentric, the periphery of which, with its bearing on the collar, is ball-shaped to increase the wearing surfaces. One revolution of the hand wheel thus causes the needle arm to vibrate once in both directions. The arm is jointed to the needle bar by a ball joint of ingenious construction, providing a large wearing surface.

The *Needle Bar* moves vertically in two bearings drilled in the standard. Upon its lower end it carries a needle-clamping screw, which, when screwed upon the tapering or split extremity of the bar, closes the two spring sides upon the needle. In addition to this the needle is grooved on its shank or stem, which groove, corresponding with a steel tongue or plate within the needle holder, insures the correct setting of the needle. This will be further explained.

At its upper end the needle bar carries a double loop of steel, working in proximity to an upright square-section stud. The whole arrangement constitutes the thread take-up, the function of which is to pull the stitches tightly into the cloth at the required moment. The action of the take-up detains the descending thread, which is passed through the metallic loop, until the eye of the needle is on the point of entering the fabric.

The *Presser Bar* is likewise carried by the end of the standard arm, and is provided with a spiral spring continually urging it downwards upon the cloth plate. Upon its lower end it carries the presser foot, which is slotted out to permit the needle to pass, and presses the cloth upon the plate to allow of the correct action of the feed teeth. An improved foot of this description is jointed near to the end of the bar, and is kept in the position represented in Fig. 35 by a small spring. This device assists the feeding of materials of varying thicknesses into the machine, and the passage of high seams. In order to prevent the presser bar from swerving, a feather was formerly fixed to it, working in a slot in the casting, but in the improved machine this is replaced by a stronger arrangement, consisting of a second rod, working in a recess between the needle and presser bar, and made fast to the latter by a screw working through a slot. The presser lifter consists of a steel cam, provided with a handle, as shown. It is screwed or jointed to the bar.

The *Thread Eyelets* are fastened in the frame, and are of hardened steel. At the part of the needle arm marked "Pull-off" is a device for taking from the thread spool the required length of thread for each stitch. It consists of two stout steel wire loops, one of which is fastened to the frame or main arm, while the other is fixed in, and vibrates with, the needle arm. The action of the pull-off will be further explained in continuance.

The Automatic Tension.—This most ingenious device consists of an arrangement by means of which the thread is so controlled in its passage to the needle that no adjustable tension is required. The device, which

is very compact, is contained in the round casting marked "Automatic Tension," and consists of a thread rest or support, upon which the thread in its passage to the needle is held by a smooth surface ring resting upon the thread by gravity simply, so as to exercise a gentle but continuous pressure thereon, in combination with a thread-clamping device, consisting of a stationary support for the thread, and a movable clamping surface, actuated by a spring, for the purpose of firmly holding the thread until the loop is almost or quite drawn up to the cloth, and then suddenly releasing the thread, leaving only a nominal friction upon it.

The releasing or relieving device consists of an eccentric operating upon the movable clamping surface at the required intervals so as to release the pressure upon the thread. A washer of soft felt is interposed between the thread-holding rest and its support, for the purpose of preventing the jars which attend the action of the eccentric through the connecting rod. In order to obviate the use of oil, and therefore to render access to the interior for this purpose unnecessary, washers of leather are fixed upon the movable clamping device, serving to keep the spindle itself clear of the metallic sides of the tube or recess. An adjustable head or tappet is fitted into the upper end of the connecting rod which raises the tension spindle. This tappet moves to and from the end of the tension spindle inside the tube, and is provided at its upper end with a leather washer fitting the tube, so as to form a guide for the upper end of the connecting rod. Sound-deadening washers of soft felt or wool are interposed between the head of the spindle, spiral spring, and clamping plate.

The Spool Holder.—This is a device for receiving the spool of thread, and is arranged with its axis in line with the first or nearest thread-receiving eyelet, in place of being vertical as usual: it is provided at its lower end with a plate or disc, against which the spool rests. This inclined spool pin is fitted into a




Fig. 36.—THE STITCH INDICATOR.

bracket, in which it is held at one end, so that it may be removed from or replaced in the holder at pleasure. The spool plate or disc before referred to is provided with an annular flange arranged to overhang that end of the spool which is in contact with, or nearest to, the disc, by which means the thread is prevented from slipping off the spool, and is also unwound without

causing the spool to revolve as usual. The obvious advantages of this ingenious device are that there is no tendency to wind the thread around the spool pin when glazed thread is in use, and that the tension of the thread spool upon the thread is always equal; the machine may also be turned in any position without




Fig. 37.—OILWAYS OF THE FEED MECHANISM.

the usual inconvenience of the spool dropping off its pin.

The *Frame* is, as shown in Fig. 35, substantially one casting. The cloth plate, upon which is indicated the number of stitches to the inch, is exhibited, as before mentioned, in Fig. 36.

Fig. 37 is a view of the machine with the new feed movements from beneath, exhibiting the bearings and relations of the parts, and also the various oil holes for the lubrication of the feed mechanism and main shaft. A cast-iron cap is jointed so as to cover over these parts.

Fig. 38 exhibits the necessary lubricating points in the machine when placed in working position upon the




Fig. 38.—OILWAYS OF THE UPPER PARTS.

table. These points are the needle bar (two places), foot bar (two places), needle-bar screw, lever stud, shaft, lower end of tension rod, and both ends of main connecting rod.

The Needle.—The short groove of the needle must be set towards the point of the Gibbs's looper, and to insure this, and also the correct height of the needle,

the stem or shank is grooved deeply in one side only, while the length of the shank is adjusted so that its upper end should pass as far upwards as possible into the needle bar. The groove corresponds with a steel tongue in the needle-bar hole, so that the needle cannot be set otherwise than accurately.

Figs. 39, 40, and 41 exhibit the operation of setting the needle in this machine. Fig. 39 shows how the point must at first be entered downwards in the needle hole to get the shank to enter the bar. Fig. 40 renders




Fig. 39.—PLACING THE NEEDLE. Fig. 40.—SETTING THE NEEDLE.

plain the pushing up of the needle into its place by means of the setting wrench. The needle is finally fastened by screwing up the nut, which, by means of the split needle bar, causes it to be grasped tightly in position, as in Fig. 41.

Fig. 42 is intended to represent the course of the thread from the spool pin to the needle eye. The direction of the thread is indicated by the arrows. The spool pin is first pulled out, and the reel placed upon it. The pin is then replaced, and the needle bar raised to

the highest point by turning the hand wheel. The course of the thread from the spool is, first from the back towards the operator, through the two staples and the arm known as the pull-off (Fig. 35), when it is passed once around the automatic tension, marked 2, Fig. 42, and from this point to 3, the eyelet on the arm, thence to the loop marked 4, through the




Fig. 41.—SCREWING UP THE NEEDLE.

take-up loop, 5, and the eyelet, 6, and finally into the needle's eye.

The machine is now ready for working. The fabric, as in most other machines, is fed from the operator. No regulation of tension is necessary. When the work to be sewn is extra thick, or when sewing on braid or cord, the thread is passed through the embroidery spring also, which is shown in Fig. 35.

For such classes of work as require to be turned continuously, such as straw hats, the machine is fitted with a "vibrating presser," which is actuated so as to

rise off the work to the required height at each stitch, to facilitate the operation of turning the goods with ease. This attachment may be put in and out of action at pleasure.

The *New Straw Hat Machine* embodies all the peculiarities of the recognised Willcox and Gibbs's type




Fig. 42.—THE THREADWAYS.

with extra arrangements, by which the operation of sewing up a straw hat from the plait may be carried out with ease and certainty.

In the first forms of this machine it was fitted with two or more feed tongues, capable of receiving different lengths of play in feeding the fabric. By these means

the circular straw-hat disc, by being fed faster at the outer edge than at the inner circle, might to a certain extent be caused to revolve under the needle without aid from the operator. Further experience, however, led Mr. Charles Willcox to devise a machine having one feeding surface only, with other attachments to facilitate the laying of the plait in correct position. The new feed mechanism is so arranged as to have great strength, and also to be entirely out of the path of the work being sewn.

The feed mechanism is different from that applied to the common machine. A shaft some five inches in length is mounted in long bearings behind the frame, and from this shaft as an axis work the actuating arm and the feed surface itself. The former part is caused to vibrate by an eccentric placed upon the main revolving shaft, and from the arm connecting the eccentric with the back axis shaft is taken the feed-point lever. Thus the feeding mechanism is entirely disconnected from the front or hook face of the machine. The ordinary cloth plate is necessarily dispensed with, and a curved plate of small size takes its place over the rotating hook.

An effective guide for the work is provided to the right of the needle plate, and is adjustable back and forth by a rack and pinion, to facilitate the changing of the width when the machine is in motion. The presser foot carries several extra attachments made in two pieces, to render the operation of making a straw hat easy and certain. At this point the width and thickness of the plait or braid can be quickly adjusted for, and the "fulness" required in some work can in this form of the machine be given with greater nicety by the fingers than by a second or third feeder,

as in the first-mentioned type of straw-hat machine. A presser vibrator completes the more remarkable arrangements in this new machine, which altogether should greatly cheapen the production of all kinds of straw hats.

Speed of these Machines.—The rate of rotation in the Willcox and Gibbs machine is, or may be, enormous. For manufacturing purposes steam power is usually employed, when the speed of working is very great: 3,000 stitches per minute are often attained, while by foot 1,500 may probably be given. The work is done with equal perfection at all speeds.

Noiselessness in Working.—The noise has been reduced to a minimum by the peculiar arrangement of the parts. Much attention has been given to this point in the Willcox and Gibbs machine, the result being an almost silent action at all speeds.

CHAPTER VI.

PROPORTIONS OF NEEDLES AND THREAD TO WORK.

THE following tables are intended to serve as a guide to the sizes of needles and threads which should be used when sewing the different classes of goods indicated, so as to provide against accidents to the machines and work, and to produce the best stitching.

The rules refer to three kinds of sewing machines—shuttle, rotating-hook lock-stitch, and single-thread, or Howe, Wheeler and Wilson, and Willcox and Gibbs.

When the under thread is not specified to be finer than the upper, the same sizes should be used for both. When a face stitch for leather is required, the flat-pointed needle is used; and when the stitch is to be sunk into the leather the twist point is usually employed. The round common point is always used for cloth goods.

The needles for all sewing machines are numbered on the shanks. Bad or uneven threads should be avoided, especially those of varying thicknesses.

FOR THE SHUTTLE (HOWE) MACHINE.—TABLE I.

Size of Needle.	Material to be sewn.	Size of cotton, linen, and twist.
000	Lace, Nainsook, Swiss, and fine Silks.	100 to 150 cotton, or 000 twist.
00	Finest Muslin, Linen, and Cambric.	80 to 100 cotton, or 00 twist.
0	Heavy Silk, light Woollen goods, Calicoes, and Muslins.	60 to 80 cotton, or 0 twist.
1	Unbleached Muslin, Cotton, &c.	40 to 60 cotton, or A and B twist.
2	Ticking, and light tailoring.	20 to 40 cotton, or B and C twist.
3	Coarse goods generally, Heavy Clothing.	16 to 20 cotton, or C and D twist.
4 and 5	Felts, and very coarse Cloth.	Coarse cotton, linen, or twist.

The two following tables refer to the Wheeler and Wilson Nos. 1, 2, and 3 machines respectively.

FOR THE DOMESTIC ROTATING-HOOK MACHINE.—TABLE II.

	KIND OF WORK.						
	Finest Muslin and Linens.	Kerchiefs, Collars, Shirt Fronts, &c.	Dressmaking, Quilting, Ordinary work.	Heavier work of the same class.	Cloth, Ticking, &c.	Heavy Cloth Work.	Heavy Cloth Work.
Size of Needle.	0	1	2	2 $\frac{1}{3}$	3	3 $\frac{1}{2}$	4
COTTON.	90 & upwards.	70 to 80	50 to 60	40 to 50	30	20	12 to 16
Upper Thread.	100 & upwards.	80 to 90	60 to 70	50 to 60	40	30	16 to 20
Lower Thread.							

SILK TABLE.

Needle.	Silk.	Soft under Cotton.
2	28	70
2 $\frac{1}{2}$	24	60
3	20	50

FOR THE NOS. 6 AND 7 MACHINES (WHEELER AND WILSON).

TABLE III.

Cloth . . .	Lawns and nainsooks.	Finest silks.	Handker- chiefs, collars, fine shirts, &c.	Common muslin, light dress- making.	Heavy dress- making.	Light clothing and cloak- making.	Heavy tailoring.	Bags and awnings.	Extra heavy work.
Leather . . .	Fine kid	Light kid	Light	Sheep, calf	Ordinary	Light har-	Heavy	Carriage	
	gloves.	and morocco.	patent leather.	and goat skin.	leather, carpet bags, and calf boots.	ness work and com- mon boots.	boots and harness work.	trimming.	
Needles . .	1	2	3	4	5	6	7	8	9 and 10
Cotton . .	300 to 200	150 to 100	90 to 80	70 to 60	50 to 40	36 to 30	24 to 20	16 to 8	
Silk . . .	32	30	26	24	22	20	18	16	
Linen . . .	—	—	—	—	100	80	60	40	25 to 20

The following table relates to the single-thread or chain-stitch type of machine, which is more especially adapted for the lighter kinds of work at high speeds.

TABLE FOR THE WILLCOX AND GIBBS MACHINE.

TABLE IV.

For calico, long-cloth, &c.	Use cotton Nos.	60 to 80
For fine lawn, nainsooks, &c.	" "	100 to 150
For fine linens	" "	80 to 120
For light woollens	" "	40 to 60
For heavy woollens	" "	20 to 40

The sizes of needles to be used upon these goods are stamped upon the cloth plate, as exhibited at page 82, Fig. 36. Glacé cottons work much more satisfactorily on the Willcox machine than those with a soft finish.

The following statement refers to the speeds at which ordinary machines may be advantageously driven. As a general rule, the stouter the needle and the coarser the thread, the slower should the speed be. Some kinds of leather may be worked at a high speed.

SPEEDS AT WHICH LOCK-STITCH MACHINES MAY BE DRIVEN.

TABLE V.

Kind of Work.	Revolutions per minute (number of Stitches).
Heaviest leather goods	220 to 250
" cloth "	250 to 350
Medium work	350 to 400
Calico and finest goods	600 to 1000

SECTION II.

DIRECTIONS FOR ADJUSTING THE VARIOUS TYPES OF SEWING MACHINERY.

CHAPTER VII.

THE ADJUSTING OF WHEELER AND WILSON MACHINES.

To "Take Down" the Machine, No. 1, 2, or 3.—By reference to p. 37, where the positions of the various sections in the smaller type of Wheeler and Wilson are explained, the allusions to names of parts following will be the more intelligible. It is a common practice with sewing-machine mechanics to attempt the efficient repairing of hook machines without removing all the parts. This is a mistake. It is usually very much easier to pull the machine to pieces at once, and to treat each part separately.

A worn or badly used rotating hook cannot by any process or expenditure of care be efficiently repaired unless it be removed from the machine. In many cases the "time" of the hook is materially altered by filing and smoothing out rough places, and its removal from its bearings is then imperative.

Before proceeding to take the machine to pieces,

always remove the needle from its yoke ; this will obviate subsequent trouble with the needle point. With a large screw-driver draw the screw fastening the presser arm in position, and remove the arm itself. Take off the cloth plate, and remove the feed bar and spool ring. Cut the fastenings of the belt, and draw the two set screws let through the leather-covered pulley, which hold the hook in position. The hook itself, if the machine be old and clogged with oil, may at first cause some trouble to pull out, but a little paraffin oil, with a tap or two upon the spindle end with a mallet, will usually suffice to render its removal easy. When the machine is very much clogged, and the hook refuses to draw, the paraffin oil may be left to soak in, and its dissolving and softening action may be hastened by gently heating the base of the machine.

A hexagon wrench is usually supplied with the machine, by means of which the lock nuts on the pivot screws may be unscrewed. Both pivot screws should be removed from the casting. The needle arm is now free. The hinge bar, in which the eccentric rod is jointed, is next to be removed from the rocking bar by drawing its screw, and it will be as well for a beginner to mark the position of the bar with regard to the screw for future adjustment. To remove the eccentric from the pulley, draw the screw holding the check disc at one end, and the drum and eccentric may be separated. If there should be any binding at this latter point, a turn backwards of the eccentric-strap screw will loosen it.

Mark the position of the check-brush holder and remove the brush and holder from the frame.

To Clean the Parts.—Clogged and gummed oil is

troublesome to remove, so that paraffin oil should be freely used upon all the parts. After a few hours the various portions may be easily wiped clean. Care must be taken to thoroughly clean out all oil ways with a metal pin.

The Spring Thread Guide.—The top thread, after leaving the bobbin, passes to the under side of the spring or barrel thread guide. In this guide it moves between two steel discs, which exert a gentle pressure upon it by means of a small brass spring in the guide pressing the discs together. This guide acts a very important part in the working of the machine, its office being to hold the thread sufficiently tight upon the tension pulley to cause it to revolve. Without this spring guide, or something equivalent, the tension pulley would not revolve at all. If the tension be tight, there is all the more need for an efficient check at the first guide.

In course of time and working the spring guide gets out of order by clogged oil or accumulated masses of fluff keeping the discs apart and preventing a check upon the thread. In some cases, where the discs chance to be too soft, the continual friction cuts grooves in them, and they will often fail to check fine sizes of cotton. To put this part in working order, draw the screw in the end of the guide, and carefully remove the brass spring—a bent pin will prove useful for this purpose. In most cases the steel discs will be found firmly gummed into the guide, and paraffin must be dropped into the aperture to release them; a sharp pointed wire will assist in loosening them, and sometimes a small bar magnet is useful. When the discs are removed, clean out the socket thoroughly, and dry off all oil. Polish up the exterior for appearance' sake, and file the discs flat upon each face, in doing which

rub them with the finger upon a fine file. They should be well polished, so that no chafing of thread may take place between them. Clean the spiral spring also, and replace the discs carefully, with their smoothed faces together; put in also the spring, after it the screw, and finally test the holding power of the guide by passing cotton as fine as No. 90 through it. A gentle and regular tension should be kept upon the thread.

The Tension Arrangement.—A thumb nut, volute spring, iron washer, felt washer, steel pulley, and another felt washer, all mounted in the above order on a stud on the needle arm, constitute the tension apparatus in this type of machine.

Some machinists have a bad habit of dropping oil upon the tension, as it is commonly called, which gradually clogs it up and stops its working by hardening the felt washers. Chiefly from this cause, but partly from dust and bad usage, the tension pulley becomes clogged up, and refuses to turn regularly or to hold the thread effectually. Remove the thumb nut, spring, washers, and pulley. Drop paraffin oil upon the volute spring, and press its ends together to squeeze out all dust and make the spring work freely. The pulley must be examined in its groove, which often gets filled up with fluff, and cleaned out; for which purpose a hooked iron wire, filed very thin at the end, will be useful. The felt washers should be renewed.

The thumb screws for increasing the pressure on the pulley in the old style of machine often get loose and fail to keep their position when the machine is in rapid motion. In the new machines a better plan is adopted: the nuts are split half through with a fine saw, and grip the screwed spindle with a spring pressure.

The old style of nut may be made good by slitting with a watchmaker's frame saw, pressing together slightly while red hot, and cooling in water.

It is of importance that the iron washer does not rotate upon the stud. The tension pulley must be made to run very smoothly, as any jerking will cause uneven and bad stitching. The thread must catch in the groove, and must not slip past without taking the wheel round. After turning once round the pulley, passing to the under side of the groove first, the thread passes through an eyelet in the needle arm near the bend. The thread hole in this eyelet is very frequently cut by the friction of the passing thread, and in these cuts the thread often sticks. If not of great depth the cut can be obliterated and the hole smoothed over with a fine round file. If the cut be deep, it will usually be best to turn the eyelet upside down, smoothing out the hole. From this point the thread passes downwards through the end of the needle yoke. The hole in this must be filed out and smoothed over if necessary. For smoothing out the eyelet holes a thin strip of FF emery cloth, oiled, or a piece of twine dipped in emery powder, may be used. It will be necessary to again refer to the needle yoke, to ascertain whether it holds the needle in line, but for the present the adjuster cannot go farther with this part.

The Presser Foot.—In holding the fabric as we operate the sewing machine, we do so with a hand that can hardly be said to be steady; our hold is an elastic one, giving and taking as the feed moves. It will be plain, therefore, that if the presser foot or feed be not perfectly steady in its movements our work cannot be sewn in a straight line. The presser foot shakes from side to side, let it be ever so little; we are stitch-

ing, for example, on the extreme edge of some linen fabric ; we endeavour to make the line straight, but find great difficulty in preventing the needle from slipping too far in, or right over the edge ; we naturally look to the feed for the important defect, but find it quite steady ; we examine the presser, and find that it has a little play—herein lies the cause of the difficulty. If the presser foot shake, we should turn out a seam corresponding in crookedness to the extent of its play. Hence it is of much importance to fit the presser foot so that it may be as free from play as possible.

The cross strips, which prevent the foot from turning round, get worn ; so does the slot in which they work, but the strips suffer most. Leaving the foot in position in the arm, fasten the latter in the vice, and measure the extent of play the foot has from side to side. This is easily done with the compass points. If the play should be very great, new strips must be put in ; but if it does not exceed $\frac{1}{16}$ th of an inch, the old ones may be made to serve. Heat the end of the cross strip in the gas—after removing the foot—and, having made its opposite end fast in the vice, beat it out at the extreme end so as to widen its body. The same should be done with the other extremity.

A smooth file is now brought into requisition, and the width of the strips reduced a little. Do not, however, yet proceed to fit the foot in position until an examination of the slots in the arm is made. A thin ward file should be used to render the sides of the guide slots parallel, and the foot may then be fitted to them. Much care should be taken to get as wide a bearing surface as possible, and that the strips may each fit its slot equally well. It is usually best to fit the ends to the slots from the outside first, and then to

place the foot spindle in position in the arm for final fitting. The result should be that the foot should move in position with perfect freedom, and yet be *free from play*. There is no remedy for a worn spindle except a new one, but it is rarely that the mechanic meets with a spindle so much too small as to need replacing.

In fitting a new steadying pin it is always best to make it from good steel, and to polish the filed sides where they bear upon the guide slot. The slots should also be made smooth. The foot is apt to be displaced from its old position in refitting it, and it is usually a saving of time to fit the needle arm, with a needle in the yoke, in position for a trial to find whether the hole in the foot is correct. The needle plate may, however, be put in position, and this will serve to indicate whether the foot is correctly placed.

In the old style of Wheeler and Wilson machine the foot itself is of steel, being bent round in one piece, rendering the glass foot unnecessary. After use the steel foot is often much cut up around the hole, and on its under side, by carelessness in not raising the foot while winding spools. The hole must be filed smooth and finished off to leave no sharp projections. The under side usually exhibits two grooves, worn there by the feed teeth. These prevent the seam from turning, and must be filed out, and the foot finished off smooth.

It is an improvement to make such pressers hard, so that they may not be so readily acted upon by needles and feed. The foot is, however, soldered to the stem, and it is difficult to harden it without loosening the joint. The foot may be made red hot quickly in a gas flame, or by a blowpipe, and the joint may easily be kept from running by covering it with wet clay or

a damp cloth. While at red heat dip quickly in cold water, which should make the steel hard—too hard for working. To temper the foot, polish it with emery cloth, and heat gradually until a deep straw colour is apparent—cool out again, and polish up. Pressers treated in this way will stand for many years.

When a difficulty is met with by the foot cutting the upper thread, much care should be taken to bevel off the under side of the hole, more especially that to which the thread inclines when drawing up the stitch.

Glass feet often fail to fit well in the sockets. It is usual, when they are too long or wide, to grind them down to the size. The under side of the hole through the glass must be carefully bevelled off; for which purpose a centre punch with paraffin oil or turpentine should be employed, rotating the point until the edges are ground off.

If the glass foot be cracked it is false economy to use it, more especially if the crack be on the side of the hole next to the rounded end, as the thread jams into the slit and breaks or chafes. These crystals are cheap enough, and should be replaced when cracked. The cause of such breakages is usually too tight a fit in the forked foot, which should be sprung further apart, or the foot should be ground narrow.

The Foot Lifter.—A word about the spring and lift collet, and we have done with the presser in this machine. Nothing wears a machine out more quickly than too strong a presser spring. It is a constant drag upon the feed cams, and speedily puts them out of shape. It wears out the feed bearings, the feed tongue, and the whole machine. In the case of a band driving a pulley, we take care that it shall be just tight enough to overcome the resistance offered to the pulley's

motion. If the belt is too tight, we are assisting to wear out the machine, and wasting power needlessly. So it is with an over-press of spring upon the feed teeth. It is not easy to give a rule to work by in laying in new springs; the point can be decided best by a consideration of the class of work to be sewn by the machine. Two springs are usually supplied with the Nos. 1, 2, and 3 Wheeler and Wilson machines. The weaker of the two should suffice for all white work, and the stronger for cloth. The so-called "tailor's spring" supplied with the machine is a mistake. When the work becomes so heavy as to need so much pressure, it is assuredly too thick for the Wheeler machine of this type to work, and such springs only serve to wear out the machine.

The lift collet and lifter are usually very much worn. In some cases the collet, which is screwed down by the top thumb screw, is nearly cut through by its lever, and a new one may be necessary. When the wearing is not so deep, the collet may be turned upside down; but in doing this the projecting tongue on the collet must be smoothed round with the file, so that the lifter may not grind upon it.

In alterations of the lifter, or in putting on a new one, the foot is often raised too high, so that the needle yoke, at the lowest point of its stroke, often strikes it. This takes place when the foot is raised in winding the spools. Examine the lifter to find if it be the cause, as the simple turning of the collet may do it. But the fault often lies in a totally different part of the mechanism—in the bolt for fastening the hinge bar to the rocker. The extent of rise and fall in the needle arm is regulated in a great degree by the slot cut in the hinge bar referred to. This bar is adjusted

by the bolt through the slot; if the needle arm, when the machine is set up, should vibrate too far to the lower side, the hinge bar should be shortened by raising it up and bolting down firmly.

The Pivot Screws.—These are the taper-pointed screws upon which the rocking bar vibrates. They are usually of fine steel, and should be quite hard. After cleaning well and filing up the jam nuts, if they should present a bad appearance by the wrench slipping in turning them, the points of the screws should be examined. If the points show grooves, or, when tested with a straight-edge, a bulged form, they must be ground down truly to the correct angle, and made quite round and smooth. When the grindstone is not available, it will be necessary to soften the screws by heating red hot, when they may be finished up with the file; they must be again hardened by heating to redness and plunging in oil. But when it becomes necessary to soften the screws, it is better, if possible, to turn the points up in the lathe.

The taper of the pivot holes in the rock bar must be examined, and if it be much out of truth, a taper countersink should be used between the lathe centres to true up the holes. If the rock bar should not already be provided with oil holes leading into the pivot apertures, holes should be drilled.

The Hinge.—The joint connecting the eccentric rod with the rocking bar and needle arm is known by this name. In most cases it is much worn. When this joint wears loose it is a common idea with mechanics that to tighten the set screw puts it right. This should not be depended upon when the machine is worn to any considerable extent. Owing to the direction of the thrust in the connecting rod, the pin through the joint

is worn only on one side. In some cases the pin may be driven out and reversed—turned half a revolution—which may make the joint tight for some time. The best remedy, however, for a bad joint is a new pin. If the hole in the eccentric rod is not round, a drill should be put through it. The joint should work very smoothly, and to this end the pin should be polished and truly round. Care is necessary in forcing out the pin to drive *from* the square end, and as the joint is frequently of cast iron, much patience is necessary to avoid breaking it. The adjusting screw should be so set that the joint at first feels rather tight. A little working, with free oiling, will speedily reduce it to an easy fit.

The Eccentric.—We proceed to a consideration of the faults usually found in the eccentric and eccentric band, but in doing so must state that it is only in cases when the machine has run for a great number of years that much mischief is done.

The looseness of the ring on the eccentric itself is a very fruitful source of miss-stitches in the operation of the Wheeler and Wilson machine. When the eccentric is not much worn—unequally worn—the set screw, under the eccentric band, will serve to tighten the latter upon the eccentric to the required degree. When, however, the eccentric band is much worn, instead of being a circle, its shape resembles the ellipse, and, when too tight for one part of the eccentric, is too wide for the other parts. The only remedy, when the band and eccentric have lost their truly round shape, is to turn them true in the lathe. Some mechanics *file* up both band and eccentric to the round, but this requires much skill and patience.

Outside calipers should be used to test the eccentric,

and if found the least deficient in truth, the adjustable jaw or other chuck in the lathe must be brought into requisition. The eccentric should be chucked true by seizing the cam at the opposite end, and the eccentric end should have driven into it a plug of brass, in which a mark may be made for the dead centre to bear against. In this way what may appear a difficult piece of work is rendered easy, and the truing may be effected in a few minutes. Only the least quantity of metal should be removed, and the work finished by polishing.

Examine the band next, and in this manner:—With a strip of FF emery cloth polish the interior face of the band. This, as it gives an equal appearance to all the surface, will enable us to determine at once the points where the now true eccentric bears most heavily. Place the eccentric in the band, and screw up the latter until one will turn upon the other tightly. A few turns will mark the point of friction and the shape of the band. To true up the band the lathe should be used, but if this should appear too difficult to accomplish, a sharp steel scraper, with a smooth half-round file, may be employed to reduce the high parts. In either case a few trials and a little patience will enable the mechanic to produce a very good circle.

In some cases, in careful hands, the eccentric, once trued up, can be *ground* into its place with a mixture of grindstone dust and water. With patience the whole operation may be got through without the aid of a lathe. Much care is, however, necessary to *perfectly* clean off all traces of the cutting dust when the work is finished. On no account should emery of any size be employed; it gets embedded in the iron, and afterwards cuts up the eccentric. It is of importance that the

screw for tightening up the eccentric strap should be tight in its hole; if it be loose the motion will cause the joint to give way and "play wide." The eccentric strap should be tightened up until no play can take place in it when the eccentric is oiled.

The Drum.—The leather-covered pulley is usually called the drum. When the leather is worn thin and smooth it should be replaced. This can be done with common leather glued or stitched on, and neatly spliced to overlap without protruding. Two holes must be punched in the leather for the set screws. The heads of these screws will serve to keep the covering in position, should the glue at any time give way.

The Feed Cam.—In very few cases is the cam worn so much as to need repair. When, however, it fails to lift the feed high enough above the plate—when the feed tongue is in good repair—or does not throw the feed far enough to give the required length of stitch, the file must be used upon it. It will be necessary to file down the raising cam where the feed tongue *falls*, and to leave the *rise* of the cam as high as possible. This must be done gradually, and a good curve given to the cam, especially where it commences to *raise* the feed.

The throw side of the cam, which carries the feed and cloth forward under the presser, should be treated in the same way. Both faces should be very smoothly finished off, because there is much friction here with the feed.

The Old Style Feed.—Up to about 1869 all the machines made by Wheeler and Wilson were fitted with what is known as the old style of feed. It consists of a long bar, grooved out in the centre longitudinally, containing a second bar, hinged at one end, known as the

feed tongue. At the cam end of the feed a projection from its frame downwards is acted upon by the throw cam, and a spring at the opposite end urges the bar back against the cam, which thus reciprocates in obedience to the shape of the cam.

To obtain the necessary rise and fall of the feed teeth, the tongue is hinged to the feed frame, and is free at the cam end to rise and fall. This tongue, partly by its own weight and partly by the weight of the presser, continually bears upon the cam, which raises it up into the cloth once at each revolution of the machine.

Hence the points of friction about the feed are as follows:—1, the throw piece; 2, the feed tongue; 3, the feed frame in its bearings on the main casting. The throw piece on the feed frame seldom requires to be touched; but the bars, where they bear in the main casting, are subject to much friction. When the machine is in motion the forward movement of the cam tends to throw the whole feed *from* the operator, and to bear more strongly upon the off side of its seat. Hence the necessity to turn attention to the farther side of the feed bar for repairing purposes. Very often the farther side will be worn quite deeply. In this case pieces of steel or iron may be dovetailed into it to make up for wear. File out a length of about one inch at each worn place. File deeper than the wearing surface, and fit beveled end pieces of iron into the openings; after these are fastened firmly in, a little solder may be run in to keep them in position. All solder and superfluous metal must be filed off, and the bar fitted as before to its seat. It must not have any movement except in a lateral direction.

The feed tongue, at the point of its bearing upon the

raising cam, begins to wear away very shortly after the machine has been in use. In two or three years a deep depression will have been worn in it, and the feed teeth, which should at each stroke rise $\frac{1}{16}$ th of an inch above the needle plate, will probably be below the level of the latter, and fail to catch the fabric to be sewn. A large irregular cut will, in fact, be found in the tongue, as wide as the widest portion of the raising cam. To remedy the defect without replacing the tongue, this worn portion should be dovetailed out with a small half-round file, and a piece of good steel fitted to it. In order to obviate the necessity of using solder, which is unsuitable at this point, the steel plate should be fitted in from one side, and riveted in position, when it may be filed to shape.

If the feed point should prove to be hard, it must be softened by heating red hot. The teeth should next be sharpened by carefully filing out with a fine half-round file, when the feed should be placed in position, with the cam and hook in their places, to test its height with the cloth and needle plates. The height must be such that the feed shall raise the presser $\frac{1}{16}$ th inch, and fall below the level of the plate upon continuing the movement of the cam. This height can be adjusted by filing the raising block on the tongue, when it should be smoothed and rounded over. The feed must have full freedom of motion in its place, and must not bear upon the slots in the needle plate when vibrating. The teeth should finally be hardened—heated to redness and plunged in water; if not too hard to be cut with files, the process must be repeated. When properly hardened polish the back of the points, and heat very gently until a deep straw colour appears, after which quench in water.

The Stitch Regulator.—In the old style of machines the length of stitch is regulated by a stop fixed to the under side of the plate. This stop prevents the feed from falling back past the length of stitch required, and the feed bar constantly beats against it as, drawn back by the spring, it prepares for each successive stitch. Hence the stitch stop must be very stiff to turn, and should not be oiled. A few taps with a riveting hammer will usually tighten its stud sufficiently. To prevent undue noise by the beating of the feed against its stop, a plug of leather is usually screwed into a hook in the butt-end of the feed—this should be renewed when required. Too much play between the top of the feed and the under side of the cloth plate will give rise to much noise. In some cases, where the feed is good and the seat of it has been deepened, a little can be filed off the main casting to bring the plate farther down upon the feed.

The Bridge Feed.—This very silent form of feed has been fitted to a large number of machines. It does not lie longitudinally under the plate like the feed last noticed. The stitch is regulated in this feed by a taper-pointed screw projecting from the feed outwards to the front of the machine, under the cloth plate. The repairs necessary to this form are few, as the wearing parts are, for the push and rise, hard steel blocks, and sometimes horn and vulcanite, which make noiseless bearings. The teeth are adjustable as to height by a screw, and may be taken out and sharpened as before. When the socket in which the regulator screw works becomes too wide to grasp it firmly, it may be heated and pressed together. It is split to seize the screw with an elastic grip.

The Draw Feed.—This excellent device is probably

the best form of feed for fine fabrics yet invented. Its parts are, moreover, so well adapted for continuous work without wear that instructions can hardly be given for repairing it. Except, perhaps, to sharpen the teeth, which are skilfully made to surround the needle hole, the so-called draw feed, as at present applied to the Wheeler and Wilson machines, calls for very little attention from the mechanic. The length of stitch is regulated by the taper screw referred to under *Bridge Feed*, and also by the older stop, as applied to the old feed, in either of which cases previous directions fully apply.

The Rotating Hook.—The construction of this ingenious device has been already explained. In inexperienced hands the rotating hook is subject to the worst kind of treatment. The main part of the mechanism in these machines is the hook; each stitch taken passes over the hook with lightning rapidity, and is subject to much friction throughout the revolution if the hook is not highly polished.

The most usual fault of the hook at high speeds lies in its tendency to cut or chafe the upper thread. When a hook is "timed" correctly, and when the needle is properly set, with other attendant conditions favourable to good stitching, and when, at a moderate speed, the machine breaks or chafes its upper thread, the fault in almost every case lies with the hook, the surface of which is rough or sharp through carelessness.

Roughness of the hook is caused chiefly by the needle. When the needle is bent in any direction out of the correct line it will injure the hook and cut it. Sometimes hooks are made so hard in temper that the needle cannot mark them; this is a very desirable condition, and ought to be universal. When the needle is

bent slightly to the right it cuts the hook upon the right side of the clearance slot, and upon the left side of the hook point; it also strikes the point itself, and blunts it. When the needle is bent still farther to the *right* very great damage is done to the hook, for the outside face is cut all round, and made so rough that no thread can pass over it without being cut. When, on the other hand, the needle is bent to the *left* it cuts up the neck of the hook on the left side, and breaks its point on the left flange of the hook. When the needle is bent *from* the operator it has little opportunity to damage the hook before it is broken on the needle plate. When, however, the needle is bent *towards* the operator it may, before striking the needle plate, do much harm to the neck of the hook.

When the needle is set *too high* simply, and is otherwise straight, it cannot harm the hook.

When, however, the needle is set *too low*, and is otherwise correct, much damage is done to the hook at the neck.

Hence, the rotating hook is subject, like shuttles, to much damage by carelessness on the part of the operator. It is to be noted, however, that all such damage is due to carelessly set needles. When care is taken to properly set needles, a rotating hook will never cut thread or miss stitches. The first duty of the mechanic is to become acquainted with the causes and localities of such defects, and to use judgment in their obliteration. *Not one grain more of metal than is absolutely necessary should be removed in repairing hooks.*

Faults at the Neck of the Hook.—When a hook is of soft steel, the thread, where it crosses the under side of the point, just at the neck, makes a deep cut. This should be as nearly as possible filed out, and the part

well curved to leave no sudden dents for the thread to fall into. Again, when the hook is soft, the thread wears a groove in the front of the neck. This also should be filed out and curved off the first-mentioned point. On the neck of the hook the needle makes many cuts. These must be filed out, and the original shape of the neck carefully preserved; any filing at this point should be gradually curved off into the thread channel.

Faults at the Point.—When the point is blunted, much care should be taken to avoid shortening it in filing up to the original shape. It is further of importance that the point shall *not* be sharp, and that the under side be carefully rounded off. Along the under side of the point, down to the neck, an examination for indentations should be made, and every irregularity filed out. The outside of the point must be carefully filed smooth, and curved to the face of the hook, and the inside, which is flat, must be filed until all cuts are removed. All such filing operations can be best done with a three or four-inch half-round smooth file. Every part must be finished off smoothly, first with a long strip of FF emery cloth, and finally with O cloth. Emery strips for this purpose may, if preferred, be oiled, which causes them to cut more smoothly.

The Face of the Hook.—Scratches on the face of the hook are best removed as follows:—Oil a smooth flat file, revolve the hook at high speed, and hold the file upon its face at an angle to coincide with it. The result will be to take an equal quantity of metal off every part of the flat face, but much care is necessary *not to make the spool cavity any shallower*. No more than is absolutely necessary should be taken off the hook face. Sometimes this treatment is necessary

with old hooks that have become rounded or convex on the face; in either case the flattening operation should be performed while the hook revolves, and with an oiled file held *firmly* in both hands at the requisite angle. The finishing should be done in the same way, but with emery cloth of different degrees of fineness wrapped around the file.

The *Cast-off Loop Slip* or *Chamfer* should be examined to find if it is rounded or too convex through wear. When the chamfer is too convex, the loops have a strong tendency to slip before their time. A half-round file may be used, and the slip must be carefully graduated into the hook face.

Final Smoothing.—The hook should be finally highly polished with a pad of the finest emery cloth held in the fingers against every part of it while it revolves. The thumb nail should be run around all the face to ascertain whether any lumps or depressions are left. The spool cavity should be examined, and any cutting made by the spool edges smoothed out. The edge of the clearance slot, projecting into the spool seat, must be made round and smooth. A piece of thick soft felt, with a paste of fine emery flour and oil spread upon it, is very useful in rapid smoothing.

As will be judged from the foregoing directions, the hook is a point of much importance in repairing a Wheeler and Wilson machine. Although the process of finishing off the hook may appear lengthy, yet an ordinary workman should be able to do it from first to last in one hour. Too much care cannot be bestowed upon the repairing of hooks—it is well repaid afterwards in the facility with which the machine will do its work. In every case the mechanic should strive to restore the hook to its original shape and smoothness. In some

instances much more filing and finishing than that mentioned will be necessary, but so much must lie with the judgment of the mechanic himself, that it is almost impossible to grasp in one set of specific instructions all the circumstances under which the rotating hook may be defective.

The Check Brush.—The most obvious use of the brush is as a check upon No. 1 loop until No. 2 loop has been secured by the hook point in the succeeding revolution. The brush, therefore, plays a very important part in the making of stitches. Suppose that we draw back the brush, while the machine is in order, so that it shall allow the thread to pass between it and the hook, we find the loop carried, but only with slight force, upwards; the loop speedily gets out of shape, assumes a twist, and is finally thrown in a heap upon the needle. This is caught by the hook point when it revolves to the needle, and the result is obviously either a miss-stitch, or the hook seizes the entangled loop and breaks it. This cannot take place if the loop be stretched upon the hook, or checked by the brush until the chamfer shall release it.

Well-made hooks are so constructed that the friction upon the loop check (which was formerly of leather) is very small, owing to the hook only bearing upon it for one-half the revolution. Hooks made upon an inferior plan, which bear upon the brush during the complete revolution, therefore wear the brush out in half the time occupied by well-made ones. Some mechanics who thoroughly understand the hook, may with advantage file off the superfluous metal wearing the brush in the part of the revolution after the loop has left the hook. In most instances of machines in need of readjustment, the brush should be simply renewed. The brush holder

should be examined to find whether the set screw is in order. Particulars relating to the setting of brush segments and brushes are given farther on, under "Adjusting and Timing."

Spools.—Four disc-like thread spools are usually supplied with each machine. When the needle is bent to the right, the spools get cut and scratched. These scratches retard the motion of the thread over the spool, and sometimes cut the loops, while they further prevent the spool from revolving freely as the under thread is wound off.

Each spool should be placed upon the spool spindle and quickly revolved by the machine, while some rough emery cloth is held tightly by the finger against its face to smooth down the scratches. The idea cherished by some mechanics that the marks and scratches must be obliterated is, however, erroneous. It is only necessary to remove the cuts so far as they affect the edges of the spool, and to smooth both faces. The inside edges of the spool may also be smoothed by inserting the edge of a chip of emery cloth. If the spool be deeply cut in the edges it is useless. The faces should be finally smoothed down. All spools should be of the same size, and when it becomes necessary, from the extent of damage sustained, to make the diameter less, the spool should be replaced. Spools should never be heated to remove old cotton. The thread picker will usually suffice, or a steel wire made sharp, thin, and pointed at the end may be used with advantage.

The Spool Ring.—The revolutions of the spools between the hook and the spool ring wear away the face of the latter, which becomes at length so flat that the bearing surface of the spool is too great, preventing

the thread from passing over freely, and retarding the motions of the spools, which fail to revolve when required to pay out thread.

In most cases the half-round file should be employed to deepen all parts of the spool ring not originally intended to bear upon the spool. When this is done, the projecting portions must be carefully rounded over. If too great a bearing surface be left, the spool will fail to revolve freely. When the spool ring is pushed into position, an adjusting screw fastened below its face prevents it from approaching the hook too closely. By screwing or unscrewing this stop, the ring may be set at any required distance from the hook face. This set screw, as its position alone determines the play of the spools, should fit into its hole tightly, and must not be capable of being easily screwed back or forth. The face of the ring should incline inwards to answer to the curve of the spools, and should be made as smooth as possible. In order to test the spools in position, the machine should be put partly together, and the spool ring set so as to give one of the spools a slight and given amount of play; if all the spools feel of the same size between the ring and the hook, they are right, and should all work well. But if large and small spools be found, the large ones should be kept out and new ones substituted, or *vice versâ*, according to the number of spools that fail to fit.

The Needle Plate.—The needle, or *throat* plate, as it is sometimes styled, is usually made to fit in grooves in the cloth plate, so as to be readily removable. Two needle plates are usually furnished with each machine, one with a small needle hole for fine work, and the other with a larger hole for the heavier classes of work. They are generally held in position in their grooves in

the cloth plate by one of the four plate screws, and may be changed by removing the screw and drawing out usually with a pin provided in the needle wrench.

Owing to carelessness on the part of the operator in setting the needles in the machine, they strike against the needle-hole edges and cut them up. Even although the needle be properly set and kept in correct position, the needle hole will in time get cut in the edges by the thread. All cuts and roughnesses must be removed from the hole edges. When the cuts are not deep a fine round file will serve the purpose, and the needle hole need not be made much larger. Much care must in all cases be taken to *well bevel off the inside edges* of the hole. This is of great importance. The loops in passing upwards into the cloth are pulled with much strain against these edges, and if the way be not clear the thread will choke up the aperture. The sides of the thread slot prolonged from the needle hole must also be bevelled off at the under side. The top edges should *not*, however, be so bevelled off. If the top edges be bevelled away, the needle will jam the fabric into the hole and slot in working; they must be made free from all sharpness, however, and smoothed over.

If it should appear from the condition of the needle hole that it will be too wide if filed clear of cuts and scratches, it will be advisable to fill it up and to make a new hole. To do this, file or drill out the hole as large as possible without breaking into the feed slots, and bevel each side slightly. Fit a piece of soft steel wire to the hole, cut it off to the thickness of the plate, and slightly rivet it in position to quite fill up the old hole. In some cases it may be advisable to afterwards run a little soft solder into the joint, but if the steel be made square to fit a hole of similar shape, this will

be unnecessary. It is not advisable, except in the case of fitting larger pieces into plates, to bronze the joint, as the heat necessary for this operation usually destroys the steel. The plate should now be filed flat, and polished, and *put aside until the machine is adjusted and timed*. The reason for this is that it is impossible to strike the exact position for the new needle hole until the needle arm with needle be perfectly adjusted in position in the machine.

Assuming, however, that the machine is adjusted, and the needle accurately in position according to the instructions given farther on, it will only be necessary to lower the needle arm gently upon the plate screwed into position, *so that the needle point may accurately mark the point for the new hole*. When the required indication is obtained, a centre mark is made at the point, and a fine drill is run through the plug in the old hole. The plate should again be tested in position, and note taken of the needle as it enters the new hole, which can be widened out to the side required to make the needle pass downwards accurately in the centre.

Size of Needle Hole.—It is somewhat difficult to give the sizes of needle holes, so much depends upon the work to be done by the machine. The mechanic should always endeavour to ascertain the class of work to be done, and make the needle hole to answer to it. As a general rule for Wheeler and Wilson machines to produce ordinary “white work,” the needle hole should be large enough to let a No. 4 needle pass easily, but not loosely, through it. For finer work the hole may be slightly less. In any case the needle hole should be large enough to allow sewing to be done with a No. 2½ needle.

When coarse and heavy work is to be done, the hole may have a diameter of one-sixteenth of an inch, or

even more. The hole should thus be large enough to allow of free sewing with a No. 4 needle. When the needle hole has been widened out to the required size, a slitting file, or a fine saw, must be used to open up the thread channel to the hole as in the original condition of the plate. Much care must then be taken to chamfer off the under side of the slot, and to make it smooth and regular. For both of these purposes there is nothing better than a long narrow strip of FF oiled emery cloth. The plate should be gripped in the vice, and the cloth entered in the slot and worked back and forth until the desired result is attained. In doing this it is necessary to *avoid* chamfering off the *upper edges* of the slot and hole. These edges must, however, be *slightly* rounded and smoothed.

The Under-Thread Check.—This is a metallic finger soldered to the under surface of the cloth plate, and extending across the needle plate a little to the right of the needle hole. Its function is to keep the under thread up to its work, and to prevent loops from getting twisted in the thread slot while being drawn up. Care should be taken that this finger is smooth on its edges. It seldom calls for repair.

Testing the Needle Yoke.—This may be done while the machine is being put together. Through various causes the needle groove gets worn or put out of the vertical line, and the result is to render it impossible to use a straight needle. To test whether the groove holds the needle straight, place the needle arm between the pivot screws moderately tight, and fix a *straight* needle in the yoke firmly. Now slowly lower the needle while you hold some edge near to it on a level with the needle plate. If the needle deviates in the slightest degree from the correct line, to right or left,

the defect will at once be noted. A slide tool should, properly speaking, be used with which to cut the needle groove straight, but with care it may be done with a small saw file. Only a little should, as a rule, be taken off. If the needle bend to the right, the groove must be deepened *above* the hole, and if to the left, the file should be used below the hole through the needle arm. Note should also be taken of the *curvature* of the needle, and how it lies in the groove. The curvature of needles should exactly correspond with the arc described by the point of the needle yoke, otherwise the needles will never play into the hole straight, and will, further, tend to displace the fabric sewn. Even although the curve may be correct, the needle yoke may not so clamp the needle as to allow it to describe the required arc. In this case the groove must be looked to for the fault. Perhaps the most generally applicable way in which to give a curved form to the groove, should it be required, is to lay a metallic block, such as a surface plate, upon the cloth plate, and to clamp a diamond-pointed tool to this, to act upon the groove while the arm is moved up and down.

Polishing the Parts.—The importance of finishing off all the parts of a machine by polishing cannot be too strongly insisted upon. It tends to make the mechanic more accurate in his work, and gives a workmanlike appearance to the whole machine when finished. For the cloth plate, which is the largest part to be polished, the revolving buff, with emery upon it, is usually best suited, but in some instances this is done by hand, which is a very laborious method. All the circular parts, such as screws, should be polished in the lathe by pressing the emery cloth against them while revolving. Electro-

plated parts, such as the arms, should be cleaned with rouge or a paste of chalk and water, and finished with a piece of soft leather. The smaller flat parts, which cannot be put upon the polishing buff, must be finished with a flat file having emery cloth wrapped around it. All rough and broken edges of screws should be filed smooth, especially those for the cloth plate.

Adjusting and “Putting up” the Machine.—Commence “putting up” by screwing the eccentric into its ring by the end disc. Next screw on the brush segment or holder, fastening it about the middle of its slot for the present—keep the brush itself out. Put the leather-covered pulley in position, with the eccentric to the left hand, and push in the hook shaft right through both bearings and drum. Press the hook and drum together to prevent any end play, and fix with one of the set screws in any position for the present. Screw in the pivots in their holes in the back standards, and draw back their lock nuts for convenience of adjusting. Place the needle arm in position, with its rock bar between the screws. Select a *straight* and accurately curved No. $2\frac{1}{2}$ needle, and fix it in the needle yoke. Bring down the needle arm slowly, and turn the hook until its point is upright. Now note the position of the needle in relation to the hook point. Draw back, or put in, the pivot screws, keeping the rocker tight between them, *until the needle shall descend so as just to clear the hook point to the right of it.* Lock up the pivot nuts in this position with much care to secure the rocker between them moderately tight. This tightness will wear off after the points have been oiled. Bring down the needle again, and note whether the locking-up has disturbed the required adjustment. If not, lock the nuts still more firmly.

It is *now*, when a new needle hole has been arranged for, that the point for drilling must be marked by the needle. Take note of this, as referred to under "Needle Plate," p. 118.

If the machine should be intended for heavy work with No. 3. needles as the smallest, then adjust as directed, using a No. $3\frac{1}{2}$ needle. It should be particularly noted that the needle arm is supposed to be *quite free* from connection with the hinge or eccentric rod during these adjustments.

Now remove the needle to prevent possible damage to the hook. Take the hinge piece, as jointed to the end of the eccentric rod, and place it in position for screwing upon the rocking bar. Note particularly if it *lies flat* upon it. If not, the back of the hinge piece should be filed until it does lie flat. Place in position, and enter the set bolt upon it. Screw the set bolt down while the slot is in mid position, and carefully note that the eccentric revolves quite freely, and that the adjustment at the hinge does not *twist* the eccentric ring. Screw the set bolt home firmly, and oil all the friction points in the machine. Put on the strap, and, irrespective of "timing" for the present, run the machine to test whether the motion is smooth. This being satisfactory, before proceeding further the machine may be "timed."

"*Timing*" the Machine.—This operation embraces the accurate adjusting of the hook and feed to the motions of the needle. In the Wheeler and Wilson machine the feed is timed by the cam, upon the end of which is cut the eccentric giving motion to the needle, so that the feed and needle always move together. Hence the feed moves up and takes its stroke while the needle is above the fabric to be sewn. The feed is, therefore, in

position and time while the needle arm is correctly set.

To time the hook, which is the only part requiring attention, place the No. $2\frac{1}{2}$ needle in the needle yoke *at the correct height*, either by the mark upon the needle stem or by means of a needle setter. Throw off the strap, turn the pulley, and loosen the hook-set screw. Bring round the hook point to the vertical line, holding the pulley from revolving meanwhile. Hold the hook, and with the pulley bring down the needle slowly until it dips and rises again about $\frac{3}{16}$ ths of an inch. In this position the eye of the needle should be on a level (horizontally) with the upper edge of the shield at the back of the hook, and the hook point should be even with the needle. Fix in this position while pressing hook and pulley lengthwise together to take up all end play.

The machine is now, *approximately*, in "time"—it may be accurately, but this must be further tested. It will be necessary, however, to adjust the brush and spools, and to put the machine in working condition, before the accuracy of the timing can be proved.

Adjusting the Brush.—At what spot on the hook, when the point of it is opposite to the needle, should the brush check the loops? The question cannot be answered off-hand, nor can a rule be given as to any unvarying position. The "segment" to which the brush is attached allows of room for adjustment, and by slackening the set screw the brush may be set at any required point. Set the brush so that the commencing end of the hook chamfer shall be opposite to its central line when the hook point is opposite to the needle. *The brush must not release the loop of thread until the hook point has fairly entered, and commences to draw the succeeding loop.* If this rule be followed very

little difficulty should be experienced in adjusting the brush.

In instruction books it is stated that "the brush should press snugly upon the hook." This word snugly is very indefinite, as it leads some operators to make the brush only graze the hook, while others push the brush so far that the chamfered portion is touched; the first fault causing entanglement of the loops, and the second, breakages and general confusion. In point of fact the brush should only touch the hook with sufficient pressure to stop the loops from passing, but it is customary, even by most experienced mechanics, to press the brush closer than is actually required, so that it may continue to act for some time without attention.

Adjusting the Spool Ring.—The spool ring must be near enough to the face of the hook to prevent the spools from slipping out of their cavity, and also to prevent the loops of thread, as they are slipped off the hook, from *passing into the spool*. Moreover, the ring must be far enough from the hook face to allow the spool free play, with space upon either side to provide room for the free passing of the loops over the spool. There are two extremes, therefore, which must be carefully avoided. Set in a spool, and allow the thread to run off from the top, to turn the spool towards you from the top. Feel with the finger the play the spool has. It is easy to judge whether it is too loose or too tight. It is wise to err on the side of having the spool too loose rather than the reverse. Place a pin in the hole of the spool, and *incline its far edge outwards*—this will at once indicate whether it is too loose or not. If the edge of the spool can be made to project beyond the edge (chamfer) of the hook, it is too loose, and would

sometimes permit the loop to slip *into* it instead of *over* it. The adjustments of the ring are obtained by screwing and unscrewing the set stud in front.

Testing the "Time."—Place the presser arm in position, with the presser hole accurately over the needle hole, and screw firmly home with the largest screw-driver. Fix in also the feed and cloth plate. Thread up the machine with No. 50 or 60 cotton, and place a wound spool in position. Put the end of the under thread in the thread wire under the front of the plate, or take it up through the needle hole. Place under the presser three thicknesses of calico, drop the presser, and proceed to slowly turn the machine, holding the ends of the threads meantime. Look under the plate, and observe the hook taking the first loop; notice how this loop is carried round behind the spool, and how, when the hook has performed half a revolution, the loop is made to slip off the chamfer and pass gently over the outside of the spool; observe also, as the revolution is completed, how the loop is arrested by the brush and detained until the hook has well secured the succeeding loop, thrown out by the needle in its rise. Take, in this way, two or three more stitches, and then narrowly watch them to test the time as follows:—If the thread slip off the hook with a snap, or even with a little tension, the hook is *too slow*, and must be moved forward by again adjusting it with the set screws in the drum—for this purpose the plate must be taken off. If the loop should slip off the chamfer loosely, look at the position of the needle eye at that instant, and it will be seen that the loop slips while the eye is yet $\frac{1}{8}$ th or so above the fabric. In this case the hook is *too fast*, and must be taken back a little. Finally, when the loop slips

just as the needle eye is about to enter the cloth, and without much tension, and noiselessly, *the time is correct*. All these directions are good *provided* that the needle be *set accurately*.

If the needle be set *too high*, the time may be correct, but the loops may entangle by being thrown over the spool with too little tension.

If the needle be set *too low*, the time may be correct, and still the thread will be broken by being thrown from the chamfer with too much tension.

After the various adjustments noted above have been carefully attended to, and are deemed correct, the machine should be tested by running it at the highest speed attainable by foot, upon at least three layers of good stiff calico. The thread should be rather fine, and there should be no necessity to use the thread oiler to prevent the upper thread from breaking. The stitching should easily stand the full necessary tension upon the upper thread, and there should be no tendency to ravel with a tension too loose. With short and long stitches the machine should run equally well. When the goods being sewn are loaded with "dressing," which causes great friction and heat at high speeds, the thread oiler should be used.

Breaking of Silk Thread.—It often occurs that a machine may be found to sew satisfactorily with cotton thread, and yet will break silk thread. Silk is much easier to chafe than cotton, and the defect usually lies in the roughness of some part over which the loop is drawn, or in the spool being too tightly confined. It is often necessary to examine the needle eye for sharpness, and to use a larger size.

Faults.—Missed stitches are caused by several faults. The needle may be too high or too low. It may be

bent away from the hook. It may also fail to throw out a loop for the hook to seize. This latter fault may be caused by several derangements. The needle may be too fine or too coarse for the thread, or the brush may stretch the preceding loop too tightly. The needle hole may be too small. The material may contain "dressing."

Thread breaking may be caused by several faults, as before noted under "Hook." The tension may be too great, or even too loose. The brush may fail to check the loops by pressing too easily upon the hook. The spool ring and spools may be rough. The hook may be rough. The under side of the feed point may present sharp corners for the loops to catch hold of. The needle-plate hole or groove may be too small, or may be sharp or rough. The needle eye may be sharp. And finally, the thread may be chafed in passing over any of the guides, or in sewing stiff materials.

Want of regularity in the stitching is usually caused by the feed being loose in its seat, by deficiency of oil about the feed bar and cams, or by a bent needle and loose presser foot.

Failure to feed is usually caused by blunt feed teeth and want of sufficient pressure upon the cloth, or by the feed teeth being too low.

Noise.—Noises are due to several causes, but the most important has reference to the needle arm. This arm should be *without play*, apart from that given it by the eccentric. Grasp the needle arm at the end, and test the steadiness. If there should be an up-and-down motion of even $\frac{1}{2}$ nd of an inch, the machine will make much noise, and an increase of play will cause it to produce bad work. Take up all play with the hinge and eccentric-strap set screws. The next most important

cause of noise is the feed, which may be badly fitted, or without a leather abutment at the end, or without oil.

Oiling.—All friction points must, of course, be well oiled. The feed must be well oiled at all bearing and friction points. The bar type of feed must be oiled on its top side, where it rubs upon the cloth plate. The presser bar should be oiled. Sperm oil only should be used, and it is often advantageous to thin it with petroleum or paraffin oil. Paraffin may also be used to make machines run freely when clogged up with old oil. Do not oil the check brush or the tension pulley. Some lubricants are too thick and strong for sewing machines, and should be thinned. For machines not in constant use, a mixture of almond and sperm oils, with a small percentage of paraffin added, will prevent them from getting gummed up.

Every machine should be thoroughly tested by running upon several kinds of material at high speeds before it is handed over to the customer, who should receive with it a sample of its work in silk and cotton thread, with a special needle setter, should there be a necessity to set the needles higher or lower than formerly.



CHAPTER VIII.

THE ADJUSTING OF SINGER MACHINES.

THE form of Singer machine to which we now turn our attention is made in two sizes, styled the "Family" and "Medium" respectively. They are in all essential particulars identical, and one set of instructions, having special reference to the smaller size, will suffice to show the mechanic how they should be dealt with in adjusting. The Singer machine is also made in large size, to suit tailors' work, under the style of the No. 2 manufacturing machine, and as the construction of this type is different from the foregoing, some special particulars for its management will be offered.

"Taking down" the Singer.—It is assumed that the machine has been much worn, and that a complete over haul is necessary to restore it to working condition. Commence by removing the band cover and spool winder. Take off the gear cover screwed to the back of the arm. Examine the gear wheels to find whether the teeth are broken. Since the introduction of malleable cast gear wheels the teeth seldom break, but all the older machines, which are most likely to fall into the mechanic's hands, have cast-iron gear wheels. Unscrew and take off the face plate, and remove the needle cam and bar, also the presser bar

and spring. Saturate all the parts about the "head" with paraffin oil to soften the old oil, which should now be cleaned off. Screw on the face plate and needle bar again tightly. Test the needle cam for vertical play; this is done by moving the bar up and down. Take a note of the play, for future reference (see "Needle Cam," p. 135). Test the needle bar also for play by moving it in several directions under and above the face plate. Take a note of this also (see "Needle Bar," p. 136). A box should be at hand to contain small parts. Slide out the shuttle covers or slides, and test the shuttle and carrier for wear. To do this, insert a pointed wire in a thread hole of the shuttle, and move it from end to end of the carrier. Take a note of the amount of play, and cause the carrier and shuttle to move backwards until the point is opposite to the needle; mark now whether the shuttle point clears the needle in the back stroke.

Unscrew the stitch-regulator stud and turn the machine over to render the underparts accessible. With a pair of flat-nosed pliers press out the pins holding the connecting rod in place, and remove pins and washers with the rod. Test the carrier and hanger for play upon the slide bars, and take a mental note of the amount of wear. With a screw-driver made from $\frac{1}{4}$ -in. steel wire, remove the screws holding the carrier. Before removing the feed, take away the feed spring and needle plate. Unscrew and remove the plate holding the stitch-regulator bar in position, and pull out the bar.

If it should appear necessary to put in a new friction roller to actuate the needle cam, or to insert a new gear wheel, the shafts, horizontal and vertical, may have to be removed. It will be necessary to take away

the latter spindle if it should have much up-and-down play, or if, which is very likely, the feed-cam lever has play upon the cam. Turn up the machine and proceed to drive out the pin to be found passed through the balance-wheel hub. For this purpose a very stiff and well-tempered steel punch, with a point small enough, must be used, and as the pins are always very tightly driven in, care must be taken to find the smaller end, and to drive the pins out with one or two good blows. Numerous weak blows will only serve to rivet up the pin point. If the pin be very hard to drive, it may be advisable to have the balance wheel upon the bench to prevent bending the shaft. When the pin has been driven out, a centring punch must be used to drive the shaft out of the balance wheel. The wheel should be taken away, and the needle disc upon the opposite extremity of the shaft may be removed by driving out its pin; this must, however, be done by resting the disc upon some resisting substance to avoid bending the shaft. With a centring punch mark the gear wheel upon the shaft, and make a similar mark directly opposite upon the shaft itself. This precaution will indicate the correct position for the wheel in putting up the machine; it is also wise to mark the vertical gear wheel in a similar manner. Drive out the wheel pin and remove the shaft by the balance-wheel end. Drive out the vertical gear pin, also the pin passing through the friction block at the lower end. The vertical spindle may now be pulled out from the under side of the machine.

Saturate all the parts with paraffin oil, and afterwards wipe clean.

The Gear Wheels.—Should it be necessary to put in a new tooth in a gear wheel, select a sharp warding file

and make a deep slot in the place for the new tooth. Keep the upper end of this slot accurately to the width of the old tooth. Make the slot taper inwards, and dovetail it towards the bottom, to resist any tendency to slipping upwards. For the new tooth select a good piece of soft iron, and file it up to the taper required to fit closely the aperture made for it. Keep it full height and width for subsequent fittings. When well fitted, cut it off a little longer than requisite, and tap it gently into position. Mark the bearing points, and fit still closer by filing them off. Slightly chamfer off the edges towards the taper end of the slot. Place the new tooth in position, file off all superfluous metal on the smaller end, rest the thick end on a block, and carefully rivet the small end over the chamfer spoken of. If this is carefully done, and the tooth well fitted, it will stand as well as a tooth cast in the wheel. Finally, file off the thick end, and finish up the tooth with a thin file to the exact size of the others, and note well that the pitch distance is equal upon both sides. It is seldom advantageous to put in more than one tooth. A new wheel should be fitted when two teeth are broken, if they are not at different parts of the wheel. Never attempt to *solder* teeth in position.

To fit a new wheel procure the wheel of the new pattern in malleable iron, if the pitch should agree with that of the remaining old one. Gear wheels all are made to one uniform pattern, and are procurable for the horizontal and vertical spindles; the wheels for the latter have smaller holes. The wheel should as nearly as possible fit the shaft. If it be too tight, a round file may be used to ease it, but no attempt should be made to fit the hole in this way if it be too small for the shaft, nor will it do to drill out a hole too small.

In either case the wheel *cannot*, except by a rare chance, *run true*. File off all rough places and burred hole edges from the shaft before fitting the wheel. Each gear wheel is fitted with two screw holes; these are convenient in setting, as set screws may be inserted in them to hold the wheel until the point for the pin hole has been found.

Put in the wheel, with the set screws at right angles to the pin hole in the shaft, and test by running with the other wheel whether the pitch of teeth will agree. Take off the wheel. Fix the shaft in the vice with the large end of its pin hole up. Scratch a straight line along the shaft, passing it through the pin hole. Make a centre mark with the punch upon this line two inches from the hole. Gauge a pair of compasses with one point in this mark, and the other accurately opposite to the centre of the pin hole. This is a gauge to be used hereafter, and in case the compasses should be altered, reverse the point over the hole and make another mark upon the line, which will indicate the required spot. Fix the wheel now in position with the set screws, and run the wheels together rapidly. Tap the new wheel towards the fixed one until the "back lash" is insignificant; allow only slight freedom between the teeth, consistent with as little noise as possible. When finally satisfactorily fixed, take the compasses, set to the gauge as before, and mark the wheel with a line. This mark must necessarily be opposite to the pin hole in the spindle. Make a centre mark here, and with a drill answering to the size of the hole in the old wheel small end, drill the new wheel in a straight line through to the central hole. Place the wheel now upon the shaft, and run the drill right through both of them, using the shaft hole as a

guide. Finish the hole by inserting a rimer or broach to fit the old hole.

By this method, which is certainly the quickest and most accurate, the gear wheels may be fitted in a few minutes, with no trouble or risk of injuring the parts. Should the wheels make a noise when set together and run, a little emery and oil may be put upon the teeth to grind off projecting portions. This emery must be carefully cleaned off afterwards. The wide end of the hole in each wheel should in every instance be indicated by a centre mark near to it.

The Feed Cam and Lever.—The cam which actuates the feed is cut upon the hub of the crank web fixed to the vertical spindle. Upon this cam is fitted a square collar, made upon the end of the feed lever. With wear this collar becomes loose, and reduces the available length of stitch to be obtained in the machine. To reduce the play heat the collar to redness, tap the two sides together a little, and afterwards tap in the end to accomplish this object in both directions. It is better to make the collar a little smaller than is actually required to take up the play, so that its sides may be filed flat and properly finished up to fit the cam. Draw-file and finish the sides smooth. Examine also the feed-lifting cam at the opposite end of the feed lever. In putting up the machine keep the latter cam to the lower side.

The Friction Roller.—Before fixing in the horizontal shaft the friction roller upon the disc must be examined. It is frequently found bound fast to its stud, which causes it to wear unequally and renders a new one necessary. If, however, the roller be as yet a good fit in the cam, it should be loosened from the pin with a pair of red-hot pliers, and made to run freely with paraffin oil. If the needle cam should have a vertical

play upon the roller of $\frac{1}{16}$ th of an inch, a new roller may be necessary. It is in most cases best to put in a new stud also. Friction studs and rollers should be made from the best steel only. The stud is turned up in the usual way to the pattern of the old one. To remove the old stud from the disc much care is necessary, to avoid breaking the edge of the latter. Cut away the riveted edges with a large drill, and drive out slowly. In turning up the new roller, drill a hole through the steel, and taper it out slightly to fit the new stud tightly; drive it on, and turn it up on the stud as a mandrel. It must be finished to fit the *widest* part of the needle cam, and slightly rounded in the direction of its length. When finished up it must be hardened by heating red hot and throwing into oil. The stud must now be reduced a little to fit the roller easily, but without play. A very little riveting of the edge will suffice to keep it upon the stud. In riveting the stud into the disc, care must be taken to do it well, and not to crack the latter.

The Needle Cam.—In the preceding section it is stated that the friction roller is made to fit the largest part of this cam only. From this it will be judged that the cam must now be fitted to the roller. All the tight places must be found and filed off, finishing with a scraper and smoothing up. Humps of the smallest size must be carefully scraped off, more especially at the portion of the cam pressed upon in the rise. When the cam is free from protuberances and is smooth, it will work upon the roller quite easily, and yet exhibit no play.

A broken cam is replaced by driving out its pins, having carefully marked the *height of the cam* upon the bar. The new cam has a web, which must be filed to

fit the needle-bar slot. Before drilling the holes place the cam at the correct height, and mark one of the holes only with a pointed wire through the bar. Drill this hole, and rivet the cam in position with a steel rivet. Finally, drill the remaining hole and rivet up. Observe that the cam must lie parallel to the face of the bar.

The Needle Bar.—When a machine has been *very much* worn, the needle bar will be *rounded* upon all sides instead of flat, and will be out of the straight. In such a case the cam must be removed, with the needle clamp, and the bar made parallel with the flat file and straight-edge. The original shape must be carefully preserved.

When, however, the machine has only been slightly worn, the bar need not be touched with the file. In this case the refitting can be done by filing the face plate.

In the style of machine we now speak of the needle bar tapers from front to back, so that its front surface is about one-fourth wider than its back. This design for a needle bar is very good, and, as will be readily understood, renders the work of refitting comparatively easy. If the bar is made to lie in its seat in the face plate it will be noted, if it be worn, that the seat is too deep for it, and that a space is observable below any straight-edge placed across the face. This indicates the necessity to file off the face plate until the bar becomes of the same level. In filing the face plate remove the needle bar and hold the plate in the left hand. Use a broad smooth file, and work evenly all over the surface. Only remove a little at first. Test the fit by screwing up tight, and running the needle bar by the hand wheel. If there should be more play at the lower side than at

the upper, remove and graduate the filing off from the top, taking most off the lower side of the face, or *vice versa*, as may be required. The final result should be a perfect fit, with no play, and complete freedom of motion vertically. The needle bar itself should on no account be filed unless the cam be removed first. This portion of the machine should be kept well oiled. An oil tube is provided through the head, which often gets choked up and useless.

The Needle Clamp.—Examine whether the needle clamp fits closely into its seat so as to catch the finer sizes of needles. Clamp a perfectly straight needle and screw the bar in position. Place the edge of the needle plate near to the descending needle, and note whether the latter descends straight. This must be done on two sides of the needle, any deflection of which will be due to the needle clamp, the groove in which is not straight. To recut these grooves some mechanics make a small cutting tool to screw to the face plate. In the absence of this it may be done with a turning graver supported upon an iron block of sufficient height placed upon the bed of the machine. The needle bar is made to move up and down slowly by turning the hand wheel by hand, and the pointed tool is held against it, in the clamp groove, while it descends: by these means, with a steady hand, the groove may be made absolutely straight. A file should rarely be used upon such work.

The needle clamp must be further examined at the eyelet through which the thread finally passes. Any grooves worn here must be obliterated with a fine file or a drill. The hole must finally be carefully chamfered off at both ends and smoothed.

The Take-up.—The thread take-up is fixed in a slot

cut in the head, and is pulled upwards by a spiral spring, acting by its twist, in a hole at right angles to the take-up lever itself. The spring may be applied with more or less force upon the lever as required. The eyelet at the extremity of the take-up is generally grooved by the thread, and must be opened up and smoothed to prevent chafing of the thread (see "Take-up pin" page 145).

The Upper Tension.—The thread passes from the side eyelet under and between a pair of steel discs, pressed together by a long spring within the face plate, which arrangement puts the requisite tension upon the thread. This part seldom calls for attention, except to free it from gummy oil which interferes with its free action.

The Presser Bar.—Upon refitting a needle bar, it often happens that, as the presser bar has not been worn to the same extent, it will be jammed up by screwing home the face plate. The presser bar must first be free from its foot and screw, and then filed upon its wide face to make it fit easily, but without shake.

The Presser Foot.—It is usually better to leave over the foot until the needle plate has been refitted than to do it at this stage. All the cuts and scratches must be filed out, and care taken to chamfer off the under side of the needle slot at its neck. The lower side of the foot, which often exhibits two grooves cut by the feed, must be rounded in the direction of its length and filed smooth. If the foot slot should not agree accurately with the needle hole, it must be refitted upon the bar until it comes directly over the hole.

The Needle Plate.—Needle plates are subject to much cutting and scratching by the needle point.

When the hole is only damaged to a slight extent, a round file may remove all the marks and roughnesses without making the hole much larger. But when the hole is much cut about the edges, it should be drilled out as large as possible, and a steel plug fitted to it. Slightly chamfer the edges of the hole, and rivet the plug in its place. Another plan is to cut away the corner of the plate containing the hole, and to braze in a new corner. This is somewhat difficult to do. To find the point through which to run the new hole, screw the plate in its place so that the feed may move easily through it, and bring down the needle point, which will now accurately indicate the place for the hole. Make a centre mark at the point, and run a small drill through at first. Open up the hole to the size required after again testing the position. Finish the hole by countersinking the under side, and smooth off all parts of the plate near to the hole.

Shuttle Side Springs.—A great deal of trouble is frequently caused by the side spring of a shuttle. In many cases Singer and other machines work entirely without these springs, but there is a constant tendency to miss loops or to produce bad work through the shuttle thread not being kept clear of the needle thread.

A side spring should be both riveted and soldered to the shuttle. It should be capable of slightly clamping the thread at its free end, but at the shoulder, near the rivet, there must be no such tendency, and the thread must have room enough under the spring to move quite freely, and also to strike the shoulder without any chance of jamming under it.

To put on a new spring, select one of the required length to suit the old holes. Fit it so that it may, when riveted down, fulfil the above conditions, and slightly

countersink the outer side of its hole. To rivet it, perhaps one of the most useful ready-made rivets is a soft-iron common pin, or a brass pin will answer. Put this through, cut to length, and rivet neatly on the outside. Wet with soldering fluid, run solder in, and finish with file and emery cloth.

The Shuttle.—This part of the machine generally receives very bad usage, and it fails to act efficiently as soon as its point gets blunted or its face rounded. The old make of the shuttle had the point block soldered in position, but recent improvements show the shuttle with a solid steel point, which is a decided advantage, as the point may now be sharpened again and again until the shuttle is even too short for use. The point of a sewing-machine shuttle, which is rapidly forced into and expands every loop of thread with lightning rapidity, cannot be too sharp and smooth. It will be judged from this that the shuttle point, although sharp at first, should not be too short; it should graduate slowly and smoothly to the body of the shuttle. The shuttle must also be very smooth all over its body. Any roughness at once chafes or cuts the thread, which always offers considerable resistance to sudden strains. If a thread loop is only slightly chafed in passing over the shuttle, *it will break in returning over the needle eye*, so that the fault of thread breaking is often assumed to be due to the needle when it is really caused by the roughness of the shuttle.

The face of the shuttle must be perfectly flat, as if only slightly rounded lengthwise, the shallower loops thrown out by the needle will bemissed. It must lie flat upon, and correspond with, the race. The shuttle face is very apt to become rounded, and to keep its point away from the loops. To flatten

the face use a smooth flat file; hold the shuttle in the left hand, and file until the face includes the heel and point, and stands the test of a straight-edge. This should be done before sharpening up the point or smoothing. In filing up the point care must be taken to commence graduating it from the shoulder, and to work towards the point, which should be finished last. Give as nearly as possible the original shape to the point, and finish with FF emery cloth wrapped around the file. Afterwards polish the point upon a buff, or burnish it with a rounded piece of polished steel. All the edges must be chamfered off with the file, to prevent possible chafing of the thread.

The inside arrangements are now variously designed, but the most common consist of a spring and a fixed centre, between which the thread bobbin is held while it revolves. The chief fault is a spring too weak, so that the bobbin slips out, or the fixed centre may be worn out of all shape. If the spring is not broken, it may be strengthened by softening in the gas flame, pulling out a little and plunging into oil to harden it. To temper the spring, blaze off the oil and cool out. The fixed centre should, when much worn, be renewed. Usually the old centre must be softened by heating to redness the heel of the shuttle. It may then be drilled through from the outside, when a file tang inserted in the hole will serve to screw it out. The new centre should be screwed or riveted into position, and the heel smoothly finished off. A very good form of spring centre for shuttles is fixed in position by screwing, so that the pressure may be increased or diminished at pleasure.

Shuttle Reels.—The ends of shuttle reels get blunted

by want of oil. When the reel is long enough, it may be repointed, but the short ones should be replaced.

The Shuttle Carrier.—The hanger and carrier should be temporarily screwed together in position to correct the latter for wear. Place in the finished shuttle, and test the play from end to end. The correct play is $\frac{3}{32}$ of an inch for ordinary working. Remove the carrier and place the shuttle in it; now push the point of the shuttle as far forward as the carrier horns will allow, but do not push it out of position. Look between the *top* horn and the point, and mark if they touch each other—they *should* touch. Now look between the bottom horn and the shuttle—they *should not* touch. To reduce the play, heat the horns nearly red hot, hold in the vice, and strike them to shorten the movements of the shuttle to the required extent. See that the horns in doing this are in correct position with regard to the shuttle point as noted above.

The carrier must be *very carefully* finished up. The horns must be rounded off with a smooth half-round file, and finished up by fixing the carrier in the vice and smoothing off with strips of emery cloth; two numbers of this should be used, FF and O. The edges of the seat along the inside of the carrier must be filed round, more particularly the front corner. The loops have a tendency to catch here, and to chafe or to cut away, if the upper tension should be slack. The heel of the carrier must be carefully filed round and smoothed. To level the rounded bearing face of the carrier, hold it in the left hand, and use a flat file as in facing up shuttles. Afterwards screw the carrier on the hanger tightly in position in the machine, and note the play upon the guide bars. Take off and file

up the face of the hanger carefully until the parts fit without play. If the hanger should prove to be much worn, a soft-iron plate may be riveted upon one side of its guide, and afterwards fitted to the bars.

The Guide Bars.—Examine the surfaces and remove any humps; also smooth off any roughnesses. Of late the lower bar has been arranged so as to screw off when required, which is a great improvement, as these bars, when of cast iron, are subject to breakage.

The Shuttle Race.—The face of the race is usually concave by wear. A strip of steel made straight upon one edge should be used to test it. With a smooth file reduce the high portions by draw-filing, or a scraper may be used instead with advantage. When the race is concave, the shuttle will soon be made convex. Smooth off the edges of the needle groove, and file away any sharp corners, top or bottom.

Shuttle Point not clearing Needle Groove.—This is to be examined for by putting the connecting rod in position and making the shuttle pass backwards to the full extent. If the point should not clear the groove by at least $\frac{1}{8}$ th of an inch, the machine will miss stitches. This fault should not be looked for until the shuttle carrier has been corrected for wear. It is usually best to lengthen the connecting rod as follows:—Heat the rod along the middle portion, lay upon an iron block or anvil, and strike crosswise with the hammer to lengthen the bar. When of the requisite length, straighten and finish up.

The Feed.—After much use the feed teeth become so worn that thin fabrics are not seized except with great pressure from above. The teeth should be recut, but before this can be done the end must be softened by heating and allowing to cool slowly. Use

a saw file of small size, or, which is better for the long grooves between the sets of teeth, a stout screw-slitting file. The teeth must, of course, be filed to have a forward throw, and be equally high all over the point. Harden again when done by heating to redness and plunging in oil. Temper by brightening the back of the point and reheating until a deep straw colour is attained. The feed hinges upon a pin set through the end of the bearing block; the slot through which this pin passes is often worn, and should be filed up to shape. It is usually necessary to replace the pin itself by a new and stouter one. See, before leaving the feed, that its point underneath is well rounded off and made smooth. This part is very apt to chafe the loops passing over the shuttle.

The Stitch Bar.—This part carries upon its end a swivel block, which fits over the feed lever. This block forms the fulcrum upon which the feed lever moves, and the length of stitch of course depends on its situation upon the lever. When the stud of the swivel gets worn, it may be refitted by rebushing the hole, or by heating and beating in to partly close it, when a rimer may be used to open the hole to the required extent. The swivel should have no play up and down. This must be adjusted by the nut and washer provided. When the grip of the block becomes loose its sides should be beaten in and refitted.

Connecting-Rod Pins.—These should be renewed when worn, but the rod should not be bound upon its studs.

To reduce Shaft Play.—Remove the pins controlling the length of the play, and bend them. Drive in the holes with the concave side towards the arbor.

The Take-up Pin.—To adjust the take-up pin, which is fastened in the top of the needle bar, lower the needle until its eye is entering the cloth; then lower the pin till its end commences to press down the take-up, and fix with the screw.

Adjusting the Machine.—Put in the shuttle carrier and shuttle, also the needle bar, and revolve the hand wheel slowly to bring the straight needle down to the lowest position. Now bring forward the shuttle point, and find whether the needle and shuttle interfere with each other. If they touch in the least degree, place a stiff steel punch upon the base of the arm, and drive a blow or two with a heavy hammer. This should set the arm over and put the needle further into the slot. If the needle and shuttle point are too far apart, apply the punch to the arm just above the stitch screw slot, and set it out. The shuttle should pass as closely as possible to the needle without actually touching it.

Place on the feed and its holder, and, while the needle plate is screwed temporarily in position as a guide, fix it to rise and fall free of the plate. Screw on its raising cam, and, by pushing the cam in the required direction, adjust the height of the feed teeth above the needle plate. The rise above the plate should never be less than $\frac{1}{16}$ th of an inch. Place in the stitch bar and remove the needle plate.

Fit on the connecting rod, and pin it in position securely.

Timing.—The feed is timed by its cam, which is cut upon the shuttle-crank hub, so that they always move together; therefore, when the shuttle is in time, the feed is also correct in its movements. Hence, there remains only the timing of the needle to the shuttle to

be accomplished. Place all the parts of the machine together, but keep the horizontal shaft gear wheel loose, with its pin out. Bring the shuttle to approach its point to the needle groove by moving the vertical gear wheel round. Now lower the needle slowly, by turning the hand wheel towards you, until it dips and rises again about $\frac{3}{16}$ ths of an inch. Lock the wheels together while you hold the two movable parts firmly in this position, and pin up the loose wheel. Now turn the machine again to find whether the locking has interfered with your timing. The shuttle should approach its point close to the needle just when the latter has risen sufficiently to throw out a loop for the point to enter.

Fix on the needle plate so that the needle may descend in the centre of its hole ; but adjust this part still more accurately. Press the needle outwards with the screw-driver against the plate, and find whether the shuttle point is likely to become blunted in passing, or gets behind it. If there be any tendency to catch the needle, tap the plate so as to prevent the needle from springing into the race, and yet leave sufficient space for the thread to pass without chafing.

Thread up the machine with about No. 50 cotton, and find, with cloth under the presser, whether the needle throws out a loop of sufficient size for the shuttle to pass into. The needle should "dip," and then be on the point of "easing" downwards when the shuttle catches the loop. This adjustment must be made very accurately, as everything depends upon it. Shift the timing wheel back or forth one tooth if the timing should turn out to be incorrect. There must be no tendency to dropping stitches.

FAULTS.—*Missing Stitches.*—If the needle should be

set too high or too low the machine will miss stitches. The correct height is about $\frac{3}{16}$ ths of an inch below the shuttle point when it comes forward to enter the loop. Stitches are also missed by the loops thrown out being twisted. This is usually due to the needle being twisted from the cross line; but it may also be caused by other faults, such as a needle hole out of round; the needle eye being too large for the thread, or even too small; or by the needle cam and bar being worn, and allowing the latter to twist in its motions. The fault may, of course, be due to a blunt shuttle point, but it may frequently be noticed even when the shuttle point is sharp and the face quite flat. In a case of this kind the fault usually lies in the carrier, which allows the shuttle face to fall away from the race surface, and to roll back when approaching a loop. To prevent this troublesome fault, which is due to the carrier being worn and allowing the shuttle to fall upon the forward lower horn, the latter should be bent or filed clear.

Breaking Threads.—Assuming the tensions to be correct, the most usual cause for breaking lies in some sharpness about the carrier, shuttle, needle eye, needle groove, plate, or presser foot. All these points should be examined. Something may be learned by looking at the broken end, and its length from the needle eye. Breaking may also be caused by the take-up being improperly set, and not relieving the thread from up strain while being drawn through the cloth. The under thread may be broken by too tight a tension, but more frequently by the sharp corner at the upper end of the needle groove. It may also break by its tension holes through the shuttle being sharp, and sometimes by sharpness upon the end edges of the

shuttle covers on the side of the needle plate. The feed being square (which it should never be) underneath, it often chafes the upper loops. If the take-up should be so set as to slacken too soon, the loop passing over the shuttle will be very loose, and may be caught in passing upon one of the carrier horns. The same may, however, be caused by a slack tension, or the horns being imperfectly finished and rounded. A break may also be caused by the needle throwing out *two* loops at once, back and front, or only from the back. In this case the needle is usually out of line, or the bar twists. In every instance of breaking stitches, an examination should be made to ascertain whether the loop is *absolutely free to expand* when struck by the shuttle point.

Bad Tension.—It sometimes occurs that the tension under the fabric is bad, chiefly irregularly, and that there is at the same time sufficient strain upon the upper thread. The fault usually lies in some impediment to the rapid drawing up of the loops. Perhaps the most marked cause is too small a needle hole, which serves to jam up such loops as chance to get twisted. It may also be caused by the “time” being too fast, for the shuttle may in this case be pulled back and held against the carrier heel, detaining the loops from passing quickly up in obedience to the take-up. This latter fault is an important one, for it indicates bad timing, and may also be due to the shuttle not going forward far enough at each stroke to give out sufficient thread.

Testing.—When repaired, the machine should be thoroughly tested upon various materials. Test first with muslin and a fine needle and cotton. Use also three thicknesses of calico with a stouter needle, and

dress stuffs with silk thread. Test upon cloth of three and four thicknesses with a stout needle and linen thread.

See that the feed tends to produce an accurately straight line of stitching. If it does not, it may be assumed that its motion is not straight, or that its teeth are cut at an oblique angle instead of at right angles to its stroke.

Make a note that the tensions upon all materials tried are easily controlled by the upper tension alone—assuming a moderate tension applied at the shuttle.

If there be any tendency to breaking needles, observe that there is no strain by the thread upon the needle to pull it to the side of the hole when at work. It must also, of course, be noted whether the feed is clear of the fabric before the needle point enters it. Note likewise that the presser should have no swerving movements to throw the needle out.

THE NO. 2 MACHINE.—This large manufacturing machine possesses certain peculiarities which call for special mention here, as they often confuse an otherwise good mechanic. The remarks already made with regard to the smaller sizes of machines apply in most particulars to this type also, and no difficulty should be experienced in treating such portions as bear a resemblance to the smaller sizes, and parts that are in construction and action essentially different will be noticed here.

The Wheel Feed.—The wheel feed, which is extensively used in the No. 2 size, is provided with fine teeth around its circumference, seizes the cloth pressed upon it as usual from above, and carries it forward at each stitch the length required. This motion at every stitch is given to the wheel by rather peculiar mecha-

nism. A kind of iron attachment, similar to a railway brake block, and called a "shoe," or clutch, is moved by a frame termed the "dog," and this frame receives its motion from a lever actuated by a cam upon the under shaft of the machine. The shoe mentioned, to grip the smooth face of a flange cast upon the wheel, must be a very close fit to the latter, and no oil or fluff should be allowed to get upon the smooth rim, otherwise the shoe will slip. If oil should get upon the shoe where it grips the wheel, the result would be a stoppage of feeding, unless, indeed, the shoe should fit exceedingly well. This is frequently a cause of great annoyance to inexperienced operators. Some, being cautioned against over-oiling the feed wheel, gather from it that the wheel is better not oiled at all, and allow it to cut its stud nearly through before attending to it. These wheels should in every instance be well oiled where there is real friction. The first and most important oil way is a hole leading through the hub of the wheel, where it runs upon its stud. The next point is the bearing of the lever pressing the shoe to the wheel. In setting a wheel of this kind, the wooden check bar must be pressed against the edge of it with sufficient force to prevent the clutch from dragging the wheel backwards when it recedes for a fresh stroke. A set screw is provided for this purpose, and it is further of much importance to set the check bar hard up against the bed of the machine. If this is not carefully seen to, the bar will vibrate with the wheel backwards, and no stitch will be taken, or the wheel will drag the cloth back and break the needles.

The No. 2 Take-up.—Upon the upper end of the face plate in this machine we find a number of wire loops and other arrangements, forming the take-up, or for

checking the motions of the take-up. These loops sometimes get out of gear, and it may prove useful to give information concerning their correct positions. The loop screwed to the back of the needle bar presses down the take-up to relieve the thread, and must be set to ease down the lever just when the needle eye is about to enter the cloth. The loop screwed to the front of the face plate is for the purpose of checking the upward movements of the take-up lever. It should be set to prevent the lever from springing farther up than the upward movement of the needle bar forces it to. It is usual, to reduce noise, to pad these loops with leather. The needle bars are generally adjustable for wear.

CHAPTER IX.

THE ADJUSTING OF GROVER AND BAKER MACHINES.

THE old Grover and Baker machine makes what is known as the double-chain stitch. The same stitch is made by an English machine called the Lancashire, used in corset making. The stitch is bad, clumsy, and wasteful of thread, and does not even possess the advantage of being easily pulled out when required. The Grover and Baker machine of this type gives the mechanic a great deal of trouble. As this machine is in extensive use, it will be unnecessary to go into details of its construction. All mechanics know it, and will readily understand the references to parts used here.

In the Grover and Baker there is a second "needle" working the under thread into the loops of the upper. This needle is only a circular grooved hook, having near to its point an eye, through which the under thread passes, lying in the groove of the hook until it is led off from a bridge crossing the groove at the stem end. The under thread is thus taken continuously direct from the reel.

The chief parts calling for attention when the machine is worn and refuses to work are the automatic thread detent, the needle plate, the circular

needle, the twist stem which gives it motion, and the driver of the same part.

Very little wear causes this machine to miss stitches. The defect generally originates at the driver of the twist spindle, and at the vertical bearings of the spindle itself.

“Taking down” the Machine.—Remove the needle and needle plate, and unscrew the presser arm from underneath. With a long thin screw-driver remove the circular needle. Cause the needle arm to descend, and make a mark on the flat side of the twist spindle towards the right; this will obviate any confusion in putting the machine together again. Mark also the driver of this spindle. Ease the lock nut at the lower bearing of the spindle, and draw the screw. The spindle and its driver may now be pulled out to the right (assuming the machine in the usual position), and separated.

The Driver: Refitting.—After cleaning off all gummed oil with paraffin and a cloth, test the driver on its spindle for end play. Hold the spindle vertically, and move the driver without twisting up and down about the middle of the twist. A little observation will serve to obtain an indication of the amount of wear. The driver must be refitted by heating to redness and quickly gripping one side in the vice, giving a blow or two upon the free side downwards, to reduce the width of the driving slot. After this treatment the driver should be too narrow to allow the spindle to enter. The surplus metal should be carefully filed off equally from both sides, and a curved form must, of course, be given to the sides, which must finally be smoothed. To insure the requisite tightness upon the twist, the driver should be too narrow to pass easily

over the flat portion of the spindle. It is wise to make the fit tighter at first than is absolutely required.

These drivers are usually made up from four or five steel plates riveted together, and may be spread out at the ends to slip with spring pressure in their grooves in the lower arm. These plates should, therefore, be separated slightly with the screw-driver edge if the driver should be found to slip too easily into its place, or if it have any play.

This part being corrected for wear, attention should be turned to the lower end of the spindle. If it be found cut up into grooves and ridges the end should be made red hot to soften it, and subsequently tapered off on the lathe or at the grindstone. The point should afterwards be hardened by heating red hot and plunging in water. Attention should also be directed to the seat of the spindle in the lower adjusting screw. This screw should be softened if necessary, and a taper countersink, corresponding to the spindle end, run into it to cut off the ridges. The screw must afterwards be hardened.

The Circular Needle.—All roughnesses must be filed out, and then smoothed over and burnished. If the point should appear blunt, a smooth file may be used to bring it to its original shape, but care must be taken that no metal be removed from the *inside* of the point. If the point be worn so as to be very short, a new needle should be fitted to the machine.

Timing.—The circular needles for Grover and Baker machines usually have thin stems filed flat opposite to the set screw, through the twist spindle. As a rule, this plan is very troublesome, as it is seldom that the circular needle can be timed to answer the motions of the needle proper at this one point. But to time the

machine, which may render necessary the filling up of the filed facet, set the twist spindle and its driver in their respective places in the machine. Be particularly careful to take up all end play of the spindle by means of the lower adjusting screw and its lock nut. Put in the circular needle loosely for the present. Fix in the needle clamp a medium-sized Grover and Baker needle, correctly curved; be careful to make the height correct. Bring down the upper needle arm slowly, and then cause it to rise again about one-eighth of an inch. Take now the circular needle, and bring its *point* round to the upper needle, raise it as high as it can be worked in position, and make fast with the set screw. If this has been done correctly, the two eyes will come opposite to each other upon continuing the revolution, and the timing should be accurate. If the hook point be too slow, or if it fail to go far enough back, a defect due to wear, take out the spindle and needle, and with a punch gently tap the upper side of the top spindle bearing to lower it slightly. If it be lowered too far, the hook will be too fast. The needle proper must, when straight and accurately fixed in the clamp, pass as near as possible without touching to the inside of the hook point. If the needle should be found to lie out of position, the set screw of the arm pivots, under the base plate, must be loosened, and the pivots tapped in either direction to place the needle accurately in position in relation to the hook.

The Needle Clamp.—The groove in which the needle is clamped is not always straight, and holds the needle with its point inclined to the right or left as the case may be. This should be carefully tested. An accurately straight needle should be placed in the clamp and screwed up; the needle arm should now be slowly

lowered, while the needle plate is held near to the needle as it descends. If the needle deviate from the true line, the fact will immediately be indicated. If it be found to lie with its point too far to the right, the needle groove must be corrected by filing the top side. If, on the other hand, the point incline to the left, file the lower part of the groove. Note should also be taken of the *curve* described by the needle; it should, of course, be equal to the arc described by the needle arm itself.

The Needle Plate.—The hole in the needle plate must be filed to remove all cuts or scratches, and afterwards smoothed and chamfered off on the under side. If the hole be too large, or cut out of shape, it should be drilled out to twice the size, and a steel plug fitted into it. If the edges are slightly countersunk, the plug may now be riveted into position, and filed flat on both sides.

To find the exact point in which to drill the new hole, finish the adjusting of the machine and place a straight needle in the clamp. Screw the needle plate into position, and slowly bring down the needle until its point shall indicate the place for the new hole. Make a centre mark at the point, and run a small drill through. Screw the plate again in its place, and test with the needle whether the new hole is accurately in position. If not, use a fine round file to open the hole on the side required, and chamfer off the under side of the hole with a drill or counter-sink. File out the thread channel as before, and smooth off all the edges.

The Tensions.—The tension studs in this machine are two in number. The top one has a strong spring, and the bottom a weaker one. They seldom call for attention from the mechanic except they be

clogged up with oil. If the discs have got roughened on the faces, they should be smoothed.

The Take-up.—After the upper thread has passed its tension stud, it extends to a kind of take-up arrangement, which consists of a long weak brass spring and cap, working vertically upon a slotted rod. The thread in its course to the needle passes over the cap and through the slot, and is therefore kept with gentle elastic force up to the top of the rod. If the take-up spring should have become compressed permanently, it may be again stretched to fill the rod. The edges of the slot must be smoothed if they exhibit sharpness.

The Detent.—The thread, after passing the take-up, is gripped by the detent, or “nippers.” This arrangement consists of a spring pressing upon a plate, and controlled by the machine itself. The springs are always much too strong. The pressure of the spring upon the plate may be removed at any moment by a cam fixed to the presser arm, while the detent, which is screwed to the needle arm, passes over it at every stroke of the latter. When the cam is found to be worn so much that it does not liberate the thread when required, it should be taken off, and a chip of thin sheet brass placed behind it. This will suffice to bring the cam farther out, and will liberate the detent when the spring slips upon the cam. This detent should be kept well oiled where its spring rubs upon the cam.

The Presser.—This part seldom calls for much attention, but it is very frequently clogged up with bad oil. To release the bar and spring for cleaning purposes, turn the lifter much farther than usual from its normal position, when it can be slipped off, and the bar pulled out.

The Feed.—The Grover and Baker feed is adjustable

for wear. It is a very troublesome arrangement through getting clogged up with old oil. To raise the feed, the teeth point alone may be raised by a set screw, as the two portions, body and point, are separate pieces. The feed may also be raised by lowering the friction block at its lower side. In most cases it will be necessary to elongate the hole to raise the teeth. To sharpen the teeth, soften by heating to redness, cut over again with a sharp half-round file, and harden by heating to redness and throwing into water. It is important that the feed be free to move upon its two studs, but yet destitute of any side play. In the rise the teeth should be $\frac{1}{16}$ th inch above the needle-plate surface, and have a free drop.

The Friction Roller.—The usual form of friction rollers in these machines is that of a square block of steel, working upon a steel stud made fast to the driving disc. The needle arm should be tested for play at the friction roller, and, when practicable, all play should be taken up. In the better-made machines, the friction race on the extremity of the lower arm is in two parts screwed together; this is very convenient, for by its means the wear can be taken up by separating the parts and filing a little off the face of the smaller one. If on trial it be discovered that the friction race is wider at the middle or at the inner end than elsewhere, the file should be carefully used to make the width equal.

If the friction roller be found to have worn its stud, a new stud to fit the friction roller should be put in, or *vice versa*. These rollers should be as hard as fire and water will make them, and the studs should also be of good steel hardened to a considerable extent. There should be no play upon the needle arm, either at the pivots or the friction roller.

Testing.—A raised chain stitch is produced by the Grover and Baker machine. About five yards of thread are thus used to give a yard of work, with an ordinary length of stitch, so that in point of economy of thread it is far behind a lock-stitch machine. Orna-mentally considered, however, the double chain has its uses.

The seam underneath should be quite tight, and drawn as close as possible to the fabric. To thread up the machine, place the upper reel, which may consist of No. 50 cotton, upon its pin, and pass the thread once round the tension stud, between the discs, slip through the eyelet, and pass through the take-up slot, above the spring cap. Release the detent spring, place the thread under it, and finally thread the needle. The under thread should be much finer than the upper to secure neat stitching, say about No. 70 cotton. The under thread pin is usually fixed to the stand of the machine. Pass the thread once around the under tension stud, and apply only a slight pressure, as very little tension upon the under thread is necessary. The under or circular needle is threaded by passing the cotton through the bridge at its heel, laying it in the groove, and finally passing it inwards through the eye of the needle.

As a testing material employ three folds of good calico. If the chain presents a loose appearance, increase the upper tension, and also the under if necessary. The stitching should be regular and tight. It is often necessary to employ the thread oiler in working this type of machine upon calico. The oiler should be stuffed with sponge, as cotton wool adheres to the thread and breaks it by getting into the needle eye.

Lubricating.—When the machine is clogged up and stiff to run, use paraffin. Sperm oil thinned with paraffin, or almond oil, is best for the ordinary lubricating. Care must be taken that the feed be well oiled, and that the twist spindle is not allowed to get dry. A drip cup is attached to the lower side of the twist spindle to catch superfluous oil. The friction roller and all the ordinary oil holes must also have attention. The friction-roller race should have an oil hole provided in its upper side. The main spindle is lubricated by holes running downwards through its bearings.

Polishing.—For the sake of appearance, if not to fix cleanly and accurate habits in the mechanic, a practice of polishing all bright parts should be adhered to. The lock nuts upon the various parts should be squared off if damaged, and the plates covering the movement should also be polished. Care must be taken that no sharp projecting edges are presented by the plates.

CHAPTER X.

ADJUSTMENTS OF THE "LITTLE WANZER" MACHINE.

THIS is a hand lock-stitch machine in extensive use. The gearing giving motion to the shuttle is of rather peculiar construction, and yields rather fast to wear. The result is a tendency to drop stitches.

Miss-stitches in this machine are usually due to the shuttle failing to go back far enough to allow its point to clear the needle, the result being, of course, that no loop can be made.

The screw upon which the carriage moves is made eccentric, so that upon releasing the set screw, and turning it to the right or left, the carrier may be caused to advance to or recede from the shuttle race. By bringing it closer to the race, less play is given to the shuttle, which frequently causes it to clear the needle groove. Sometimes, however, this plan is useless, and another must be adopted. Remove the screws and take out the connecting link. This rod, if made a little shorter by bending, will pull the carriage farther back and make the shuttle clear the groove. Make the link red hot, grasp in the vice, and, with a blow from a hammer, give the bend required. Much care is necessary not to *twist* the link, so as to put the holes out of line. When the link is thus shortened, a

little adjusting with the eccentrical screw will set matters right, and give the shuttle the required play about $\frac{1}{8}$ th inch. When a new shuttle is necessary it should be tried on the carriage before bending the link. The shuttle used must be quite flat in the face, and lie upon the race throughout the stroke.

The Spring Thread Guide.—Upon the face plate of this machine is provided a spring thread guide, to prevent slack thread from being thrown down by the needle. It is important that the thread, fine and coarse, shall be clasped here with elastic pressure, and this at all parts of the guide to which the thread may shift in working. To insure this, the spring and plate must be examined, and the latter made quite flat and smooth. The spiral spring should press strongly upon the end of the plate, which must be free to move on its screw. In other respects this machine is adjusted in the usual way.

CHAPTER XI.

ADJUSTMENTS OF THE WEIR MACHINE.

A SMALL chain-stitch machine under this name often proves a source of much trouble to the mechanic. The little hook by which it makes its stitches or loops is different from the loopers of other machines, and has a peculiar action. The looper is, as those who possess the machine will know, a simple hook, which does not revolve like most other loopers, the motion being through an arc of a circle only. It does not act by twisting the loop as do the rotating loopers, but so spreads it out, and retains it in that position, until the next loop is caught, that a continuous chain stitch is formed with the one thread used.

The machine is always a very troublesome one to those who do not understand its action. A very little examination will suffice to show the mechanic that the gearing of the looper is rather delicate, and subject to wear fast. This more particularly applies to the side play the looper soon gains after much working. It will be observed that if the hook should gain side play from wear, it will develope a tendency to miss stitches; and it is a peculiarity of this machine that it misses its stitches in a different manner from that of other machines. It may, indeed, miss from the hook failing

to catch the loops, as in other machines, but it is generally found to do it in quite another fashion, an explanation of which is here given.

Let us observe the machine while slowly making its stitches. The reel is mounted upon a tension pin fixed to a bracket on the upper end of the needle bar, and is kept in position and in the requisite tension by a pair of brass cones and a spiral spring regulated by two set nuts. The thread passes from the reel, and is taken one turn around what acts as a detent pin. It is necessary to observe that the thread commences its turn to the left of this pin, or next to the small detent roller found below. The function of this roller is to detain the thread from freely running down when it is not required. The thread next passes through an eyelet hole in the face plate, and finally through the needle eye. We place a piece of doubled calico beneath the presser, and turn up the end of the machine to clearly observe the making of stitches. Turning the hand wheel very slowly, we observe the looper going backwards as the needle descends. When the needle has attained its lowest point the looper has reached the extremity of its backward stroke, and turns to come forward. The needle now begins to rise, and in doing so throws out the usual loop of thread from its side, and when this loop is well formed the hook point will commence to enter it. The needle next rises, leaving a loop upon the hook. The latter now continues its forward motion, and when the needle has reached its highest point will be at the extremity of its stroke, having the loop still upon its neck. The needle finally descends, and a little observation will disclose the peculiarity of this machine referred to. As the needle descends the looper recedes, and it will be specially observed that

the looper has spread out the loop, the narrow end of which disappears through the needle hole, while the body of the loop is spread out directly under it. The needle now passes downwards *through* the loop which is threaded upon the needle. The hook retains hold of the captive loop until its point recedes past the needle, when the loop slips off and is drawn upwards upon the needle into the cloth by the tension caused by the descending needle. When the needle has reached its lowest point the loop has disappeared up into the cloth; a fresh one is next taken up, and the ingenious action repeated.

The movement is thus throwing one loop over another in endless succession. But it is at the stage indicated below by italics that the machine usually fails. New loopers are wider at the neck than thread-worn ones, and there are other causes by which the looper in time gets thinner. The result is as near as possible as follows:—The loop, which when upon the hook should be spread out wide enough to fully cover the needle's path downwards, is not with worn hooks sufficiently spread out, and the needle in descending either strikes and cuts the thread, or fails to enter the loop, and a miss is indicated. Now in most other machines the shuttle, or hook, fails to enter the needle loop to cause a miss, but here we have the *needle* failing to enter its own *previously made loop*; this is the chief peculiarity of the Weir.

Adjusting the Gearing.—When the looper becomes so narrow at the neck that the loops are not spread widely enough to cover the needle hole, it should be replaced. But if it be found to have sufficient width, and the loop do not fully cover the needle's path, the fault is obviously that the hook is either too far from,

or too near to, the needle. The whole of the gearing about the looper is attached to one plate, which is adjustable upon a hub let into the casting. Looking to the right of the hub, a set screw is found, which retains the hub in position. The screw being loosened, the gearing may be drawn out or pushed in carefully until the point of the hook shall just graze the needle in passing. It is necessary to observe, however, that the gear is not allowed to move to the right or left, as this would alter the throw of the hook.

Timing.—It is somewhat difficult to give an exact rule for the timing of Weir's hooks, as so much depends upon their shape. The machine is, of course, "timed" by releasing the large wheel and moving the gear wheels, or pinions, as required. Some loopers that have not much "hook" must be so set that when at the position farthest from the needle in the back motion, their points shall be about one-sixteenth of an inch from the needle. A looper that is much hooked must be set a little farther back, otherwise it will fail to release its captive loops when required.

It must, of course, be assumed that the play or looseness upon any or all of the parts has been taken up as much as practicable. When the motion plate is unsteady, file or turn a little off its screw, where it butts against the frame, which will serve to take up the play. When the hook has play, it may be taken up by putting a thin washer in, and the same plan may be resorted to in tightening the motion plate. If the hook and the plate are steady, the machine should, as far as these parts are concerned, work well.

The Thread Detent.—The thread, after leaving the reel, takes one turn round a pin moving with the needle bar; and at a certain part of the stroke this pin

comes in contact with a roller, the stud of which is fixed to a spring. This part is frequently a source of trouble. The roller should press somewhat stiffly upon the twist of thread around the pin, and prevent all motion of the thread. The pressure should be no greater than is necessary to do this. Breaking of the thread is sometimes caused by the roller pressing too tightly upon it. The roller is adjustable as to pressure and height.

The Feed.—When the feed teeth get blunted, they should be recut. When they fall too low and do not catch the material, the feed bar may be heated a few inches from the point, and gently bent upwards.

Needle Plate.—The needle hole in this plate is usually of elongated form, and, as the plate is very thin, it must be well chamfered off from beneath and smoothed. The same precautions must be taken with the presser foot. When sewing dressed calico, it may be necessary to oil the thread bobbin.

INDEX.

- A** **ADJUSTMENT** of Wheeler & Wilson Machine, 94
 Thread guide, 96
 Tension, 97
 Presser foot, 98
 Foot lifter, 101
 Hinge, 103
 Pivot screws, 103
 Eccentric, 104
 Drum, 106
 Under-thread check, 119
 Needle yoke, 119
 Machine (final), 121
 Brush holder, 123
 Spool ring, 124
Adjustment of Singer Machines,
 129
 Feed cam, 134
 Needle bar, 136
 Clamp, 137
 Plate, 138
 Shuttle side spring, 139
 Shuttle, 140
 Reels for shuttles, 141
 Shuttle carrier, 142
 Guide bars, 143
 Shuttle race, 143
 Feed, 143
 Stitch bar, 144
 Take-up pin, 145
 Machine (final), 145
Adjustment of Grover and Baker
Machines, 152
 Driver, 153
 Circular needle, 154
Adjustment of Grover and Baker
Needle clamp, 155
 Plate, 156
 Tension, 156
 Detent, 157
 Take-up, 157
 Feed, 157
 Friction roller, 158
Adjustments of the Wanzer
Machine, 161
 Weir Machine, 163
 Detent, 166
 Feed, 167
 Automatic Tension, 80
- B** **BAND,** to lace, 66
 Baster plate, 22
 Bobbin winder, 35
 Shuttle, 35
 Holder (hinged Wheeler & Wilson), 40
 to place in position, 67
 Braiding, 70
 Break of threads in Singer
 Machines, 147
 Bridge feed, Wheeler & Wilson,
 adjustment of, 109
 Brush check, 47
 Care of, 67
 Wheeler & Wilson, adjust-
 ment of, 114
 Holder, adjustment of, 123
- C** **AM,** Howe, 28
 Wheeler & Wilson, 41

Cam, Wheeler & Wilson, 53
 adjustment of, 106
 Cast-off (Wheeler & Wilson), ad-
 justment of, 113
 Check brush, 47
 adjustment of, 114
 Circular needle (Grove & Baker),
 adjustment of, 154
 Cloth plate, 40
 Copes, 24

DETENT (Grover & Baker),
 adjustment of, 157
 (Weir), adjustment of, 166

Draw feed, 42
 point, 43
 (W. & W.), adjustment of,
 109

Driver, shuttle, 34

Drum (W. & W.), adjustment of,
 106

ECCENTRIC motion, 41
 (W. & W.), adjustments of,
 104

Elements of the Sewing Machine,
 19

FAILURE to feed in W. & W.
 Machines, 127

Faults of rotating hook, 111
 in W. & W. Machine, 126
 Singer Machine, 146

Feeder, principle of, 19

Four-motion, 22

Top, 22

Mechanism, 22

Feed-wheel, 23

Howe, 28

Bar, old style of, 41

Stop, 41

Cam, 41

Draw, 43

Care of, 65

Gibbs, 75

Cam (W. & W.), adjustment
 of, 106

Old style, W. & W., adjust-
 ment of, 106

Feed, Singer, adjustment of, 143
 Wheel (Singer), adjustment
 of, 149

Feed, Grover & Baker, adjustment
 of, 157

Weir, adjustment of, 167

Felling, 69

First sewing machine, 4

Description of, 26

Foot lifter (W. & W.), adjust-
 ment of, 101

Friction roller (Singer), adjust-
 ment of, 134

Friction roller (Grover & Baker),
 adjustment of, 158

GAUGES, to use, 68

Gear wheels (Singer), adjust-
 ment of, 131

Gearing (Weir), adjustment of, 165

Gibbs, inventor, 14

Gibbs' Lock-stitch Machine, 72

Spring foot, 80

Take-up, 79

Needle clamp, 79

Spool holder, 82

Needle, 84

Straw-hat machine, 87

Glass feet (W. & W.), adjust-
 ment of, 101

Grover and Baker Machine, ad-
 justment of, 152

Driver, adjustment of, 153

Machine, "Timing" of, 154

Needle clamp, adjustment of,
 155

Needle plate, adjustment of,
 156

Tension, 156

Take-up, 157

Feed, 157

Detent, 157

Machine, testing of, 159

Guide bars (Singer), adjustment
 of, 143

HIGH-BED machine (W. &
 W.), 38

History of the Sewing Machine,
 1

Hook (Rotating) Machine, 37

action of explained, 46

single thread, 76

Howe, inventor, portrait of, 8

Howe cams, 28

Howe, Feed, 28
Tension, 30
Shuttle, 34

LATCH of shuttle, 34
Lock stitch, invention of, 3
Lock stitch, the, 20
Machines, speed of, 93
Loop made by machine, 33
Looper, Gibbs', 74
Single thread, 75
Loose wheel in Singer Machines, 36

MECHANISM, feeding, 22
Minor parts of the sewing machine, 23
Missed stitches in Singer Machines, 146

NEEDLES for the Sewing Machine, 21
Howe, type of, 33
Plate, 40
Plate, to change, 65
to set, 66
to sharpen, 70
Clamp, Gibbs', 79
Gibbs', type of, 84
and thread, tables of, 90
Plate (W. & W.), adjustment of, 116
Hole, size of W. & W., 118
Yoke (W. & W.), adjustment of, 119
Cam (Singer), adjustment of, 135
Bar (Singer), adjustment of, 136
Clamp (Singer), adjustment of, 137
Plate (Singer), adjustment of, 138
Clamp (Grover & Baker), adjustment of, 155
Plate (Grover & Baker), adjustment of, 156
Plate (Weir), adjustment of, 167
No. 2 machine, adjustment of, 149

No. 7 machine (W. & W.), description of, 59
No. 8 machine (W. & W.), description of, 62
Noise in W. & W. Machines, 127

OIL to use for Sewing Machines, 71

PIVOT Screws, adjustment of, 103
Polishing, 120
Portrait of Elias Howe, 8
Portrait of Allen B. Wilson, 12
Presser, 24
Foot joint, 59
Rolling, 59
Foot (W. & W.), to adjust, 138
Bar (Singer), to adjust, 138
Foot (Singer), to adjust, 138
(Grover & Baker), to adjust, 157

RACE, Shuttle, 33
Race, adjustment of Singer Machine, 143
Reels, adjustment of Singer Machine, 141
Rolling Presser, 59
Rotating Hook, invention of, 14
Machines, 37
Description of, 46
Action of explained, 46
Machine, No. 6, 49
New form of, 55
Machines, use of, 63
Adjustment of, 110

SEWING Machine, history of the, 1
Shuttle Sewing Machine, description of the, 26
Sewing Machine, Howe under parts, 28
Race, 33
Driver, 34
Latch of, 34
Description of, 34
Bobbin or reel, 35
Side-spring (Singer), adjustment of, 139

Shuttle Sewing Machine (Singer),
 adjustment of, 140
 (Singer) Reels, adjustment
 of, 141
 Carrier (Singer), adjustment
 of, 142
 Point, adjustment of, 143
 Race (Singer), adjustment of,
 143
 Singer, loose wheel arrangement,
 36
 Machines, adjustment of,
 129
 Gear-wheels, 131
 Feed cam, 134
 Friction roller, 134
 Needle cam, 135
 Needle bar, 136
 Presser bar, 138
 Presser foot, 138
 Needle plate, 138
 Shuttle, 140
 Feed, 143
 Stitch bar, 144
 Machine, "Timing" of, 145
 Singer Machine, adjustment of,
 145
 Take-up pin, adjustment of,
 145
 Machine, faults in, 146
 Wheel feed, adjustment of,
 149
 No. 2 Machine, adjustment
 of, 149
 Take-up, 150
 Single-thread machines, 74
 Speed of single-thread machines,
 89
 Lock-stitch machines, 93
 Spools, 24
 Holder of, Gibbs', 82
 Spool-ring (W. & W.), adjust-
 ment of, 115
 Spring foot, Gibbs', 80
 Thread guide, 96
 Shuttle, 139
 Stitch, machine, 19
 Single-thread, 20
 Regulator (W. & W.), ad-
 justment of, 109
 Bar (single), 144
 Straw-hat Machine, Gibbs', 87

TAKE-UP, 24
 Gibbs', 79
 Singer, adjustment of, 137
 Pin, 145
 No. 2 Singer, 150
 Grover & Baker, adjustment
 of, 157
 Tension wheel, 23
 Howes', 31
 Under Wheeler & Wilson,
 58
 to regulate, 67
 Gibbs' automatic, 80
 Adjustments of W. & W.,
 97
 Tension, Singer, adjustment of,
 138
 Bad in Singer Machine, 148
 Grover & Baker, adjustment
 of, 156
 Testing "time" of W. & W. ma-
 chines, 125
 Singer Machine, 148
 Grover & Baker Machine,
 159
 Thread, upper, 24
 Under, 24
 Oiler, 70
 and needles, tables of, 90
 Guide (W. & W.), 96
 Breaking, in W. & W. Ma-
 chines, 127
 "Timing" of W. & W. Machines,
 122
 to test, 125
 Singer Machine, 145
 Grover & Baker Machine,
 154
 Weir Machines, 166
 Top feed, 22

UNDER thread, 24
 Tension of W. & W. Ma-
 chine, 58
 Broken, 67
 Check, adjustment of, 119
 Upper thread, 24
 Use of rotating-hook machines,
 63

VARIABLE motion mechan-
 ism, 53

- W**ANZER Machine, adjustment of, 161
 Wanzer thread-guide, adjustment of, 162
 Wheel, tension, 23
 Feed, 23
 Singer, adjustment of, 149
 Wheeler & Wilson Machines, 37
 Bar feed, 41
 Cams, 41, 53
 Variable motion, 53
 Machine No. 7, 59
 Machine No. 8, 62
 to "take down," 94
 Adjustment of, 94
 Hinge, 103
 Eccentric, 104
 Cam, 106
 Old-style feed, 106
 Drum, 106
 Bridge feed, 109
 Draw feed, 109
 Regulator, 109
 Spools, 115
 Wheeler & Wilson spool ring, 115
 Needle plate, 116
 Needle yoke, 119
 Machine, final, 121
 Machine, timing of, 122
 Spool-ring, adjusting of, 124
 to test time of, 125
 Machine, faults in, 126
 Machine, failure to feed of, 127
 Machine, thread-breaking in, 127
 Machine, noise in, 127
 Weir Machine, adjustment of, 163
 Gearing, adjustment of, 165
 Gearing, timing of, 166
 Needle-plate, adjustment of, 167
 Willcox & Gibbs' Machines, 74
 Wilson, inventor, 10
 First experiments of, 11
 Winder for shuttle reels, 35

THE END.

BY THE SAME AUTHOR.

Crown 8vo, with 94 Illustrations, price 7s. 6d., cloth.

ELECTRIC LIGHT,

ITS PRODUCTION AND USE;

EMBODYING

*PLAIN DIRECTIONS FOR THE WORKING OF GALVANIC BATTERIES,
ELECTRIC LAMPS, AND DYNAMO-ELECTRIC MACHINES.*

By J. W. URQUHART, C.E.,

AUTHOR OF "ELECTRO-PLATING: A PRACTICAL HANDBOOK," ETC.

EDITED BY

F. C. WEBB, M.I.C.E., M.S.T.E.

"As a popular work it will doubtless meet with considerable approval. . . . The book can be recommended to those who wish to learn something about the electric light, while the practical information will be found useful to amateurs."—*ENGLISH MECHANIC*.

"An interesting volume. . . . It is intended to be popular, and is, therefore, prepared in a style to suit the general reader, yet accuracy and systematic arrangement have been as carefully considered as if the book had been intended for the professional man."—*MINING JOURNAL*.

"The book contains a general account of the means adopted in producing the electric light. . . . We welcome it as an important addition to the literature of the electric light. Students of the subject should not fail to read it."—*COLLIERY GUARDIAN*.

"As a practical exposition of the various systems of electric lighting, we consider it likely to be useful to the large and increasing class who are interested in the subject."—*DESIGN AND WORK*.

"A clear and practical little book."—*WESTMINSTER REVIEW*.

"It is the only work at present available which gives in language intelligible for the most part to the ordinary reader a general but concise history of the means which have been adopted up to the present time in producing the electric light."—*METROPOLITAN*.

"To those who wish to know the mechanical stages that have marked the progress of electric lighting, no better practical guide could be found than Mr. Urquhart's work."—*SCOTSMAN*.

CROSBY LOCKWOOD & CO., 7, Stationers' Hall Court, London.

BY THE SAME AUTHOR. RECENTLY PUBLISHED.

With Illustrations, crown 8vo, price 5s., cloth.

ELECTRO-PLATING; A PRACTICAL HANDBOOK.

INCLUDING

THE PRACTICE OF ELECTRO-TYPING.

OPINIONS OF THE PRESS.

"The author has carefully thought out his subject, and should be considered by all platers who aim at doing good and lasting work."—ENGINEER.

"An excellent practical manual."—ENGINEERING.

"The information given appears to be based on direct personal knowledge. . . . Its science is sound, and the style is always clear."—ATHENÆUM.

"Any ordinarily intelligent person may become an adept in electro-deposition with a very little science indeed, and this is the book to show him or her the way."—BUILDER.

"A large amount of thoroughly practical information. . . . The author is at home in dealing with his subject. . . . Undoubtedly a useful work, and one which can be recommended."—TELEGRAPHIC JOURNAL.

"Any amateur will find no difficulty in understanding the book from beginning to end. Everywhere it shows signs of having been drawn up after considerable experience on the part of the author."—SPECTATOR.

"The volume is without a rival in its particular sphere, and the lucid style in which it is written commends it to those amateurs and experimental electrotypers who have but slight, if any, knowledge of the processes of the art to which they turn their attention."—DESIGN AND WORK.

"A thoroughly practical manual."—IRON.

"An excellent work, giving the newest information concerning the ever-progressive arts of electro-plating and electro-typing."—HOROLOGICAL JOURNAL.

"Peculiarly acceptable to those who find it necessary for the conduct of their business that they should be able to do some portion of their electro-plating."—JEWELLER AND METALWORKER.

In the press, to form a Companion Volume to the above.

ELECTRO-TYPING; A PRACTICAL MANUAL.

Forming a New and Systematic Guide to the Reproduction and Multiplication of Printing Surfaces and Works of Art by the Electro-deposition of Metals.

CROSBY LOCKWOOD & CO., 7, Stationers' Hall Court, London.

Weale's Rudimentary Series.



PHILADELPHIA, 1876.
THE PRIZE MEDAL

Was awarded to the Publishers for
Books: Rudimentary, Scientific,
"WEALE'S SERIES," ETC.



A NEW LIST OF WEALE'S SERIES

RUDIMENTARY SCIENTIFIC, EDUCATIONAL,
AND CLASSICAL.

Comprising nearly Three Hundred and Fifty distinct works in almost every department of Science, Art, and Education, recommended to the notice of Engineers, Architects, Builders, Artisans, and Students generally, as well as to those interested in Workmen's Libraries, Literary and Scientific Institutions, Colleges, Schools, Science Classes, &c., &c.


"WEALE'S SERIES includes Text-Books on almost every branch of Science and Industry, comprising such subjects as Agriculture, Architecture and Building, Civil Engineering, Fine Arts, Mechanics and Mechanical Engineering, Physical and Chemical Science, and many miscellaneous Treatises. The whole are constantly undergoing revision, and new editions, brought up to the latest discoveries in scientific research, are constantly issued. The prices at which they are sold are as low as their excellence is assured."—*American Literary Gazette*.

"Amongst the literature of technical education, WEALE'S SERIES has ever enjoyed a high reputation, and the additions being made by Messrs. CROSBY LOCKWOOD & CO. render the series even more complete, and bring the information upon the several subjects down to the present time."—*Mining Journal*.

"It is impossible to do otherwise than bear testimony to the value of WEALE'S SERIES."—*Engineer*.

"Everybody—even that outrageous nuisance 'Every Schoolboy'—knows the merits of 'WEALE'S RUDIMENTARY SERIES.' Any persons wishing to acquire knowledge cannot do better than look through Weale's Series and get all the books they require. The Series is indeed an inexhaustible mine of literary wealth."—*The Metropolitan*.

"WEALE'S SERIES has become a standard as well as an unrivalled collection of treatises in all branches of art and science."—*Public Opinion*.



LONDON, 1862.
THE PRIZE MEDAL

Was awarded to the Publishers of
"WEALE'S SERIES."



CROSBY LOCKWOOD & CO.,

7, STATIONERS' HALL COURT, LUDGATE HILL, LONDON, E.C.

WEALE'S RUDIMENTARY SCIENTIFIC SERIES.




** The volumes of this Series are freely Illustrated with Woodcuts, or otherwise, where requisite. Throughout the following List it must be understood that the books are bound in limp cloth, unless otherwise stated; but the volumes marked with a ‡ may also be had strongly bound in cloth boards for 6d. extra.

N.B.—In ordering from this List it is recommended, as a means of facilitating business and obviating error, to quote the numbers affixed to the volumes, as well as the titles and prices.

No. ARCHITECTURE, BUILDING, ETC.


16. *ARCHITECTURE—ORDERS*—The Orders and their Æsthetic Principles. By W. H. LEEDS. Illustrated. 1s. 6d.
17. *ARCHITECTURE—STYLES*—The History and Description of the Styles of Architecture of Various Countries, from the Earliest to the Present Period. By T. TALBOT BURY, F.R.I.B.A., &c. Illustrated. 2s.
** *ORDERS AND STYLES OF ARCHITECTURE, in One Vol., 3s. 6d.*
18. *ARCHITECTURE—DESIGN*—The Principles of Design in Architecture, as deducible from Nature and exemplified in the Works of the Greek and Gothic Architects. By E. L. GARBETT, Architect. Illustrated. 2s.
** *The three preceding Works, in One handsome Vol., half bound, entitled "MODERN ARCHITECTURE," price 6s.*
22. *THE ART OF BUILDING*, Rudiments of. General Principles of Construction, Materials used in Building, Strength and Use of Materials, Working Drawings, Specifications, and Estimates. By E. DOBSON, 2s.‡
23. *BRICKS AND TILES*, Rudimentary Treatise on the Manufacture of; containing an Outline of the Principles of Brickmaking. By EDW. DOBSON, M.R.I.B.A. With Additions by C. TOMLINSON, F.R.S. Illustrated, 3s.‡
25. *MASONRY AND STONECUTTING*, Rudimentary Treatise on; in which the Principles of Masonic Projection and their application to the Construction of Curved Wing-Walls, Domes, Oblique Bridges, and Roman and Gothic Vaulting, are concisely explained. By EDWARD DOBSON, M.R.I.B.A., &c. Illustrated with Plates and Diagrams. 2s. 6d.‡
44. *FOUNDATIONS AND CONCRETE WORKS*, a Rudimentary Treatise on; containing a Synopsis of the principal cases of Foundation Works, with the usual Modes of Treatment, and Practical Remarks on Footings, Planking, Sand, Concrete, Béton, Pile-driving, Caissons, and Cofferdams. By E. DOBSON, M.R.I.B.A., &c. Fourth Edition, revised by GEORGE DODD, C.E. Illustrated. 1s. 6d.
42. *COTTAGE BUILDING*. By C. BRUCE ALLEN, Architect. Ninth Edition, revised and enlarged. Numerous Illustrations. 1s. 6d.
45. *LIMES, CEMENTS, MORTARS, CONCRETES, MASTICS, PLASTERING*, &c. By G. R. BURNELL, C.E. Eleventh Edition. 1s. 6d.
57. *WARMING AND VENTILATION*, a Rudimentary Treatise on; being a concise Exposition of the General Principles of the Art of Warming and Ventilating Domestic and Public Buildings, Mines, Lighthouses, Ships, &c. By CHARLES TOMLINSON, F.R.S., &c. Illustrated. 3s.
- 83** *CONSTRUCTION OF DOOR LOCKS*. Compiled from the Papers of A. C. HOBBS, Esq., of New York, and Edited by CHARLES TOMLINSON, F.R.S. To which is added, a Description of Fenby's Patent Locks, and a Note upon IRON SAFES by ROBERT MALLETT, M.I.C.E. Illus. 2s. 6d.
- III. *ARCHES, PIERS, BUTTRESSES, &c.*: Experimental Essays on the Principles of Construction in; made with a view to their being useful to the Practical Builder. By WILLIAM BLAND. Illustrated. 1s. 6d.

 The ‡ indicates that these vols. may be had strongly bound at 6d. extra.

LONDON: CROSBY LOCKWOOD AND CO.,

Architecture, Building, etc., *continued.*

116. *THE ACOUSTICS OF PUBLIC BUILDINGS*; or, The Principles of the Science of Sound applied to the purposes of the Architect and Builder. By T. ROGER SMITH, M.R.I.B.A., Architect. Illustrated. 1s. 6d.
124. *CONSTRUCTION OF ROOFS*, Treatise on the, as regards Carpentry and Joinery. Deduced from the Works of ROBISON, PRICE, and TREGGOLD. Illustrated. 1s. 6d.
127. *ARCHITECTURAL MODELLING IN PAPER*, the Art of. By T. A. RICHARDSON, Architect. Illustrated. 1s. 6d.
128. *VITRUVIUS—THE ARCHITECTURE OF MARCUS VITRUVIUS POLLO*. In Ten Books. Translated from the Latin by JOSEPH GWILT, F.S.A., F.R.A.S. With 23 Plates. 5s.
130. *GRECIAN ARCHITECTURE*, An Inquiry into the Principles of Beauty in; with an Historical View of the Rise and Progress of the Art in Greece. By the EARL OF ABERDEEN. 1s.
- *.* *The two preceding Works in One handsome Vol., half bound, entitled "ANCIENT ARCHITECTURE," price 6s.*
- 16, 17, 18, 128, and 130, in *One Vol., entitled "ANCIENT AND MODERN ARCHITECTURE," half bound, 12s.*
132. *DWELLING-HOUSES*, a Rudimentary Treatise on the Erection of. Illustrated by a Perspective View, Plans, Elevations, and Sections of a pair of Semi-detached Villas, with the Specification, Quantities, and Estimates, and every requisite detail, in sequence, for their Construction and Finishing. By S. H. BROOKS, Architect. New Edition, with Plates. 2s. 6d.‡
156. *QUANTITIES AND MEASUREMENTS*, How to Calculate and Take them in Bricklayers', Masons', Plasterers', Plumbers', Painters', Paper-hangers', Gilders', Smiths', Carpenters', and Joiners' Work. By A. C. BEATON, Architect and Surveyor. New and Enlarged Edition. Illus. 1s. 6d.
175. *LOCKWOOD & CO.'S BUILDER'S AND CONTRACTOR'S PRICE BOOK*, for 1880, containing the latest Prices of all kinds of Builders' Materials and Labour, and of all Trades connected with Building: Lists of the Members of the Metropolitan Board of Works, of Districts, District Officers, and District Surveyors, and the Metropolitan Bye-laws. Edited by FRANCIS T. W. MILLER, Architect and Surveyor. 3s. 6d.; half bound, 4s.
182. *CARPENTRY AND JOINERY—THE ELEMENTARY PRINCIPLES OF CARPENTRY*. Chiefly composed from the Standard Work of THOMAS TREGGOLD, C.E. With Additions from the Works of the most Recent Authorities, and a TREATISE ON JOINERY by E. WYNDHAM TARN, M.A. Numerous Illustrations. 3s. 6d.‡
- 182*. *CARPENTRY AND JOINERY. ATLAS* of 35 Plates to accompany the foregoing book. With Descriptive Letterpress. 4to. 6s.; cloth boards, 7s. 6d.
187. *HINTS TO YOUNG ARCHITECTS*. By GEORGE WIGHTWICK. New, Revised, and enlarged Edition. By G. HUSKISSON GUILLAUME, Architect. With numerous Woodcuts. 3s. 6d.‡
188. *HOUSE PAINTING, GRAINING, MARBLING, AND SIGN WRITING*: A Practical Manual of, containing full information on the Processes of House-Painting, the Formation of Letters and Practice of Sign-Writing, the Principles of Decorative Art, a Course of Elementary Drawing for House-Painters, Writers, &c., &c. With 9 Coloured Plates of Woods and Marbles, and nearly 150 Wood Engravings. By ELLIS A. DAVIDSON. Second Edition, carefully revised. 5s. cloth limp; 6s. cloth boards.
189. *THE RUDIMENTS OF PRACTICAL BRICKLAYING*. In Six Sections: General Principles; Arch Drawing, Cutting, and Setting; Pointing; Paving, Tiling, Materials; Slating and Plastering; Practical Geometry, Mensuration, &c. By ADAM HAMMOND. Illustrated. 1s. 6d.
191. *PLUMBING*. A Text-Book to the Practice of the Art or Craft of the Plumber. With Chapters upon House Drainage, embodying the latest Improvements. Second Edition, enlarged. Containing 300 Illustrations. By W. P. BUCHAN, Sanitary Engineer. 3s. 6d.‡ *[Just published.]*

 The ‡ indicates that these vols. may be had strongly bound at 6d. extra.

Architecture, Building, etc., *continued.*

192. *THE TIMBER IMPORTER'S, TIMBER MERCHANT'S,* and *BUILDER'S STANDARD GUIDE*; comprising copious and valuable Memoranda for the Retailer and Builder. By RICHARD E. GRANDY. Second Edition, Revised. 3s.‡
205. *THE ART OF LETTER PAINTING MADE EASY.* By J. G. BADENOCH. Illustrated with 12 full-page Engravings of Examples. 1s. [Just published.]
206. *A BOOK ON BUILDING, Civil and Ecclesiastical,* including *CHURCH RESTORATION.* With the Theory of Domes and the Great Pyramid, and Dimensions of many Churches and other Great Buildings. By Sir EDMUND BECKETT, Bart., LL.D., Q.C., F.R.A.S., Chancellor and Vicar-General of York. Second Edition, enlarged, 4s. 6d.‡ [Just published.]

CIVIL ENGINEERING, ETC.

13. *CIVIL ENGINEERING,* the Rudiments of. By HENRY LAW, C.E., and GEORGE R. BURNELL, C.E. New Edition, much enlarged and thoroughly revised by D. KINNEAR CLARK, C.E. [Nearly ready.]
29. *THE DRAINAGE OF DISTRICTS AND LANDS.* By G. DRYSDALE DEMPSEY, C.E. [New Edition in preparation.]
30. *THE DRAINAGE OF TOWNS AND BUILDINGS.* By G. DRYSDALE DEMPSEY, C.E. New Edition. Illustrated. 2s. 6d.
31. *WELL-DIGGING, BORING, AND PUMP-WORK.* By JOHN GEORGE SWINDELL, A.R.I.B.A. New Edition, by G. R. BURNELL, C.E. 1s. 6d.
35. *THE BLASTING AND QUARRYING OF STONE,* for Building and other Purposes. With Remarks on the Blowing up of Bridges. By Gen. Sir JOHN BURGOYNE, Bart., K.C.B. Illustrated. 1s. 6d.
62. *RAILWAY CONSTRUCTION,* Elementary and Practical Instructions on the Science of. By Sir M. STEPHENSON, C.E. New Edition, by EDWARD NUGENT, C.E. With Statistics of the Capital, Dividends, and Working of Railways in the United Kingdom. By E. D. CHATTAWAY. 4s.
- 80*. *EMBANKING LANDS FROM THE SEA,* the Practice of. Treated as a Means of Profitable Employment for Capital. With Examples and Particulars of actual Embankments, and also Practical Remarks on the Repair of old Sea Walls. By JOHN WIGGINS, F.G.S. New Edition. 2s.
81. *WATER WORKS,* for the Supply of Cities and Towns. With a Description of the Principal Geological Formations of England as influencing Supplies of Water; and Details of Engines and Pumping Machinery for raising Water. By SAMUEL HUGHES, F.G.S., C.E. New Edition. 4s.‡
117. *SUBTERRANEAN SURVEYING,* an Elementary and Practical Treatise on. By THOMAS FENWICK. Also the Method of Conducting Subterranean Surveys without the Use of the Magnetic Needle, and other Modern Improvements. By THOMAS BAKER, C.E. Illustrated. 2s. 6d.‡
118. *CIVIL ENGINEERING IN NORTH AMERICA,* a Sketch of. By DAVID STEVENSON, F.R.S.E., &c. Plates and Diagrams. 3s.
197. *ROADS AND STREETS (THE CONSTRUCTION OF),* in two Parts: I. *THE ART OF CONSTRUCTING COMMON ROADS,* by HENRY LAW, C.E., revised and condensed by D. KINNEAR CLARK, C.E.; II. *RECENT PRACTICE,* including pavements of Stone, Wood, and Asphalte, by D. K. CLARK, M.I.C.E. 4s. 6d.‡
203. *SANITARY WORK IN THE SMALLER TOWNS AND IN VILLAGES.* Comprising:—1. Some of the more Common Forms of Nuisance and their Remedies; 2. Drainage; 3. Water Supply. A useful book for Members of Local Boards and Rural Sanitary Authorities, Health Officers, Engineers, Surveyors, &c. By CHARLES SLAGG, A.I.C.E. 2s. 6d.‡
212. *THE CONSTRUCTION OF GAS-WORKS,* and the Manufacture and Distribution of Coal Gas. Originally written by SAMUEL HUGHES, C.E. Sixth Edition, re-written and much Enlarged by WILLIAM RICHARDS, C.E. With 72 Illustrations. 4s. 6d.‡ [Just published.]
213. *PIONEER ENGINEERING.* A Treatise on the Engineering Operations connected with the Settlement of Waste Lands in New Countries. By EDWARD DOBSON, Assoc. Inst. C.E., Author of "The Art of Building," &c. 4s. 6d.‡ [Just published.]

 The ‡ indicates that these vols. may be had strongly bound at 6d. extra.

LONDON: CROSBY LOCKWOOD AND CO.,

MECHANICAL ENGINEERING, ETC.


33. **CRANES**, the Construction of, and other Machinery for Raising Heavy Bodies for the Erection of Buildings, and for Hoisting Goods. By JOSEPH GLYNN, F.R.S., &c. Illustrated. 1s. 6d.
34. **THE STEAM ENGINE**, a Rudimentary Treatise on. By Dr. LARDNER. Illustrated. 1s. 6d.
59. **STEAM BOILERS**: their Construction and Management. By R. ARMSTRONG, C.E. Illustrated. 1s. 6d.
67. **CLOCKS, WATCHES, AND BELLS**, a Rudimentary Treatise on. By Sir EDMUND BECKETT (late EDMUND BECKETT DENISON), LL.D., Q.C. A New, Revised, and considerably Enlarged Edition (the 6th), with very numerous Illustrations. 4s. 6d. cloth limp; 5s. 6d. cloth boards, gilt.
82. **THE POWER OF WATER**, as applied to drive Flour Mills, and to give motion to Turbines and other Hydrostatic Engines. By JOSEPH GLYNN, F.R.S., &c. New Edition, Illustrated. 2s.†
98. **PRACTICAL MECHANISM**, the Elements of; and Machine Tools. By T. BAKER, C.E. With Remarks on Tools and Machinery, by J. NASMYTH, C.E. Plates. 2s. 6d.†
114. **MACHINERY**, Elementary Principles of, in its Construction and Working. Illustrated by numerous Examples of Modern Machinery for different Branches of Manufacture. By C. D. ABEL, C.E. 1s. 6d.
139. **THE STEAM ENGINE**, a Treatise on the Mathematical Theory of, with Rules at length, and Examples for the Use of Practical Men. By T. BAKER, C.E. Illustrated. 1s. 6d.
162. **THE BRASS FOUNDER'S MANUAL**; Instructions for Modelling, Pattern-Making, Moulding, Turning, Filing, Burnishing, Bronzing, &c. With copious Receipts, numerous Tables, and Notes on Prime Costs and Estimates. By WALTER GRAHAM. Illustrated. 2s.†
164. **MODERN WORKSHOP PRACTICE**, as applied to Marine, Land, and Locomotive Engines, Floating Docks, Dredging Machines, Bridges, Cranes, Ship-building, &c., &c. By J. G. WINTON. Illustrated. 3s.†
165. **IRON AND HEAT**, exhibiting the Principles concerned in the Construction of Iron Beams, Pillars, and Bridge Girders, and the Action of Heat in the Smelting Furnace. By J. ARMOUR, C.E. 2s. 6d.†
166. **POWER IN MOTION**: Horse-Power, Toothed-Wheel Gearing, Long and Short Driving Bands, and Angular Forces. By JAMES ARMOUR, C.E. With 73 Diagrams. 2s. 6d.†
167. **THE APPLICATION OF IRON TO THE CONSTRUCTION OF BRIDGES, GIRDERS, ROOFS, AND OTHER WORKS**. By FRANCIS CAMPIN, C.E. Second Edition, revised and corrected. 2s. 6d.†
171. **THE WORKMAN'S MANUAL OF ENGINEERING DRAWING**. By JOHN MAXTON, Engineer, Instructor in Engineering Drawing, Royal Naval College, Greenwich. Third Edition. Illustrated with 7 Plates and nearly 350 Woodcuts. 3s. 6d.†
190. **STEAM AND THE STEAM ENGINE**, Stationary and Portable. Being an extension of Mr. John Sewell's "Treatise on Steam." By D. K. CLARK, M.I.C.E. Second Edition, revised. 3s. 6d.†
200. **FUEL**, its Combustion and Economy; being an Abridgment of "A Treatise on the Combustion of Coal and the Prevention of Smoke," by C. W. WILLIAMS, A.I.C.E. With extensive additions on Recent Practice in the Combustion and Economy of Fuel—Coal, Coke, Wood, Peat, Petroleum, &c.—by D. K. CLARK, M.I.C.E. 2nd Edition. 3s. 6d.† [Just published.]
202. **LOCOMOTIVE ENGINES**, A Rudimentary Treatise on. Comprising an Historical Sketch and Description of the Locomotive Engine, by G. D. DEMPSEY, C.E.; with large additions treating of the Modern Locomotive, by D. KINNEAR CLARK, M.I.C.E. 3s.† [Just published.]
211. **THE BOILERMAKER'S ASSISTANT** in Drawing, Tempering, and Calculating Boiler Work and Tank Work, with Rules for the Evaporated Power and the Horse Power of Steam Boilers, and the Proportions of Safety-Valves; and useful Tables of Rivet Joints, of Circles, Weights of Metals, &c. By JOHN COURTNEY, Practical Boiler Maker. Edited by D. K. CLARK, C.E. 100 Illustrations. 2s. [Just published.]

 The † indicates that these vols. may be had strongly bound at 6d. extra.

7, STATIONERS' HALL COURT, LUDGATE HILL, E.C.

SHIPBUILDING, NAVIGATION, MARINE ENGINEERING, ETC.


51. *NAVAL ARCHITECTURE*, the Rudiments of; or an Exposition of the Elementary Principles of the Science, and their Practical Application to Naval Construction. Compiled for the Use of Beginners. By JAMES PEAKE, School of Naval Architecture, H.M. Dockyard, Portsmouth. Fourth Edition, corrected, with Plates and Diagrams. 3s. 6d.†
- 53*. *SHIPS FOR OCEAN AND RIVER SERVICE*, Elementary and Practical Principles of the Construction of. By HAKON A. SOMMERFELDT, Surveyor of the Royal Norwegian Navy. With an Appendix. 1s. 6d.
- 53**. *AN ATLAS OF ENGRAVINGS* to illustrate the above. Twelve large folding plates. Royal 4to, cloth. 7s. 6d.
54. *MASTING, MAST-MAKING, AND RIGGING OF SHIPS*, Rudimentary Treatise on. Also Tables of Spars, Rigging, Blocks; Chain, Wire, and Hemp Ropes, &c., relative to every class of vessels. With an Appendix of Dimensions of Masts and Yards of the Royal Navy. By ROBERT KIPPING, N.A. Fourteenth Edition. Illustrated. 2s.†
- 54*. *IRON SHIP-BUILDING*. With Practical Examples and Details for the Use of Ship Owners and Ship Builders. By JOHN GRANTHAM, Consulting Engineer and Naval Architect. 5th Edition, with Additions. 4s.
- 54**. *AN ATLAS OF FORTY PLATES* to illustrate the above. Fifth Edition. Including the latest Examples, such as H.M. Steam Frigates "Warrior," "Hercules," "Bellerophon;" H.M. Troop Ship "Serapis," Iron Floating Dock, &c., &c. 4to, boards. 38s.
55. *THE SAILOR'S SEA BOOK*: a Rudimentary Treatise on Navigation. Part I. How to Keep the Log and Work it off. Part II. On Finding the Latitude and Longitude. By JAMES GREENWOOD, B.A. To which are added, the Deviation and Error of the Compass; Great Circle Sailing; the International (Commercial) Code of Signals; the Rule of the Road at Sea; Rocket and Mortar Apparatus for Saving Life; the Law of Storms; and a Brief Dictionary of Sea Terms. With numerous Woodcuts and Coloured Plates of Flags. New, thoroughly revised and much enlarged edition. By W. H. ROSSER. 2s. 6d.† [Just published.]
80. *MARINE ENGINES, AND STEAM VESSELS*, a Treatise on. Together with Practical Remarks on the Screw and Propelling Power, as used in the Royal and Merchant Navy. By ROBERT MURRAY, C.E., Engineer-Surveyor to the Board of Trade. With a Glossary of Technical Terms, and their Equivalents in French, German, and Spanish. Seventh Edition, revised and enlarged. Illustrated. 3s.†
- 83bis. *THE FORMS OF SHIPS AND BOATS*: Hints, Experimentally Derived, on some of the Principles regulating Ship-building. By W. BLAND. Seventh Edition, revised, with numerous Illustrations and Models. 1s. 6d.
99. *NAVIGATION AND NAUTICAL ASTRONOMY*, in Theory and Practice. With Attempts to facilitate the Finding of the Time and the Longitude at Sea. By J. R. YOUNG, formerly Professor of Mathematics in Belfast College. Illustrated. 2s. 6d.
- 100*. *TABLES* intended to facilitate the Operations of Navigation and Nautical Astronomy, as an Accompaniment to the above Book. By J. R. YOUNG. 1s. 6d.
106. *SHIPS' ANCHORS*, a Treatise on. By G. COTSELL, N.A. 1s. 6d.
149. *SAILS AND SAIL-MAKING*, an Elementary Treatise on. With Draughting, and the Centre of Effort of the Sails. Also, Weights and Sizes of Ropes; Mastng, Rigging, and Sails of Steam Vessels, &c., &c. Eleventh Edition, enlarged, with an Appendix. By ROBERT KIPPING, N.A., Sailmaker, Quayside, Newcastle. Illustrated. 2s. 6d.†
155. *THE ENGINEER'S GUIDE TO THE ROYAL AND MERCANTILE NAVIES*. By a PRACTICAL ENGINEER. Revised by D. F. M'CARTHY, late of the Ordnance Survey Office, Southampton. 3s.
- 55 & 204. *PRACTICAL NAVIGATION*. Consisting of The Sailor's Sea-Book. By JAMES GREENWOOD and W. H. ROSSER. Together with the requisite Mathematical and Nautical Tables for the Working of the Problems. By HENRY LAW, C.E., and J. R. YOUNG, formerly Professor of Mathematics in Belfast College. Illustrated with numerous Wood Engravings and Coloured Plates. 7s. Strongly half-bound in leather.

 The † indicates that these vols. may be had strongly bound at 6d. extra.

LONDON: CROSBY LOCKWOOD AND CO.,

PHYSICAL SCIENCE, NATURAL PHILOSOPHY, ETC.

1. *CHEMISTRY*, for the Use of Beginners. By Professor GEORGE FOWNES, F.R.S. With an Appendix on the Application of Chemistry to Agriculture. 1s.
2. *NATURAL PHILOSOPHY*, Introduction to the Study of; for the Use of Beginners. By C. TOMLINSON, Lecturer on Natural Science in King's College School, London. Woodcuts. 1s. 6d.
4. *MINERALOGY*, Rudiments of; a concise View of the Properties of Minerals. By A. RAMSAY, Jun. Woodcuts and Steel Plates. 3s.†
6. *MECHANICS*, Rudimentary Treatise on; being a concise Exposition of the General Principles of Mechanical Science, and their Applications. By CHARLES TOMLINSON. Illustrated. 1s. 6d.
7. *ELECTRICITY*; showing the General Principles of Electrical Science, and the purposes to which it has been applied. By Sir W. SNOW HARRIS, F.R.S., &c. With Additions by R. SABINE, C.E., F.S.A. 1s. 6d.
- 7*. *GALVANISM*, Rudimentary Treatise on; and the General Principles of Animal and Voltaic Electricity. By Sir W. SNOW HARRIS. New Edition, with considerable Additions by ROBERT SABINE, C.E., F.S.A. 1s. 6d.
8. *MAGNETISM*; being a concise Exposition of the General Principles of Magnetical Science, and the Purposes to which it has been applied. By Sir W. SNOW HARRIS. New Edition, revised and enlarged by H. M. NOAD, Ph.D., Vice-President of the Chemical Society, Author of "A Manual of Electricity," &c., &c. With 165 Woodcuts. 3s. 6d.†
11. *THE ELECTRIC TELEGRAPH*; its History and Progress; with Descriptions of some of the Apparatus. By R. SABINE, C.E., F.S.A. 3s.
12. *PNEUMATICS*, for the Use of Beginners. By CHARLES TOMLINSON. Illustrated. 1s. 6d.
72. *MANUAL OF THE MOLLUSCA*; a Treatise on Recent and Fossil Shells. By Dr. S. P. WOODWARD, A.L.S. With Appendix by RALPH TATE, A.L.S., F.G.S. With numerous Plates and 300 Woodcuts. 6s. 6d. Cloth boards, 7s. 6d.
- 79*. *PHOTOGRAPHY*, Popular Treatise on; with a Description of the Stereoscope, &c. Translated from the French of D. VAN MONCKHOVEN, by W. H. THORNTWAITE, Ph.D. Woodcuts. 1s. 6d.
96. *ASTRONOMY*. By the Rev. R. MAIN, M.A., F.R.S., &c. New Edition, with an Appendix on "Spectrum Analysis." Woodcuts. 1s. 6d.
97. *STATICS AND DYNAMICS*, the Principles and Practice of; embracing also a clear development of Hydrostatics, Hydrodynamics, and Central Forces. By T. BAKER, C.E. 1s. 6d.
138. *TELEGRAPH*, Handbook of the; a Manual of Telegraphy, Telegraph Clerks' Remembrancer, and Guide to Candidates for Employment in the Telegraph Service. By R. BOND. Fourth Edition, revised and enlarged; to which is appended, QUESTIONS on MAGNETISM, ELECTRICITY, and PRACTICAL TELEGRAPHY, for the Use of Students, by W. MCGREGOR, First Assistant Supnt., Indian Gov. Telegraphs. 3s.†
143. *EXPERIMENTAL ESSAYS*. By CHARLES TOMLINSON. I. On the Motions of Camphor on Water. II. On the Motion of Camphor towards the Light. III. History of the Modern Theory of Dew. Woodcuts. 1s.
173. *PHYSICAL GEOLOGY*, partly based on Major-General PORTLOCK's "Rudiments of Geology." By RALPH TATE, A.L.S., &c. Woodcuts. 2s.
174. *HISTORICAL GEOLOGY*, partly based on Major-General PORTLOCK's "Rudiments." By RALPH TATE, A.L.S., &c. Woodcuts. 2s. 6d.
- 173 & 174. *RUDIMENTARY TREATISE ON GEOLOGY*, Physical and Historical. Partly based on Major-General PORTLOCK's "Rudiments of Geology." By RALPH TATE, A.L.S., F.G.S., &c., &c. Numerous Illustrations. In One Volume. 4s. 6d.†
183. *ANIMAL PHYSICS*, Handbook of. By Dr. LARDNER, D.C.L., & formerly Professor of Natural Philosophy and Astronomy in University College, Lond. With 520 Illustrations. In One Vol. 7s. 6d., cloth boards.
184. *ANIMAL PHYSICS*. By Dr. LARDNER. Part I., Chapters I—VII. 4s.
184. *ANIMAL PHYSICS*. By Dr. LARDNER. Part II., Chapters VIII—XVIII. 3s.

 The † indicates that these vols. may be had strongly bound at 6d. extra.

7. STATIONERS' HALL COURT, LUDGATE HILL, E.C.


MINING, METALLURGY, ETC.

117. *SUBTERRANEAN SURVEYING*, Elementary and Practical Treatise on, with and without the Magnetic Needle. By THOMAS FENWICK, Surveyor of Mines, and THOMAS BAKER, C.E. Illustrated. 2s. 6d.†
133. *METALLURGY OF COPPER*; an Introduction to the Methods of Seeking, Mining, and Assaying Copper, and Manufacturing its Alloys. By ROBERT H. LAMBORN, Ph.D. Woodcuts. 2s. 6d.†
134. *METALLURGY OF SILVER AND LEAD*. A Description of the Ores; their Assay and Treatment, and valuable Constituents. By Dr. R. H. LAMBORN. Woodcuts. 2s. 6d.†
135. *ELECTRO-METALLURGY*; Practically Treated. By ALEXANDER WATT, F.R.S.S.A. Seventh Edition, revised, with important additions, including the Electro-Deposition of Nickel, &c., &c. Woodcuts. 3s.†
172. *MINING TOOLS*, Manual of. For the Use of Mine Managers, Agents, Students, &c. Comprising Observations on the Materials from, and Processes by, which they are manufactured; their Special Uses, Applications, Qualities, and Efficiency. By WILLIAM MORGANS, Lecturer on Mining at the Bristol School of Mines. 2s. 6d.†
- 172*. *MINING TOOLS, ATLAS* of Engravings to Illustrate the above, containing 235 Illustrations of Mining Tools, drawn to Scale. 4to. 4s. 6d.; cloth boards, 6s.
176. *METALLURGY OF IRON*, a Treatise on the. Containing History of Iron Manufacture, Methods of Assay, and Analyses of Iron Ores, Processes of Manufacture of Iron and Steel, &c. By H. BAUERMAN, F.G.S. Fourth Edition, enlarged, with numerous Illustrations. 4s. 6d.†
180. *COAL AND COAL MINING*, A Rudimentary Treatise on. By WARINGTON W. SMYTH, M.A., F.R.S., &c., Chief Inspector of the Mines of the Crown and of the Duchy of Cornwall. Fifth Edition, revised and enlarged. With numerous Illustrations. 3s. 6d.†
195. *THE MINERAL SURVEYOR AND VALUER'S COMPLETE GUIDE*, with new Traverse Tables, and Descriptions of Improved Instruments; also the Correct Principles of Laying out and Valuing Mineral Properties. By WILLIAM LINTERN, Mining and Civil Engineer. With four Plates of Diagrams, Plans, &c. 3s. 6d.†
214. *A TREATISE ON SLATE AND SLATE QUARRYING*, Scientific, Practical, and Commercial. By D. C. DAVIES, F.G.S., Mining Engineer, &c. With numerous Illustrations and Folding Plates. 3s.†

[Just published.]

FINE ARTS.

20. *PERSPECTIVE FOR BEGINNERS*. Adapted to Young Students and Amateurs in Architecture, Painting, &c. By GEORGE PYNE, Artist. Woodcuts. 2s.
40. *GLASS STAINING*; or, The Art of Painting on Glass. From & the German of Dr. GESSERT. With an Appendix on THE ART OF ENAMELLING, &c.; together with THE ART OF PAINTING ON GLASS. From the German of EMANUEL OTTO FROMBERG. In One Volume. 2s. 6d.
41. *MUSIC*, A Rudimentary and Practical Treatise on. With numerous Examples. By CHARLES CHILD SPENCER. 2s. 6d.
71. *PIANOFORTE*, The Art of Playing the. With numerous Exercises and Lessons. Written and Selected from the Best Masters, by CHARLES CHILD SPENCER. 3s. 6d.
181. *PAINTING POPULARLY EXPLAINED*, including Fresco, Oil, Mosaic, Water Colour, Water-Glass, Tempera, Encaustic, Miniature, Painting on Ivory, Vellum, Pottery, Enamel, Glass, &c. With Historical Sketches of the Progress of the Art by THOMAS JOHN GULLICK, assisted by JOHN TIMBS, F.S.A. Fourth Edition, revised and enlarged, with Frontispiece and Vignette. 5s.†
186. *A GRAMMAR OF COLOURING*, applied to Decorative Painting and the Arts. By GEORGE FIELD. New Edition, enlarged and adapted to the Use of the Ornamental Painter and Designer. By ELLIS A. DAVIDSON, Author of "Drawing for Carpenters," &c. With two new Coloured Diagrams and numerous Engravings on Wood. 3s.†

 The † indicates that these vols. may be had strongly bound at 6d. extra.

LONDON: CROSBY LOCKWOOD AND CO.,

AGRICULTURE, GARDENING, ETC.


29. *THE DRAINAGE OF DISTRICTS AND LANDS.* By G. DRYSDALE DEMSEY, C.E. [New Edition in preparation.]
66. *CLAY LANDS AND LOAMY SOILS.* By Professor DONALDSON. 1s.
131. *MILLER'S, MERCHANT'S, AND FARMER'S READY RECKONER*, for ascertaining at sight the value of any quantity of Corn, from One Bushel to One Hundred Quarters, at any given price, from £1 to £5 per Qr. With approximate values of Millstones, Millwork, &c. 1s.
140. *SOILS, MANURES, AND CROPS.* (Vol. 1. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN. Woodcuts. 2s.
141. *FARMING AND FARMING ECONOMY*, Notes, Historical and Practical, on. (Vol. 2. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN. Woodcuts. 3s.
142. *STOCK; CATTLE, SHEEP, AND HORSES.* (Vol. 3. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN. Woodcuts. 2s. 6d.
145. *DAIRY, PIGS, AND POULTRY*, Management of the. By R. SCOTT BURN. With Notes on the Diseases of Stock. (Vol. 4. OUTLINES OF MODERN FARMING.) Woodcuts. 2s.
146. *UTILIZATION OF SEWAGE, IRRIGATION, AND RECLAMATION OF WASTE LAND.* (Vol. 5. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN. Woodcuts. 2s. 6d.
- ** Nos. 140-1-2-5-6, in One Vol., handsomely half-bound, entitled "OUTLINES OF MODERN FARMING." By ROBERT SCOTT BURN. Price 12s.
177. *FRUIT TREES*, The Scientific and Profitable Culture of. From the French of DU BREUIL. Revised by GEO. GLENNY. 187 Woodcuts. 3s. 6d.†
198. *SHEEP; THE HISTORY, STRUCTURE, ECONOMY, AND DISEASES OF.* By W. C. SPOONER, M.R.V.C., &c. Fourth Edition, considerably enlarged; with numerous fine engravings, including some specimens of New and Improved Breeds. 366 pp. 3s. 6d.†
201. *KITCHEN GARDENING MADE EASY.* Showing how to prepare and lay out the ground, the best means of cultivating every known Vegetable and Herb, with cultural directions for the management of them all the year round. By GEORGE M. F. GLENNY, Editor of "Glenny's Illustrated Garden Almanack," and Author of "Floriculture," &c. 1s. 6d.†
207. *OUTLINES OF FARM MANAGEMENT, and the Organization of Farm Labour:* Treating of the General Work of the Farm; Field and Live Stock; Details of Contract Work; Specialities of Labour; Economical Management of the Farmhouse and Cottage, and their Domestic Animals. By ROBERT SCOTT BURN. Numerous Illustrations. 2s. 6d.†
208. *OUTLINES OF LANDED ESTATES MANAGEMENT:* Treating of the Varieties of Lands on the Estate; Peculiarities of its Farms; Methods of Farming; the Setting-out of Farms and their Fields; the Construction of Roads, Fences, Gates, and the various Farm Buildings; the several Classes of Waste or Unproductive Lands; Irrigation; Drainage, Plantation, &c. By R. SCOTT BURN. With numerous Illustrations. 2s. 6d.†
- *** Nos. 207 & 208 in One Vol., handsomely half-bound, entitled "OUTLINES OF LANDED ESTATES AND FARM MANAGEMENT." By R. SCOTT BURN. Price 6s.
209. *THE TREE PLANTER AND PLANT PROPAGATOR:* Being a Practical Manual on the Propagation of Forest Trees, Fruit Trees, Flowering Shrubs, Flowering Plants, Pot-Herbs, &c.; with numerous Illustrations of Grafting, Layering, Budding, Cuttings, &c., Useful Implements, Houses, Pits, &c. By SAMUEL WOOD, Author of "Good Gardening." 2s.†
210. *THE TREE PRUNER:* Being a Practical Manual on the Pruning of Fruit Trees, including also their Training and Renovation, with the Best Method of bringing Old and Worn-out Trees into a State of Bearing; also treating of the Pruning of Shrubs, Climbers and Flowering Plants. With numerous Illustrations. By SAMUEL WOOD, Author of "Good Gardening," &c. 2s.†
- *** Nos. 209 & 210 in One Vol., handsomely half-bound, entitled "THE TREE PLANTER, PROPAGATOR AND PRUNER." By SAMUEL WOOD. Price 5s.



The † indicates that these vols. may be had strongly bound at 6d. extra.

ARITHMETIC, GEOMETRY, MATHEMATICS, ETC.


32. **MATHEMATICAL INSTRUMENTS**, a Treatise on; in which their Construction and the Methods of Testing, Adjusting, and Using them are concisely Explained. By J. F. HEATHER, M.A., of the Royal Military Academy, Woolwich. Original Edition, in 1 vol., Illustrated. 1s. 6d.
- * * * *In ordering the above, be careful to say, "Original Edition" (No. 32), to distinguish it from the Enlarged Edition in 3 vols. (Nos. 168-9-70.)*
60. **LAND AND ENGINEERING SURVEYING**, a Treatise on; with all the Modern Improvements. Arranged for the Use of Schools and Private Students; also for Practical Land Surveyors and Engineers. By T. BAKER, C.E. New Edition, revised by EDWARD NUGENT, C.E. Illustrated with Plates and Diagrams. 2s.†
- 61*. **READY RECKONER FOR THE ADMEASUREMENT OF LAND**. By ABRAHAM ARMAN, Schoolmaster, Thurleigh, Beds. To which is added a Table, showing the Price of Work, from 2s. 6d. to £1 per acre, and Tables for the Valuation of Land, from 1s. to £1,000 per acre, and from one pole to two thousand acres in extent, &c., &c. 1s. 6d.
76. **DESCRIPTIVE GEOMETRY**, an Elementary Treatise on; with a Theory of Shadows and of Perspective, extracted from the French of G. MONGE. To which is added, a description of the Principles and Practice of Isometrical Projection; the whole being intended as an introduction to the Application of Descriptive Geometry to various branches of the Arts. By J. F. HEATHER, M.A. Illustrated with 14 Plates. 2s.
178. **PRACTICAL PLANE GEOMETRY**: giving the Simplest Modes of Constructing Figures contained in one Plane and Geometrical Construction of the Ground. By J. F. HEATHER, M.A. With 215 Woodcuts. 2s.
179. **PROJECTION**: Orthographic, Topographic, and Perspective: giving the various Modes of Delineating Solid Forms by Constructions on a Single Plane Surface. By J. F. HEATHER, M.A. [In preparation.]
- * * * *The above three volumes will form a COMPLETE ELEMENTARY COURSE OF MATHEMATICAL DRAWING.*
83. **COMMERCIAL BOOK-KEEPING**. With Commercial Phrases and Forms in English, French, Italian, and German. By JAMES HADDON, M.A., Arithmetical Master of King's College School, London. 1s. 6d.
84. **ARITHMETIC**, a Rudimentary Treatise on: with full Explanations of its Theoretical Principles, and numerous Examples for Practice. For the Use of Schools and for Self-Instruction. By J. R. YOUNG, late Professor of Mathematics in Belfast College. New Edition, with Index. 1s. 6d.
- 84*. A KEY to the above, containing Solutions in full to the Exercises, together with Comments, Explanations, and Improved Processes, for the Use of Teachers and Unassisted Learners. By J. R. YOUNG. 1s. 6d.
85. **EQUATIONAL ARITHMETIC**, applied to Questions of Interest,
- 85*. Annuities, Life Assurance, and General Commerce; with various Tables by which all Calculations may be greatly facilitated. By W. HIRSELEY. 2s.
86. **ALGEBRA**, the Elements of. By JAMES HADDON, M.A., Second Mathematical Master of King's College School. With Appendix, containing miscellaneous Investigations, and a Collection of Problems in various parts of Algebra. 2s.
- 86*. A KEY AND COMPANION to the above Book, forming an extensive repository of Solved Examples and Problems in Illustration of the various Expedients necessary in Algebraical Operations. Especially adapted for Self-Instruction. By J. R. YOUNG. 1s. 6d.
88. **EUCLID, THE ELEMENTS OF**: with many additional Propositions
89. and Explanatory Notes: to which is prefixed, an Introductory Essay on Logic. By HENRY LAW, C.E. 2s. 6d.†
- * * * *Sold also separately, viz. :—*
88. **EUCLID, The First Three Books**. By HENRY LAW, C.E. 1s.
89. **EUCLID, Books 4, 5, 6, 11, 12**. By HENRY LAW, C.E. 1s. 6d.

 *The † indicates that these vols. may be had strongly bound at 6d. extra.*

LONDON: CROSBY LOCKWOOD AND CO.,

Arithmetic, Geometry, Mathematics, etc., *continued.*

90. *ANALYTICAL GEOMETRY AND CONIC SECTIONS*, a Rudimentary Treatise on. By JAMES HANN, late Mathematical Master of King's College School, London. A New Edition, re-written and enlarged by J. R. YOUNG, formerly Professor of Mathematics at Belfast College. 2s.‡
91. *PLANE TRIGONOMETRY*, the Elements of. By JAMES HANN, formerly Mathematical Master of King's College, London. 1s.
92. *SPHERICAL TRIGONOMETRY*, the Elements of. By JAMES HANN. Revised by CHARLES H. DOWLING, C.E. 1s.
 ** Or with "The Elements of Plane Trigonometry," in One Volume, 2s.
93. *MENSURATION AND MEASURING*, for Students and Practical Use. With the Mensuration and Levelling of Land for the Purposes of Modern Engineering. By T. BAKER, C.E. New Edition, with Corrections and Additions by E. NUGENT, C.E. Illustrated. 1s. 6d.
- 101*. *MEASURES, WEIGHTS, AND MONEYS OF ALL NATIONS*, and an Analysis of the Christian, Hebrew, and Mahometan Calendars. By W. S. B. WOOLHOUSE, F.R.A.S. [Reprinting.]
102. *INTEGRAL CALCULUS*, Rudimentary Treatise on the. By HOMERSHAM COX, B.A. Illustrated. 1s.
103. *INTEGRAL CALCULUS*, Examples on the. By JAMES HANN, late of King's College, London. Illustrated. 1s.
101. *DIFFERENTIAL CALCULUS*, Elements of the. By W. S. B. WOOLHOUSE, F.R.A.S., &c. 1s. 6d.
105. *MNEMONICAL LESSONS*. — GEOMETRY, ALGEBRA, AND TRIGONOMETRY, in Easy Mnemonical Lessons. By the Rev. THOMAS PENYNGTON KIRKMAN, M.A. 1s. 6d.
136. *ARITHMETIC*, Rudimentary, for the Use of Schools and Self-Instruction. By JAMES HADDON, M.A. Revised by ABRAHAM ARMAN. 1s. 6d.
137. A KEY TO HADDON'S RUDIMENTARY ARITHMETIC. By A. ARMAN. 1s. 6d.
168. *DRAWING AND MEASURING INSTRUMENTS*. Including—I. Instruments employed in Geometrical and Mechanical Drawing, and in the Construction, Copying, and Measurement of Maps and Plans. II. Instruments used for the purposes of Accurate Measurement, and for Arithmetical Computations. By J. F. HEATHER, M.A., late of the Royal Military Academy, Woolwich, Author of "Descriptive Geometry," &c., &c. Illustrated. 1s. 6d.
169. *OPTICAL INSTRUMENTS*. Including (more especially) Telescopes, Microscopes, and Apparatus for producing copies of Maps and Plans by Photography. By J. F. HEATHER, M.A. Illustrated. 1s. 6d.
170. *SURVEYING AND ASTRONOMICAL INSTRUMENTS*. Including—I. Instruments Used for Determining the Geometrical Features of a portion of Ground. II. Instruments Employed in Astronomical Observations. By J. F. HEATHER, M.A. Illustrated. 1s. 6d.
- ** The above three volumes form an enlargement of the Author's original work, "Mathematical Instruments: their Construction, Adjustment, Testing, and Use," the Thirteenth Edition of which is on sale, price 1s. 6d. (See No. 32 in the Series.)
168. } *MATHEMATICAL INSTRUMENTS*. By J. F. HEATHER,
 169. } M.A. Enlarged Edition, for the most part entirely re-written. The 3 Parts as
 170. } above, in One thick Volume. With numerous Illustrations. 4s. 6d.‡
158. *THE SLIDE RULE, AND HOW TO USE IT*; containing full, easy, and simple Instructions to perform all Business Calculations with unexampled rapidity and accuracy. By CHARLES HOARE, C.E. With a Slide Rule in tuck of cover. 3s.‡
185. *THE COMPLETE MEASURER*; setting forth the Measurement of Boards, Glass, &c., &c.; Unequal-sided, Square-sided, Octagonal-sided, Round Timber and Stone, and Standing Timber. With a Table showing the solidity of hewn or eight-sided timber, or of any octagonal-sided column. Compiled for Timber-growers, Merchants, and Surveyors, Stonemasons, Architects, and others. By RICHARD HORTON. Third Edition, with valuable additions. 4s.; strongly bound in leather, 5s.

 The ‡ indicates that these vols. may be had strongly bound at 6d. extra.


7, STATIONERS' HALL COURT, LUDGATE HILL, E.C.

Arithmetic, Geometry, Mathematics, etc., *continued.*

196. *THEORY OF COMPOUND INTEREST AND ANNUITIES*; with Tables of Logarithms for the more Difficult Computations of Interest, Discount, Annuities, &c. By FÉDOR THOMAN, of the Société Cr  dit Mobilier, Paris. 4s.†
199. *INTUITIVE CALCULATIONS*; or, Easy and Compendious Methods of Performing the various Arithmetical Operations required in Commercial and Business Transactions; together with Full Explanations of Decimals and Duodecimals, several Useful Tables, and an Examination and Discussion of the best Schemes for a Decimal Coinage. By DANIEL O'GORMAN. Twenty-fifth Edition, corrected and enlarged by J. R. YOUNG, formerly Professor of Mathematics in Belfast College. 3s.†
- 20†. *MATHEMATICAL TABLES*, for Trigonometrical, Astronomical, and Nautical Calculations; to which is prefixed a Treatise on Logarithms. By HENRY LAW, C.E. Together with a Series of Tables for Navigation and Nautical Astronomy. By J. R. YOUNG, formerly Professor of Mathematics in Belfast College. New Edition. 3s. 6d.† [Just published.]

MISCELLANEOUS VOLUMES.

36. *A DICTIONARY OF TERMS used in ARCHITECTURE, BUILDING, ENGINEERING, MINING, METALLURGY, ARCHÆOLOGY, the FINE ARTS, &c.* By JOHN WEALE. Fifth Edition. Revised by ROBERT HUNT, F.R.S., Keeper of Mining Records. Numerous Illustrations. 5s. cloth limp; 6s. cloth boards.
50. *THE LAW OF CONTRACTS FOR WORKS AND SERVICES.* By DAVID GIBBONS. Third Edition, enlarged. 3s.†
112. *MANUAL OF DOMESTIC MEDICINE.* By R. GOODING, B.A., M.D. Intended as a Family Guide in all Cases of Accident and Emergency. 2s.†
- 112*. *MANAGEMENT OF HEALTH.* A Manual of Home and Personal Hygiene. By the Rev. JAMES BAIRD, B.A. 1s.
150. *LOGIC*, Pure and Applied. By S. H. EMMENS. 1s. 6d.
152. *PRACTICAL HINTS FOR INVESTING MONEY.* With an Explanation of the Mode of Transacting Business on the Stock Exchange. By FRANCIS PLAYFORD, Sworn Broker. 1s. 6d.
153. *SELECTIONS FROM LOCKE'S ESSAYS ON THE HUMAN UNDERSTANDING.* With Notes by S. H. EMMENS. 2s.
154. *GENERAL HINTS TO EMIGRANTS.* Containing Notices of the various Fields for Emigration. With Hints on Preparation for Emigrating, Outfits, &c., &c. With Directions and Recipes useful to the Emigrant. With a Map of the World. 2s.
157. *THE EMIGRANT'S GUIDE TO NATAL.* By ROBERT JAMES MANN, F.R.A.S., F.M.S. Second Edition, carefully corrected to the present Date. Map. 2s.
193. *HANDBOOK OF FIELD FORTIFICATION*, intended for the Guidance of Officers Preparing for Promotion, and especially adapted to the requirements of Beginners. By Major W. W. KNOLLYS, F.R.G.S., 93rd Sutherland Highlanders, &c. With 163 Woodcuts. 3s.†
194. *THE HOUSE MANAGER*: Being a Guide to Housekeeping. Practical Cookery, Pickling and Preserving, Household Work, Dairy Management, the Table and Dessert, Cellarage of Wines, Home-brewing and Wine-making, the Boudoir and Dressing-room, Travelling, Stable Economy, Gardening Operations, &c. By AN OLD HOUSEKEEPER. 3s. 6d.†
194. *HOUSE BOOK (The)*. Comprising:—I. THE HOUSE MANAGER. II. DOMESTIC MEDICINE. By RALPH GOODING, M.D. III. MANAGEMENT OF HEALTH. By JAMES BAIRD. In One Vol., & strongly half-bound. 6s.
- 112*.

 The † indicates that these vols. may be had strongly bound at 6d. extra.

LONDON: CROSBY LOCKWOOD AND CO.,

EDUCATIONAL AND CLASSICAL SERIES.

HISTORY.

1. **England, Outlines of the History of;** more especially with reference to the Origin and Progress of the English Constitution. By WILLIAM DOUGLAS HAMILTON, F.S.A., of Her Majesty's Public Record Office. 4th Edition, revised. 5s.; cloth boards, 6s.
5. **Greece, Outlines of the History of;** in connection with the Rise of the Arts and Civilization in Europe. By W. DOUGLAS HAMILTON, of University College, London, and EDWARD LEVIEN, M.A., of Balliol College, Oxford. 2s. 6d.; cloth boards, 3s. 6d.
7. **Rome, Outlines of the History of;** from the Earliest Period to the Christian Era and the Commencement of the Decline of the Empire. By EDWARD LEVIEN, of Balliol College, Oxford. Map, 2s. 6d.; cl. bds. 3s. 6d.
9. **Chronology of History, Art, Literature, and Progress,** from the Creation of the World to the Conclusion of the Franco-German War. The Continuation by W. D. HAMILTON, F.S.A. 3s.; cloth boards, 3s. 6d.
50. **Dates and Events in English History,** for the use of Candidates in Public and Private Examinations. By the Rev. E. RAND. 1s.

ENGLISH LANGUAGE AND MISCELLANEOUS.

11. **Grammar of the English Tongue, Spoken and Written.** With an Introduction to the Study of Comparative Philology. By HYDE CLARKE, D.C.L. Third Edition. 1s. 6d.
- 11*. **Philology; Handbook of the Comparative Philology of English,** Anglo-Saxon, Frisian, Flemish or Dutch, Low or Platt Dutch, High Dutch or German, Danish, Swedish, Icelandic, Latin, Italian, French, Spanish, and Portuguese Tongues. By HYDE CLARKE, D.C.L. 1s.
12. **Dictionary of the English Language, as Spoken and Written.** Containing above 100,000 Words. By HYDE CLARKE, D.C.L. 3s. 6d.; cloth boards, 4s. 6d.; complete with the GRAMMAR, cloth bds., 5s. 6d.
48. **Composition and Punctuation, familiarly Explained** for those who have neglected the Study of Grammar. By JUSTIN BREMAN. 17th Edition. 1s. 6d.
49. **Derivative Spelling-Book: Giving the Origin of Every Word** from the Greek, Latin, Saxon, German, Teutonic, Dutch, French, Spanish, and other Languages; with their present Acceptation and Pronunciation. By J. ROWBOTHAM, F.R.A.S. Improved Edition. 1s. 6d.
51. **The Art of Extempore Speaking: Hints for the Pulpit, the Senate, and the Bar.** By M. BATAIN, Vicar-General and Professor at the Sorbonne. Translated from the French. 7th Edition, carefully corrected. 2s. 6d.
52. **Mining and Quarrying, with the Sciences connected there-with.** First Book of, for Schools. By J. H. COLLINS, F.G.S., Lecturer to the Miners' Association of Cornwall and Devon. 1s.
53. **Places and Facts in Political and Physical Geography,** for Candidates in Examinations. By the Rev. EDGAR RAND, B.A. 1s.
54. **Analytical Chemistry, Qualitative and Quantitative, a Course of.** To which is prefixed, a Brief Treatise upon Modern Chemical Nomenclature and Notation. By WM. W. PINK and GEORGE E. WEBSTER. 2s.

THE SCHOOL MANAGERS' SERIES OF READING BOOKS,

Adapted to the Requirements of the New Code. Edited by the Rev. A. R. GRANT, Rector of Hitcham, and Honorary Canon of Ely; formerly H.M. Inspector of Schools.

INTRODUCTORY PRIMER, 3d.

	s.	d.		s.	d.
FIRST STANDARD . . .	0	6	FOURTH STANDARD . . .	1	2
SECOND " . . .	0	10	FIFTH " . . .	1	6
THIRD " . . .	1	0	SIXTH " . . .	1	6

LESSONS FROM THE BIBLE. Part I. Old Testament. 1s.

LESSONS FROM THE BIBLE. Part II. New Testament, to which is added

THE GEOGRAPHY OF THE BIBLE, for very young Children. By Rev. C. THORNTON FORSTER. 1s. 2d. ** Or the Two Parts in One Volume. 2s.

FRENCH.

24. French Grammar. With Complete and Concise Rules on the Genders of French Nouns. By G. L. STRAUSS, Ph.D. 1s. 6d.
 25. French-English Dictionary. Comprising a large number of New Terms used in Engineering, Mining, &c. By ALFRED ELWES. 1s. 6d.
 26. English-French Dictionary. By ALFRED ELWES. 2s.
 25,26. French Dictionary (as above). Complete, in One Vol., 3s.; cloth boards, 3s. 6d. ** Or with the GRAMMAR, cloth boards, 4s. 6d.
 47. French and English Phrase Book: containing Introductory Lessons, with Translations, several Vocabularies of Words, a Collection of suitable Phrases, and Easy Familiar Dialogues. 1s.

GERMAN.

39. German Grammar. Adapted for English Students, from Heyse's Theoretical and Practical Grammar, by Dr. G. L. STRAUSS. 1s.
 40. German Reader: A Series of Extracts, carefully culled from the most approved Authors of Germany; with Notes, Philological and Explanatory. By G. L. STRAUSS, Ph.D. 1s.
 41. German Triglot Dictionary. By NICHOLAS ESTERHAZY S. A. HAMILTON. Part I. English-German-French. 1s.
 42. German Triglot Dictionary. Part II. German-French-English. 1s.
 43. German Triglot Dictionary. Part III. French-German-English. 1s.
 41-43. German Triglot Dictionary (as above), in One Vol., 3s.; cloth boards, 4s. ** Or with the GERMAN GRAMMAR, cloth boards, 5s.

ITALIAN.

27. Italian Grammar, arranged in Twenty Lessons, with a Course of Exercises. By ALFRED ELWES. 1s. 6d.
 28. Italian Triglot Dictionary, wherein the Genders of all the Italian and French Nouns are carefully noted down. By ALFRED ELWES. Vol. 1. Italian-English-French. 2s. 6d.
 30. Italian Triglot Dictionary. By A. ELWES. Vol. 2. English-French-Italian. 2s. 6d.
 32. Italian Triglot Dictionary. By ALFRED ELWES. Vol. 3. French-Italian-English. 2s. 6d.
 28,30. Italian Triglot Dictionary (as above). In One Vol., 7s. 6d.
 32. Cloth boards.

SPANISH AND PORTUGUESE.

34. Spanish Grammar, in a Simple and Practical Form. With a Course of Exercises. By ALFRED ELWES. 1s. 6d.
 35. Spanish-English and English-Spanish Dictionary. Including a large number of Technical Terms used in Mining, Engineering, &c., with the proper Accents and the Gender of every Noun. By ALFRED ELWES. 4s.; cloth boards, 5s. ** Or with the GRAMMAR, cloth boards, 6s.
 55. Portuguese Grammar, in a Simple and Practical Form. With a Course of Exercises. By ALFRED ELWES. 1s. 6d.
 56. Portuguese-English and English-Portuguese Dictionary, with the Genders of each Noun. By ALFRED ELWES.
[In preparation.]

HEBREW.

- 46*. Hebrew Grammar. By Dr. BRESSLAU. 1s. 6d.
 44. Hebrew and English Dictionary, Biblical and Rabbinical; containing the Hebrew and Chaldee Roots of the Old Testament Post-Rabbinical Writings. By Dr. BRESSLAU. 6s. ** Or with the GRAMMAR, 7s.
 46. English and Hebrew Dictionary. By Dr. BRESSLAU. 3s.
 44,46. Hebrew Dictionary (as above), in Two Vols., complete, with 46*. the GRAMMAR, cloth boards, 12s.

LATIN.

19. **Latin Grammar.** Containing the Inflections and Elementary Principles of Translation and Construction. By the Rev. THOMAS GOODWIN, M.A., Head Master of the Greenwich Proprietary School. 1s.
20. **Latin-English Dictionary.** By the Rev. THOMAS GOODWIN, M.A. 2s.
22. **English-Latin Dictionary;** together with an Appendix of French and Italian Words which have their origin from the Latin. By the Rev. THOMAS GOODWIN, M.A. 1s. 6d.
- 20, 22. **Latin Dictionary** (as above). Complete in One Vol., 3s. 6d.; cloth boards, 4s. 6d. * * Or with the GRAMMAR, cloth boards, 5s. 6d.

LATIN CLASSICS. With Explanatory Notes in English.

1. **Latin Delectus.** Containing Extracts from Classical Authors, with Genealogical Vocabularies and Explanatory Notes, by H. YOUNG. 1s.
2. **Cæsar's Commentarii de Bello Gallico.** Notes, and a Geographical Register for the Use of Schools, by H. YOUNG. 2s.
3. **Cornelius Nepos.** With Notes. By H. YOUNG. 1s.
4. **Virgilii Maronis Bucolica et Georgica.** With Notes on the Bucolics by W. RUSHTON, M.A., and on the Georgics by H. YOUNG. 1s. 6d.
5. **Virgilii Maronis Æneis.** With Notes, Critical and Explanatory, by H. YOUNG. New Edition, revised and improved. With copious Additional Notes by Rev. T. H. L. LEARY, D.C.L., formerly Scholar of Brasenose College, Oxford. 3s.
- 5* ——— Part 1. Books i.—vi., 1s. 6d.
- 5** ——— Part 2. Books vii.—xii., 2s.
6. **Horace; Odes, Epode, and Carmen Sæculare.** Notes by H. YOUNG. 1s. 6d.
7. **Horace; Satires, Epistles, and Ars Poetica.** Notes by W. BROWNRIGG SMITH, M.A., F.R.G.S. 1s. 6d.
8. **Sallustii Crispi Catalina et Bellum Jugurthinum.** Notes, Critical and Explanatory, by W. M. DONNE, B.A., Trin. Coll., Cam. 1s. 6d.
9. **Terentii Andria et Heautontimorumenos.** With Notes, Critical and Explanatory, by the Rev. JAMES DAVIES, M.A. 1s. 6d.
10. **Terentii Adelphi, Hecyra, Phormio.** Edited, with Notes, Critical and Explanatory, by the Rev. JAMES DAVIES, M.A. 2s.
11. **Terentii Eunuchus, Comœdia.** Notes, by Rev. J. DAVIES, M.A. 1s. 6d.
12. **Ciceronis Oratio pro Sexto Roscio Amerino.** Edited, with an Introduction, Analysis, and Notes, Explanatory and Critical, by the Rev. JAMES DAVIES, M.A. 1s.
13. **Ciceronis Orationes in Catilinam, Verrem, et pro Archia.** With Introduction, Analysis, and Notes, Explanatory and Critical, by Rev. T. H. L. LEARY, D.C.L. formerly Scholar of Brasenose College, Oxford. 1s. 6d.
14. **Ciceronis Cato Major, Lælius, Brutus, sive de Senectute, de Amicitia, de Claris Oratoribus Dialogi.** With Notes by W. BROWNRIGG SMITH, M.A., F.R.G.S. 2s.
16. **Livy: History of Rome.** Notes by H. YOUNG and W. B. SMITH, M.A. Part 1. Books i., ii., 1s. 6d.
- 16* ——— Part 2. Books iii., iv., v., 1s. 6d.
17. ——— Part 3. Books xxi., xxii., 1s. 6d.
19. **Latin Verse Selections,** from Catullus, Tibullus, Propertius, and Ovid. Notes by W. B. DONNE, M.A., Trinity College, Cambridge. 2s.
20. **Latin Prose Selections,** from Varro, Columella, Vitruvius, Seneca, Quintilian, Florus, Velleius Paterculus, Valerius Maximus Suetonius, Apuleius, &c. Notes by W. B. DONNE, M.A. 2s.
21. **Juvenalis Satiræ.** With Prolegomena and Notes by T. H. S. ESCOTT, B.A., Lecturer on Logic at King's College, London. 2s.

GREEK.

14. Greek Grammar, in accordance with the Principles and Philo-
logical Researches of the most eminent Scholars of our own day. By HANS
CLAUDE HAMILTON. 1s. 6d.
- 15, 17. Greek Lexicon. Containing all the Words in General Use, with
their Significations, Inflections, and Doubtful Quantities. By HENRY R.
HAMILTON. Vol. 1. Greek-English, 2s.; Vol. 2. English-Greek, 2s. Or the
Two Vols. in One, 4s.: cloth boards, 5s.
- 14, 15. Greek Lexicon (as above). Complete, with the GRAMMAR, in
17. One Vol., cloth boards, 6s.
- GREEK CLASSICS.** With Explanatory Notes in English.
1. Greek Delectus. Containing Extracts from Classical Authors,
with Genealogical Vocabulary and Explanatory Notes, by H. YOUNG. New
Edition, with an improved and enlarged Supplementary Vocabulary, by JOHN
HUTCHISON, M.A., of the High School, Glasgow. 1s. 6d.
- 2, 3. Xenophon's Anabasis; or, The Retreat of the Ten Thousand.
Notes and a Geographical Register, by H. YOUNG. Part 1. Books i. to iii.,
1s. Part 2. Books iv. to vii., 1s.
4. Lucian's Select Dialogues. The Text carefully revised, with
Grammatical and Explanatory Notes, by H. YOUNG. 1s. 6d.
- 5-12. Homer, The Works of. According to the Text of BAUMLEIN.
With Notes, Critical and Explanatory, drawn from the best and latest
Authorities, with Preliminary Observations and Appendices, by T. H. L.
LEARY, M.A., D.C.L.
- | | | |
|--------------|-------------------------------------|--|
| THE ILIAD: | Part 1. Books i. to vi., 1s. 6d. | Part 3. Books xiii. to xviii., 1s. 6d. |
| | Part 2. Books vii. to xii., 1s. 6d. | Part 4. Books xix. to xxiv., 1s. 6d. |
| THE ODYSSEY: | Part 1. Books i. to vi., 1s. 6d. | Part 3. Books xiii. to xviii., 1s. 6d. |
| | Part 2. Books vii. to xii., 1s. 6d. | Part 4. Books xix. to xxiv., and
Hymns, 2s. |
13. Plato's Dialogues: The Apology of Socrates, the Crito, and
the Phædo. From the Text of C. F. HERMANN. Edited with Notes, Critical
and Explanatory, by the Rev. JAMES DAVIES, M.A. 2s.
- 14-17. Herodotus, The History of, chiefly after the Text of GAISFORD.
With Preliminary Observations and Appendices, and Notes, Critical and
Explanatory, by T. H. L. LEARY, M.A., D.C.L.
- | | |
|---------|---|
| Part 1. | Books i., ii. (The Clio and Euterpe), 2s. |
| Part 2. | Books iii., iv. (The Thalia and Melpomene), 2s. |
| Part 3. | Books v.-vii. (The Terpsichore, Erato, and Polymnia), 2s. |
| Part 4. | Books viii., ix. (The Urania and Calliope) and Index, 1s. 6d. |
18. Sophocles: Œdipus Tyrannus. Notes by H. YOUNG. 1s.
20. Sophocles: Antigone. From the Text of DINDORF. Notes,
Critical and Explanatory, by the Rev. JOHN MILNER, B.A. 2s.
23. Euripides: Hecuba and Medea. Chiefly from the Text of DIN-
DORF. With Notes, Critical and Explanatory, by W. BROWNRIGG SMITH,
M.A., F.R.G.S. 1s. 6d.
26. Euripides: Alcestis. Chiefly from the Text of DINDORF. With
Notes, Critical and Explanatory, by JOHN MILNER, B.A. 1s. 6d.
30. Æschylus: Prometheus Vincetus: The Prometheus Bound. From
the Text of DINDORF. Edited, with English Notes, Critical and Explanatory,
by the Rev. JAMES DAVIES, M.A. 1s.
32. Æschylus: Septem Contra Thebes: The Seven against Thebes.
From the Text of DINDORF. Edited, with English Notes, Critical and Ex-
planatory, by the Rev. JAMES DAVIES, M.A. 1s.
40. Aristophanes: Acharnians. Chiefly from the Text of C. H.
WEISE. With Notes, by C. S. T. TOWNSHEND, M.A. 1s. 6d.
41. Thucydides: History of the Peloponnesian War. Notes by H.
YOUNG. Book 1. 1s.
42. Xenophon's Panegyric on Agesilaus. Notes and Intro-
duction by LL. F. W. JEWITT. 1s. 6d.
43. Demosthenes. The Oration on the Crown and the Philippics.
With English Notes. By Rev. T. H. L. LEARY, D.C.L., formerly Scholar of
Brasenose College, Oxford. 1s. 6d.

LONDON, December, 1880.

A Catalogue of Books

INCLUDING MANY NEW AND STANDARD WORKS IN

ENGINEERING, ARCHITECTURE, AGRICULTURE,
MATHEMATICS, MECHANICS, SCIENCE, ETC.

PUBLISHED BY

CROSBY LOCKWOOD & CO.,

7, STATIONERS'-HALL COURT, LUDGATE HILL, E.C.

ENGINEERING, SURVEYING, ETC.

Humber's New Work on Water-Supply.

A COMPREHENSIVE TREATISE on the WATER-SUPPLY of CITIES and TOWNS. By WILLIAM HUMBER, A-M. Inst. C.E., and M. Inst. M.E. Illustrated with 50 Double Plates, 1 Single Plate, Coloured Frontispiece, and upwards of 250 Woodcuts, and containing 400 pages of Text, Imp. 4to, 6l. 6s. elegantly and substantially half-bound in morocco.

List of Contents:—

I. Historical Sketch of some of the means that have been adopted for the Supply of Water to Cities and Towns.—II. Water and the Foreign Matter usually associated with it.—III. Rainfall and Evaporation.—IV. Springs and the water-bearing formations of various districts.—V. Measurement and Estimation of the Flow of Water.—VI. On the Selection of the Source of Supply.—VII. Wells.—VIII. Reservoirs.—IX. The Purification of Water.—X. Pumps.—XI. Pumping Machinery.—XII. Conduits.—XIII. Distribution of Water.—XIV. Meters, Service Pipes, and House Fittings.—XV. The Law and Economy of Water Works.—XVI. Constant and Intermittent Supply.—XVII. Description of Plates.—Appendices, giving Tables of Rates of Supply, Velocities, &c. &c., together with Specifications of several Works illustrated, among which will be found:—Aberdeen, Bideford, Canterbury, Dundee, Halifax, Lambeth, Rotherham, Dublin, and others.

"The most systematic and valuable work upon water supply hitherto produced in English, or in any other language . . . Mr. Humber's work is characterised almost throughout by an exhaustiveness much more distinctive of French and German than of English technical treatises."—*Engineer*.

Humber's Great Work on Bridge Construction.

A COMPLETE and PRACTICAL TREATISE on CAST and WROUGHT-IRON BRIDGE CONSTRUCTION, including Iron Foundations. In Three Parts—Theoretical, Practical, and Descriptive. By WILLIAM HUMBER, A-M. Inst. C.E., and M. Inst. M.E. Third Edition, with 115 Double Plates. In 2 vols. imp. 4to, 6l. 16s. 6d. half-bound in morocco.

"A book—and particularly a large and costly treatise like Mr. Humber's—which has reached its third edition may certainly be said to have established its own reputation."—*Engineering*.

Humber's Modern Engineering.

A RECORD of the PROGRESS of MODERN ENGINEERING. First Series. Comprising Civil, Mechanical, Marine, Hydraulic, Railway, Bridge, and other Engineering Works, &c. By WILLIAM HUMBER, A-M. Inst. C.E., &c. Imp. 4to, with 36 Double Plates, drawn to a large scale, and Portrait of John Hawkshaw C.E., F.R.S., &c., and descriptive Letter-press, Specifications, &c. 3*l.* 3*s.* half morocco.

List of the Plates and Diagrams.

Victoria Station and Roof, L. B. & S. C. R. (8 plates); Southport Pier (2 plates); Victoria Station and Roof, L. C. & D. and G. W. R. (6 plates); Roof of Cremorne Music Hall; Bridge over G. N. Railway; Roof of Station, Dutch Rhenish Rail (2

plates); Bridge over the Thames, West London Extension Railway (5 plates); Armour Plates; Suspension Bridge, Thames (4 plates); The Allen Engine; Suspension Bridge, Avon (3 plates); Underground Railway (3 plates).

"Handsomely lithographed and printed. It will find favour with many who desire to preserve in a permanent form copies of the plans and specifications prepared for the guidance of the contractors for many important engineering works."—*Engineer*.

HUMBER'S RECORD OF MODERN ENGINEERING. Second Series. Imp. 4to, with 36 Double Plates, Portrait of Robert Stephenson, C.E., &c., and descriptive Letterpress, Specifications, &c. 3*l.* 3*s.* half morocco.

List of the Plates and Diagrams.

Birkenhead Docks, Low Water Basin (15 plates); Charing Cross Station Roof, C. C. Railway (3 plates); Digswell Viaduct, G. N. Railway; Robbery Wood Viaduct, G. N. Railway; Iron Permanent Way; Clydach Viaduct, Merthyr, Tredegar, and Abergavenny Railway; Ebbw

Viaduct, Merthyr, Tredegar, and Abergavenny Railway; College Wood Viaduct, Cornwall Railway; Dublin Winter Palace Roof (3 plates); Bridge over the Thames, L. C. and D. Railway (6 plates); Albert Harbour, Greenock (4 plates).

HUMBER'S RECORD OF MODERN ENGINEERING. Third Series. Imp. 4to, with 40 Double Plates, Portrait of J. R. M'Clean, Esq., late Pres. Inst. C.E., and descriptive Letterpress, Specifications, &c. 3*l.* 3*s.* half morocco.

List of the Plates and Diagrams.

MAIN DRAINAGE, METROPOLIS.—*North Side*.—Map showing Interception of Sewers; Middle Level Sewer (2 plates); Outfall Sewer, Bridge over River Lea (3 plates); Outfall Sewer, Bridge over Marsh Lane, North Woolwich Railway, and Bow and Barking Railway Junction; Outfall Sewer, Bridge over Bow and Barking Railway (3 plates); Outfall Sewer, Bridge over East London Waterworks' Feeder (2 plates); Outfall Sewer, Reservoir (2 plates); Outfall Sewer, Tumbling Bay and Outlet; Outfall Sewer, Penstocks. *South Side*.—Outfall Sewer, Bermondsey

Branch (2 plates); Outfall Sewer, Reservoir and Outlet (4 plates); Outfall Sewer, Filth Hoist; Sections of Sewers (North and South Sides).

THAMES EMBANKMENT.—Section of River Wall; Steamboat Pier, Westminster (2 plates); Landing Stairs between Charing Cross and Waterloo Bridges; York Gate (2 plates); Overflow and Outlet at Savoy Street Sewer (3 plates); Steamboat Pier, Waterloo Bridge (3 plates); Junction of Sewers, Plans and Sections; Gullies, Plans and Sections; Rolling Stock; Granite and Iron Forts.

HUMBER'S RECORD OF MODERN ENGINEERING. Fourth Series. Imp. 4to, with 36 Double Plates, Portrait of John Fowler, Esq., late Pres. Inst. C.E., and descriptive Letterpress, Specifications, &c. 3*l.* 3*s.* half morocco.

List of the Plates and Diagrams.

Abbey Mills Pumping Station, Main Drainage, Metropolis (4 plates); Barrow Docks (5 plates); Manquis Viaduct, Santiago and Valparaiso Railway (2 plates); Adam's Locomotive, St. Helen's Canal Railway (2 plates); Cannon Street Station Roof, Charing Cross Railway (3 plates); Road Bridge over the River Moka (2 plates); Telegraphic Apparatus for Meso-

potamia; Viaduct over the River Wye, Midland Railway (3 plates); St. German's Viaduct, Cornwall Railway (2 plates); Wrought-Iron Cylinder for Diving Bell; Millwall Docks (6 plates); Milroy's Patent Excavator, Metropolitan District Railway (6 plates); Harbours, Ports, and Breakwaters (3 plates).

Strains, Formulæ & Diagrams for Calculation of.

A HANDY BOOK for the CALCULATION of STRAINS in GIRDERS and SIMILAR STRUCTURES, and their STRENGTH; consisting of Formulæ and Corresponding Diagrams, with numerous Details for Practical Application, &c. By WILLIAM HUMBER, A-M. Inst. C.E., &c. Third Edition. With nearly 100 Woodcuts and 3 Plates, Crown 8vo, 7s. 6d. cloth.

"The arrangement of the matter in this little volume is as convenient as it well could be. . . . The system of employing diagrams as a substitute for complex computations is one justly coming into great favour, and in that respect Mr. Humber's volume is fully up to the times."—*Engineering*.

"The formulæ are neatly expressed, and the diagrams good."—*Athenæum*.

Strains.

THE STRAINS ON STRUCTURES OF IRONWORK; with Practical Remarks on Iron Construction. By F. W. SHEILDS, M. Inst. C.E. Second Edition, with 5 Plates. Royal 8vo, 5s. cloth.

"The student cannot find a better little book on this subject than that written by Mr. Shields."—*Engineer*.

Barlow on the Strength of Materials, enlarged.

A TREATISE ON THE STRENGTH OF MATERIALS, with Rules for application in Architecture, the Construction of Suspension Bridges, Railways, &c.; and an Appendix on the Power of Locomotive Engines, and the effect of Inclined Planes and Gradients. By PETER BARLOW, F.R.S. A New Edition, revised by his Sons, P. W. BARLOW, F.R.S., and W. H. BARLOW, F.R.S. The whole arranged and edited by W. HUMBER, A-M. Inst. C.E. 8vo, 400 pp., with 19 large Plates, 18s. cloth.

"The best book on the subject which has yet appeared. . . . We know of no work that so completely fulfils its mission."—*English Mechanic*.

"The standard treatise upon this particular subject."—*Engineer*.

Strength of Cast Iron, &c.

A PRACTICAL ESSAY on the STRENGTH of CAST IRON and OTHER METALS. By THOMAS TREDGOLD, C.E. Fifth Edition. To which are added, Experimental Researches on the Strength and other Properties of Cast Iron, by E. HODGKINSON, F.R.S. With 9 Engravings and numerous Woodcuts. 8vo, 12s. cloth. * * HODGKINSON'S RESEARCHES, separate, price 6s.

Hydraulics.

HYDRAULIC TABLES, CO-EFFICIENTS, and FORMULÆ for finding the Discharge of Water from Orifices, Notches, Weirs, Pipes, and Rivers. With New Formulæ, Tables, and General Information on Rain-fall, Catchment-Basins, Drainage, Sewerage, Water Supply for Towns and Mill Power. By JOHN NEVILLE, Civil Engineer, M.R.I.A. Third Edition, carefully revised, with considerable Additions. Numerous Illustrations. Cr. 8vo, 14s. cloth.

"Undoubtedly an exceedingly useful and elaborate compilation."—*Iron*.

"Alike valuable to students and engineers in practice."—*Mining Journal*.

River Engineering.

RIVER BARS: Notes on the Causes of their Formation, and on their Treatment by Induced Tidal Scour, with a Description of the Successful Reduction by this Method of the Bar at Dublin. By I. J. MANN, Assistant Engineer to the Dublin Port and Docks Board. With Illustrations. Demy 8vo. [In the press.]

Levelling.

A TREATISE on the PRINCIPLES and PRACTICE of LEVELLING; showing its Application to Purposes of Railway and Civil Engineering, in the Construction of Roads; with Mr. TELFORD's Rules for the same. By FREDERICK W. SIMMS, F.G.S., M. Inst. C.E. Sixth Edition, very carefully revised, with the addition of Mr. LAW's Practical Examples for Setting out Railway Curves, and Mr. TRAUTWINE's Field Practice of Laying out Circular Curves. With 7 Plates and numerous Woodcuts. 8vo, 8s. 6d. cloth.

* * TRAUTWINE on Curves, separate, 5s.
 "The text-book on levelling in most of our engineering schools and colleges."—*Engineer.*

Practical Tunnelling.

PRACTICAL TUNNELLING: Explaining in detail the Setting out of the Works, Shaft-sinking and Heading-Driving, Ranging the Lines and Levelling under Ground, Sub-Excavating, Timbering, and the Construction of the Brickwork of Tunnels with the amount of labour required for, and the Cost of, the various portions of the work. By F. W. SIMMS, M. Inst. C.E. Third Edition, Revised and Extended. By D. KINNEAR CLARK, M.I.C.E. Imp. 8vo, with 21 Folding Plates and numerous Wood Engravings, 30s. cloth.

"It has been regarded from the first as a text-book of the subject. . . Mr. Clark has added immensely to the value of the book."—*Engineer.*

Steam.

STEAM AND THE STEAM ENGINE, Stationary and Portable. Being an Extension of Sewell's Treatise on Steam. By D. KINNEAR CLARK, M.I.C.E. Second Edition. 12mo, 4s. cloth.

Civil and Hydraulic Engineering.

CIVIL ENGINEERING (THE RUDIMENTS OF). By HENRY LAW, M. Inst. C.E. Including a Treatise on Hydraulic Engineering, by GEORGE R. BURNELL, M.I.C.E. Sixth Edition, Revised, with large additions on Recent Practice in Civil Engineering, by D. KINNEAR CLARK, M. Inst. C.E. [*In the press.*]

Gas-Lighting.

COMMON SENSE FOR GAS-USERS: a Catechism of Gas-Lighting for Householders, Gasfitters, Millowners, Architects, Engineers, &c. By R. WILSON, C.E. 2nd Edition. Cr. 8vo, 2s. 6d.

Bridge Construction in Masonry, Timber, & Iron.

EXAMPLES OF BRIDGE AND VIADUCT CONSTRUCTION OF MASONRY, TIMBER, AND IRON; consisting of 46 Plates from the Contract Drawings or Admeasurement of select Works. By W. DAVIS HASKOLL, C.E. Second Edition, with the addition of 554 Estimates, and the Practice of Setting out Works, with 6 pages of Diagrams. Imp. 4to, 2l. 12s. 6d. half-morocco.

"A work of the present nature by a man of Mr. Haskoll's experience, must prove invaluable. The tables of estimates considerably enhance its value."—*Engineering.*

Earthwork.

EARTHWORK TABLES, showing the Contents in Cubic Yards of Embankments, Cuttings, &c., of Heights or Depths up to an average of 80 feet. By JOSEPH BROADBENT, C.E., and FRANCIS CAMPIN, C.E. Cr. 8vo, oblong, 5s. cloth.

Tramways and their Working.

TRAMWAYS: their CONSTRUCTION and WORKING. Containing a Comprehensive History of the System; an exhaustive Analysis of the Various Modes of Traction, including Horse Power, Steam, Heated Water, and Compressed Air; a Description of the varieties of Rolling Stock; and ample Details of Cost and Working Expenses, with Special Reference to the Tramways of the United Kingdom. By D. KINNEAR CLARK, M. I. C. E., Author of 'Railway Machinery,' &c., in one vol. 8vo, with numerous Illustrations and thirteen folding Plates, 18s. cloth.

"All interested in tramways must refer to it, as all railway engineers have turned to the author's work 'Railway Machinery.'"—*The Engineer*.

"Mr. Clark's book is indispensable for the students of the subject."—*The Builder*.

Pioneer Engineering.

PIONEER ENGINEERING. A Treatise on the Engineering Operations connected with the Settlement of Waste Lands in New Countries. By EDWARD DOBSON, A.I.C.E. With Plates and Wood Engravings. Revised Edition. 12mo, 5s. cloth.

"A workmanlike production, and one without possession of which no man should start to encounter the duties of a pioneer engineer."—*Athenæum*.

"There is much in the book to render it very useful to an engineer proceeding to the colonies."—*Engineer*.

Steam Engine.

TEXT-BOOK ON THE STEAM ENGINE. By T. M. GOODEVE, M.A., Barrister-at-Law, Author of "The Principles of Mechanics," "The Elements of Mechanism," &c. Third Edition. With numerous Illustrations. Crown 8vo, 6s. cloth.

"Professor Goodeve has given us a treatise on the steam engine, which will bear comparison with anything written by Huxley or Maxwell, and we can award it no higher praise."—*Engineer*.

"Mr. Goodeve's text-book is a work of which every young engineer should possess himself."—*Mining Journal*.

Steam.

THE SAFE USE OF STEAM: containing Rules for Unprofessional Steam Users. By an ENGINEER. 4th Edition. Sewed, 6d.

"If steam-users would but learn this little book by heart, boiler explosions would become sensations by their rarity."—*English Mechanic*.

Works of Construction.

MATERIALS AND CONSTRUCTION: a Theoretical and Practical Treatise on the Strains, Designing, and Erection of Works of Construction. By FRANCIS CAMPIN, C.E., Author of "A Practical Treatise on Mechanical Engineering;" "The Principles and Construction of Machinery," &c. With Numerous Illustrations. 12mo, 3s. 6d. cloth boards. [Just published.]

Iron Bridges, Girders, Roofs, &c.

A TREATISE ON THE APPLICATION OF IRON TO THE CONSTRUCTION OF BRIDGES, GIRDERS, ROOFS, AND OTHER WORKS. By FRANCIS CAMPIN, C.E. Second Edition, Revised and Corrected. 12mo, 3s. cloth.

Construction of Iron Beams, Pillars, &c.

IRON AND HEAT; exhibiting the Principles concerned in the construction of Iron Beams, Pillars, and Bridge Girders, and the Action of Heat in the Smelting Furnace. By J. ARMOUR, C.E. 3s.

Oblique Arches.

A PRACTICAL TREATISE ON THE CONSTRUCTION OF OBLIQUE ARCHES. By JOHN HART. 3rd Ed. Imp. 8vo, 8s. cloth.

Oblique Bridges.

A PRACTICAL and THEORETICAL ESSAY on OBLIQUE BRIDGES, with 13 large Plates. By the late GEO. WATSON BUCK, M.I.C.E. Third Edition, revised by his Son, J. H. WATSON BUCK, M.I.C.E.; and with the addition of Description to Diagrams for Facilitating the Construction of Oblique Bridges, by W. H. BARLOW, M.I.C.E. Royal 8vo, 12s. cloth. [*Just published.*]

"The standard text book for all engineers regarding skew arches is Mr. Buck's treatise and it would be impossible to consult a better."—*Engineer.*

Gas and Gasworks.

THE CONSTRUCTION OF GASWORKS AND THE MANUFACTURE AND DISTRIBUTION OF COAL-GAS. Originally written by SAMUEL HUGHES, C.E. Sixth Edition. Re-written and much Enlarged, by WILLIAM RICHARDS, C.E. With 72 Woodcuts. 12mo, 5s. cloth boards. [*Just published.*]

Waterworks for Cities and Towns.

WATERWORKS for the SUPPLY of CITIES and TOWNS, with a Description of the Principal Geological Formations of England as influencing Supplies of Water. By S. HUGHES. 4s. 6d. cloth.

Locomotive-Engine Driving.

LOCOMOTIVE-ENGINE DRIVING; a Practical Manual for Engineers in charge of Locomotive Engines. By MICHAEL REYNOLDS, M.S.E., formerly Locomotive Inspector L. B. and S. C. R. Fourth Edition, greatly enlarged. Comprising A KEY TO THE LOCOMOTIVE ENGINE. With Illustrations and Portrait of Author. Crown 8vo, 4s. 6d. cloth.

"Mr. Reynolds deserves the title of the engine driver's friend."—*Railway News.*

"Mr. Reynolds has supplied a want, and has supplied it well. We can confidently recommend the book not only to the practical driver, but to every one who takes an interest in the performance of locomotive engines."—*Engineer.*

The Engineer, Fireman, and Engine-Boy.

THE MODEL LOCOMOTIVE ENGINEER, FIREMAN, AND ENGINE-BOY: comprising a Historical Notice of the Pioneer Locomotive Engines and their Inventors, with a project for the establishment of Certificates of Qualification in the Running Service of Railways. By MICHAEL REYNOLDS, Author of "Locomotive-Engine Driving." Crown 8vo, 4s. 6d. cloth.


"From the technical knowledge of the author it will appeal to the railway man of to-day more forcibly than anything written by Dr. Smiles."—*English Mechanic.*

Stationary Engine Driving.

STATIONARY ENGINE DRIVING. A Practical Manual for Engineers in Charge of Stationary Engines. By MICHAEL REYNOLDS ("The Engine-Driver's Friend"), Author of "Locomotive Engine Driving," &c. With Plates and Woodcuts, and Steel Portrait of James Watt. Crown 8vo, 4s. 6d. cloth. [*Just published.*]

Engine-Driving Life.

ENGINE-DRIVING LIFE; or Stirring Adventures and Incidents in the Lives of Locomotive Engine-Drivers. By MICHAEL REYNOLDS. Crown 8vo, 2s. cloth. [*Just published.*]



Fire Engineering.

FIRES, FIRE-ENGINES, AND FIRE BRIGADES. With a History of Fire-Engines, their Construction, Use, and Management; Remarks on Fire-Proof Buildings, and the Preservation of Life from Fire; Statistics of the Fire Appliances in English Towns; Foreign Fire Systems; Hints on Fire Brigades, &c., &c. By CHARLES F. T. YOUNG, C.E. With numerous Illustrations, handsomely printed, 544 pp., demy 8vo, 17. 4s. cloth.

"We can most heartily commend this book."—*Engineering*.

"Mr. Young's book on 'Fire Engines and Fire Brigades' contains a mass of information, which has been collected from a variety of sources. The subject is so intensely interesting and useful that it demands consideration."—*Building News*.

Trigonometrical Surveying.

AN OUTLINE OF THE METHOD OF CONDUCTING A TRIGONOMETRICAL SURVEY, for the Formation of Geographical and Topographical Maps and Plans, Military Reconnaissance, Levelling, &c., with the most useful Problems in Geodesy and Practical Astronomy. By LIEUT.-GEN. FROME, R.E., late Inspector-General of Fortifications. Fourth Edition, Enlarged, and partly Re-written. By CAPTAIN CHARLES WARREN, R.E. With 19 Plates and 115 Woodcuts, royal 8vo, 16s. cloth.

Tables of Curves.

TABLES OF TANGENTIAL ANGLES and MULTIPLES for setting out Curves from 5 to 200 Radius. By ALEXANDER BEAZELEY, M. Inst. C.E. Second Edition. Printed on 48 Cards, and sold in a cloth box, waistcoat-pocket size, 3s. 6d.

"Each table is printed on a small card, which, being placed on the theodolite, leaves the hands free to manipulate the instrument—no small advantage as regards the rapidity of work."—*Engineer*.

"Very handy; a man may know that all his day's work must fall on two of these cards, which he puts into his own card-case, and leaves the rest behind."—*Athenæum*.

Engineering Fieldwork.

THE PRACTICE OF ENGINEERING FIELDWORK, applied to Land and Hydraulic, Hydrographic, and Submarine Surveying and Levelling. Second Edition, revised, with considerable additions, and a Supplement on WATERWORKS, SEWERS, SEWAGE, and IRRIGATION. By W. DAVIS HASKOLL, C.E. Numerous folding Plates. In One Volume, demy 8vo, 17. 5s., cloth boards.

Large Tunnel Shafts.

THE CONSTRUCTION OF LARGE TUNNEL SHAFTS. A Practical and Theoretical Essay. By J. H. WATSON BUCK, M. Inst. C.E., Resident Engineer, London and North-Western Railway. Illustrated with Folding Plates. Royal 8vo, 12s. cloth.

[Just published.]

"Many of the methods given are of extreme practical value to the mason, and the observations on the form of arch, the rules for ordering the stone, and the construction of the templates, will be found of considerable use. We commend the book to the engineering profession, and to all who have to build similar shafts."—*Building News*.

"Will be regarded by civil engineers as of the utmost value, and calculated to save much time and obviate many mistakes."—*Colliery Guardian*.

Survey Practice.

AID TO SURVEY PRACTICE: for Reference in Surveying, Levelling, Setting-out and in Route Surveys of Travellers by Land and Sea. With Tables, Illustrations, and Records. By **LOWIS D'A. JACKSON, A.M.I.C.E.** Author of "Hydraulic Manual and Statistics," "Canal and Culvert Tables," &c. Large crown, 8vo, 12s. 6d., cloth. [*Just published.*]

"Mr. Jackson has produced a valuable *vade-mecum* for the surveyor. We can recommend this book as containing an admirable supplement to the teaching of the accomplished surveyor."—*Athenæum*.

"A general text book was wanted, and we are able to speak with confidence of Mr. Jackson's treatise. . . . We cannot recommend to the student who knows something of the mathematical principles of the subject a better course than to fortify his practice in the field under a competent surveyor with a study of Mr. Jackson's useful manual. The field records illustrate every kind of survey, and will be found an essential aid to the student."—*Building News*.

"The author brings to his work a fortunate union of theory and practical experience which, aided by a clear and lucid style of writing, renders the book both a very useful one and very agreeable to read."—*Builder*.

Sanitary Work.

SANITARY WORK IN THE SMALLER TOWNS AND IN VILLAGES. Comprising:—1. Some of the more Common Forms of Nuisance and their Remedies; 2. Drainage; 3. Water Supply. By **CHAS. SLAGG, Assoc. Inst. C.E.** Crown 8vo, 3s. cloth.

"A very useful book, and may be safely recommended. The author has had practical experience in the works of which he treats."—*Builder*.

Locomotives.

LOCOMOTIVE ENGINES, A Rudimentary Treatise on. Comprising an Historical Sketch and Description of the Locomotive Engine. By **G. D. DEMPSEY, C.E.** With large additions treating of the MODERN LOCOMOTIVE, by **D. KINNEAR CLARK, C.E., M.I.C.E.**, Author of "Tramways, their Construction and Working," &c., &c. With numerous Illustrations. 12mo. 3s. 6d. cloth boards.

"The student cannot fail to profit largely by adopting this as his preliminary text-book."—*Iron and Coal Trades Review*.

"Seems a model of what an elementary technical book should be."—*Academy*.

Fuels and their Economy.

FUEL, its Combustion and Economy; consisting of an Abridgment of "A Treatise on the Combustion of Coal and the Prevention of Smoke." By **C. W. WILLIAMS, A.I.C.E.** With extensive additions on Recent Practice in the Combustion and Economy of Fuel—Coal, Coke, Wood, Peat, Petroleum, &c.; by **D. KINNEAR CLARK, C.E., M.I.C.E.** Second Edition, revised. With numerous Illustrations. 12mo. 4s. cloth boards. [*Just published.*]

"Students should buy the book and read it, as one of the most complete and satisfactory treatises on the combustion and economy of fuel to be had."—*Engineer*.

Roads and Streets.

THE CONSTRUCTION OF ROADS AND STREETS. In Two Parts. I. The Art of Constructing Common Roads. By **HENRY LAW, C.E.** Revised and Condensed by **D. KINNEAR CLARK, C.E.**—II. Recent Practice in the Construction of Roads and Streets: including Pavements of Stone, Wood, and Asphalte. By **D. KINNEAR CLARK, C.E., M.I.C.E.** Second Edition, revised. 12mo, 5s. cloth.

"A book which every borough surveyor and engineer must possess, and which will be of considerable service to architects, builders, and property owners generally."—*Building News*.

Sewing Machine (The).

SEWING MACHINERY; being a Practical Manual of the Sewing Machine, comprising its History and Details of its Construction, with full Technical Directions for the Adjusting of Sewing Machines. By J. W. URQUHART, Author of "Electro Plating: a Practical Manual;" "Electric Light: its Production and Use." With Numerous Illustrations. 12mo, 2s. 6d. cloth boards. [Just published.

Field-Book for Engineers.

THE ENGINEER'S, MINING SURVEYOR'S, and CONTRACTOR'S FIELD-BOOK. By W. DAVIS HASKOLL, C.E. Consisting of a Series of Tables, with Rules, Explanations of Systems, and Use of Theodolite for Traverse Surveying and Plotting the Work with minute accuracy by means of Straight Edge and Set Square only; Levelling with the Theodolite, Casting out and Reducing Levels to Datum, and Plotting Sections in the ordinary manner; Setting out Curves with the Theodolite by Tangential Angles and Multiples with Right and Left-hand Readings of the Instrument; Setting out Curves without Theodolite on the System of Tangential Angles by Sets of Tangents and Offsets; and Earthwork Tables to 80 feet deep, calculated for every 6 inches in depth. With numerous woodcuts. 4th Edition, enlarged. Cr. 8vo. 12s. cloth.

"The book is very handy, and the author might have added that the separate tables of sines and tangents to every minute will make it useful for many other purposes, the genuine traverse tables existing all the same."—*Athenæum*.

"Cannot fail, from its portability and utility, to be extensively patronised by the engineering profession."—*Mining Journal*.

Earthwork, Measurement and Calculation of.

A MANUAL on EARTHWORK. By ALEX. J. S. GRAHAM, C.E., Resident Engineer, Forest of Dean Central Railway. With numerous Diagrams. 18mo, 2s. 6d. cloth.

"As a really handy book for reference, we know of no work equal to it; and the railway engineers and others employed in the measurement and calculation of earthwork will find a great amount of practical information very admirably arranged, and available for general or rough estimates, as well as for the more exact calculations required in the engineers' contractor's offices."—*Artizan*.

Drawing for Engineers, &c.

THE WORKMAN'S MANUAL OF ENGINEERING DRAWING. By JOHN MAXTON, Instructor in Engineering Drawing, Royal Naval College, Greenwich, formerly of R. S. N. A., South Kensington. Fourth Edition, carefully revised. With upwards of 300 Plates and Diagrams. 12mo, cloth, strongly bound, 4s.

"A copy of it should be kept for reference in every drawing office."—*Engineering*.

"Indispensable for teachers of engineering drawing."—*Mechanics' Magazine*.

Weale's Dictionary of Terms.

A DICTIONARY of TERMS used in ARCHITECTURE, BUILDING, ENGINEERING, MINING, METALLURGY, ARCHÆOLOGY, the FINE ARTS, &c. By JOHN WEALE. Fifth Edition, revised by ROBERT HUNT, F.R.S., Keeper of Mining Records, Editor of "Ure's Dictionary of Arts." 12mo, 6s. cl. bds.

"The best small technological dictionary in the language."—*Architect*.

"The absolute accuracy of a work of this character can only be judged of after extensive consultation, and from our examination it appears very correct and very complete."—*Mining Journal*.

MINING, METALLURGY, ETC.

Metalliferous Minerals and Mining.

A TREATISE ON METALLIFEROUS MINERALS AND MINING. By D.C. DAVIES, F.G.S., author of "A Treatise on Slate and Slate Quarrying." With numerous wood engravings. Second Edition, revised. Cr. 8vo. 12s. 6d. cloth. [*Just published.*]

"Without question, the most exhaustive and the most practically useful work we have seen; the amount of information given is enormous, and it is given concisely and intelligibly."—*Mining Journal*.

"The volume is one which no student of mineralogy should be without."—*Colliery Guardian*.

"The author has gathered together from all available sources a vast amount of really useful information. As a history of the present state of mining throughout the world this book has a real value, and it supplies an actual want, for no such information has hitherto been brought together within such limited space."—*Athenæum*.

Slate and Slate Quarrying.

A TREATISE ON SLATE AND SLATE QUARRYING, Scientific, Practical, and Commercial. By D. C. DAVIES, F.G.S., Mining Engineer, &c. With numerous Illustrations and Folding Plates. Second Edition, carefully revised. 12mo, 3s. 6d. cloth boards.

"Mr. Davies has written a useful and practical hand-book on an important industry, with all the conditions and details of which he appears familiar."—*Engineering*.

"The work is illustrated by actual practice, and is unusually thorough and lucid. Mr. Davies has completed his work with industry and skill."—*Builder*.

Metallurgy of Iron.

A TREATISE ON THE METALLURGY OF IRON: containing Outlines of the History of Iron Manufacture, Methods of Assay, and Analyses of Iron Ores, Processes of Manufacture of Iron and Steel, &c. By H. BAUERMAN, F.G.S., Associate of the Royal School of Mines. With numerous Illustrations. Fourth Edition, revised and much enlarged. 12mo, cloth boards, 5s.

"Has the merit of brevity and conciseness, as to less important points, while all material matters are very fully and thoroughly entered into."—*Standard*.

Manual of Mining Tools.

MINING TOOLS. For the use of Mine Managers, Agents, Mining Students, &c. By WILLIAM MORGANS, Lecturer on Practical Mining at the Bristol School of Mines. Volume of Text. 12mo, 3s. With an Atlas of Plates, containing 235 Illustrations. 4to, 6s. Together, 9s. cloth boards.

"Students in the Science of Mining, and Overmen, Captains, Managers, and Viewers may gain practical knowledge and useful hints by the study of Mr. Morgans' Manual."—*Colliery Guardian*.

Mining, Surveying and Valuing.

THE MINERAL SURVEYOR AND VALUER'S COMPLETE GUIDE, comprising a Treatise on Improved Mining Surveying, with new Traverse Tables; and Descriptions of Improved Instruments; also an Exposition of the Correct Principles of Laying out and Valuing Home and Foreign Iron and Coal Mineral Properties. By WILLIAM LINTERN, Mining and Civil Engineer. With four Plates of Diagrams, Plans, &c., 12mo, 4s. cloth.

"Contains much valuable information given in a small compass, and which, as far as we have tested it, is thoroughly trustworthy."—*Iron and Coal Trades Review*.

* * The above, bound with THOMAN'S TABLES. (See page 20.) Price 7s. 6d. cloth.

Coal and Coal Mining.

COAL AND COAL MINING: a Rudimentary Treatise on. By WARINGTON W. SMYTH, M.A., F.R.S., &c., Chief Inspector of the Mines of the Crown. Fifth edition, revised and corrected. 12mo, with numerous Illustrations, 4s. cloth boards.

"Every portion of the volume appears to have been prepared with much care, and as an outline is given of every known coal-field in this and other countries, as well as of the two principal methods of working, the book will doubtless interest a very large number of readers."—*Mining Journal*.

Underground Pumping Machinery.

MINE DRAINAGE; being a Complete and Practical Treatise on Direct-Acting Underground Steam Pumping Machinery, with a Description of a large number of the best known Engines, their General Utility and the Special Sphere of their Action, the Mode of their Application, and their merits compared with other forms of Pumping Machinery. By STEPHEN MICHELL, Joint-Author of "The Cornish System of Mine Drainage." 8vo. [Nearly ready.

NAVAL ARCHITECTURE, NAVIGATION, ETC.

Pocket Book for Naval Architects & Shipbuilders.

THE NAVAL ARCHITECT'S AND SHIPBUILDER'S POCKET BOOK OF FORMULÆ, RULES, AND TABLES AND MARINE ENGINEER'S AND SURVEYOR'S HANDY BOOK OF REFERENCE. By CLEMENT MACKROW, Naval Draughtsman, Associate of the Institution of Naval Architects. With numerous Diagrams, &c. Fcap., strongly bound in leather, with elastic strap for pocket, 12s. 6d.

"Should be used by all who are engaged in the construction or design of vessels."—*Engineer*.

"There is scarcely a subject on which a naval architect or shipbuilder can require to refresh his memory which will not be found within the covers of Mr. Mackrow's book."—*English Mechanic*.

"Mr. Mackrow has compressed an extraordinary amount of information into this useful volume."—*Athenæum*.

Grantham's Iron Ship-Building.

ON IRON SHIP-BUILDING; with Practical Examples and Details. Fifth Edition. Imp. 4to, boards, enlarged from 24 to 40 Plates (21 quite new), including the latest Examples. Together with separate Text, also considerably enlarged, 12mo, cloth limp. By JOHN GRANTHAM, M. Inst. C.E., &c. 2l. 2s. complete.

"Mr. Grantham's work is of great interest. It will, we are confident, command an extensive circulation among shipbuilders in general. By order of the Board of Admiralty, the work will form the text-book on which the examination in iron ship-building of candidates for promotion in the dockyards will be mainly based."—*Engineering*.

Pocket-Book for Marine Engineers.

A POCKET-BOOK OF USEFUL TABLES AND FORMULÆ FOR MARINE ENGINEERS. By FRANK PROCTOR, A.I.N.A. Second Edition, revised and enlarged. Royal 32mo, leather, gilt edges, with strap, 4s.

"A most useful companion to all marine engineers."—*United Service Gazette*.

"Scarcely anything required by a naval engineer appears to have been forgotten."—*Iron*.

Light-Houses.

EUROPEAN LIGHT-HOUSE SYSTEMS; being a Report of a Tour of Inspection made in 1873. By Major GEORGE H. ELLIOT, Corps of Engineers, U.S.A. Illustrated by 51 Engravings and 31 Woodcuts in the Text. 8vo, 21s. cloth.

Surveying (Land and Marine).

LAND AND MARINE SURVEYING, in Reference to the Preparation of Plans for Roads and Railways, Canals, Rivers, Towns' Water Supplies, Docks and Harbours; with Description and Use of Surveying Instruments. By W. DAVIS HASKOLL, C.E. With 14 folding Plates, and numerous Woodcuts. 8vo, 12s. 6d. cloth.

"A most useful and well arranged book for the aid of a student."—*Builder*.

"Of the utmost practical utility, and may be safely recommended to all students who aspire to become clean and expert surveyors."—*Mining Journal*.

Storms.

STORMS: their Nature, Classification, and Laws, with the Means of Predicting them by their Embodiments, the Clouds. By WILLIAM BLASIUS. Crown 8vo, 10s. 6d. cloth boards.

Rudimentary Navigation.

THE SAILOR'S SEA-BOOK: a Rudimentary Treatise on Navigation. By JAMES GREENWOOD, B.A. New and enlarged edition. By W. H. ROSSER. 12mo, 3s. cloth boards.

Mathematical and Nautical Tables.

MATHEMATICAL TABLES, for Trigonometrical, Astronomical, and Nautical Calculations; to which is prefixed a Treatise on Logarithms. By HENRY LAW, C.E. Together with a Series of Tables for Navigation and Nautical Astronomy. By J. R. YOUNG, formerly Professor of Mathematics in Belfast College. New Edition. 12mo, 4s. cloth boards.

Navigation (Practical), with Tables.

PRACTICAL NAVIGATION: consisting of the Sailor's Sea-Book, by JAMES GREENWOOD and W. H. ROSSER; together with the requisite Mathematical and Nautical Tables for the Working of the Problems. By HENRY LAW, C.E., and Professor J. R. YOUNG. Illustrated with numerous Wood Engravings and Coloured Plates. 12mo, 7s. strongly half bound in leather.

WEALE'S RUDIMENTARY SERIES.

The following books in Naval Architecture, etc., are published in the above series.

- MASTING, MAST-MAKING, AND RIGGING OF SHIPS. By ROBERT KIPPING, N.A. Fourteenth Edition. 12mo, 2s. 6d. cloth.
- SAILS AND SAIL-MAKING. Tenth Edition, enlarged. By ROBERT KIPPING, N.A. Illustrated. 12mo, 3s. cloth boards.
- NAVAL ARCHITECTURE. By JAMES PEAKE. Fourth Edition, with Plates and Diagrams. 12mo, 4s. cloth boards.
- MARINE ENGINES, AND STEAM VESSELS. By ROBERT MURRAY, C.E. Seventh Edition. 12mo, 3s. 6d. cloth boards.

ARCHITECTURE, BUILDING, ETC.

Construction.

THE SCIENCE of BUILDING: An Elementary Treatise on the Principles of Construction. By E. WYNDHAM TARN, M.A., Architect. With 47 Wood Engravings. Demy 8vo. 8s. 6d. cloth.

"A very valuable book, which we strongly recommend to all students."—*Builder*.
 "No architectural student should be without this hand-book."—*Architect*.

Villa Architecture.

A HANDY BOOK of VILLA ARCHITECTURE; being a Series of Designs for Villa Residences in various Styles. With Detailed Specifications and Estimates. By C. WICKES, Architect, Author of "The Spires and Towers of the Mediæval Churches of England," &c. 31 Plates, 4to, half morocco, gilt edges, 1l. 1s.

* * Also an Enlarged edition of the above. 61 Plates, with Detailed Specifications, Estimates, &c. 2l. 2s. half morocco.

"The whole of the designs bear evidence of their being the work of an artistic architect, and they will prove very valuable and suggestive."—*Building News*.

Useful Text-Book for Architects.

THE ARCHITECT'S GUIDE: Being a Text-book of Useful Information for Architects, Engineers, Surveyors, Contractors, Clerks of Works, &c., &c. By FREDERICK ROGERS, Architect, Author of "Specifications for Practical Architecture," &c. With numerous Illustrations. Crown 8vo, 6s. cloth.

"As a text-book of useful information for architects, engineers, surveyors, &c., it would be hard to find a handier or more complete little volume."—*Standard*.

Taylor and Cresy's Rome.

THE ARCHITECTURAL ANTIQUITIES OF ROME. By the late G. L. TAYLOR, Esq., F.S.A., and EDWARD CRESY, Esq. New Edition, thoroughly revised, and supplemented under the editorial care of the Rev. ALEXANDER TAYLOR, M.A. (son of the late G. L. Taylor, Esq.), Chaplain of Gray's Inn. This is the only book which gives on a large scale, and with the precision of architectural measurement, the principal Monuments of Ancient Rome in plan, elevation, and detail. Large folio, with 130 Plates, half-bound, 3l. 3s.

* * Originally published in two volumes, folio, at 18l. 18s.

Vitruvius' Architecture.

THE ARCHITECTURE OF MARCUS VITRUVIUS POLLIO. Translated by JOSEPH GWILT, F.S.A., F.R.A.S. Numerous Plates. 12mo, cloth limp. 5s.

The Young Architect's Book.

HINTS TO YOUNG ARCHITECTS. By GEORGE WIGHTWICK, Architect. New Edition, revised and enlarged. By G. HUSKISSON GUILLAUME, Architect. 12mo, cloth boards, 4s.

"Will be found an acquisition to pupils, and a copy ought to be considered as necessary a purchase as a box of instruments."—*Architect*.

"A large amount of information, which young architects will do well to acquire, if they wish to succeed in the everyday work of their profession."—*English Mechanic*.

Drawing for Builders and Students.

PRACTICAL RULES ON DRAWING for the OPERATIVE BUILDER and YOUNG STUDENT in ARCHITECTURE. By GEORGE PYNE. With 14 Plates, 4to, 7s. 6d. boards.

The House-Owner's Estimator.

THE HOUSE-OWNER'S ESTIMATOR; or, What will it Cost to Build, Alter, or Repair? A Price-Book adapted to the Use of Unprofessional People as well as for the Architectural Surveyor and Builder. By the late JAMES D. SIMON, A.R.I.B.A. Edited and Revised by FRANCIS T. W. MILLER, Surveyor. With numerous Illustrations. Second Edition, with the prices carefully corrected to present time. Crown 8vo, cloth, 3s. 6d.

"In two years it will repay its cost a hundred times over."—*Field*.

"A very handy book for those who want to know what a house will cost to build, alter, or repair."—*English Mechanic*.

Boiler and Factory Chimneys.

BOILER AND FACTORY CHIMNEYS; their Draught-power and Stability, with a chapter on Lightning Conductors. By ROBERT WILSON, C.E., Author of "Treatise on Steam Boilers," &c., &c. Crown 8vo, 3s. 6d. cloth.

Civil and Ecclesiastical Building.

A BOOK ON BUILDING, CIVIL AND ECCLESIASTICAL, Including CHURCH RESTORATION. By Sir EDMUND BECKETT, Bart., LL.D., Q.C., F.R.A.S., Chancellor and Vicar-General of York. Author of "Clocks and Watches and Bells," &c. Second Edition, 12mo, 5s. cloth boards.

"A book which is always amusing and nearly always instructive. Sir E. Beckett will be read for the raciness of his style. We are able very cordially to recommend all persons to read it for themselves. The style throughout is in the highest degree condensed and epigrammatic."—*Times*.

"We commend the book to the thoughtful consideration of all who are interested in the building art."—*Builder*.

Architecture, Ancient and Modern.

RUDIMENTARY ARCHITECTURE, Ancient and Modern. Consisting of VITRUVIUS, translated by JOSEPH GWILT, F.S.A., &c., with 23 fine copper plates; GRECIAN Architecture, by the EARL of ABERDEEN; the ORDERS of Architecture, by W. H. LEEDS, Esq.; The STYLES of Architecture of Various Countries, by T. TALBOT BURY; The PRINCIPLES of DESIGN in Architecture, by E. L. GARBETT. In one volume, half-bound (pp. 1,100), copiously illustrated, 12s.

* * Sold separately, in two vols., as follows—

ANCIENT ARCHITECTURE. Containing Gwilt's Vitruvius and Aberdeen's Grecian Architecture. Price 6s. half-bound.

N.B.—*This is the only edition of VITRUVIUS procurable at a moderate price.*

MODERN ARCHITECTURE. Containing the Orders, by Leeds; The Styles, by Bury; and Design, by Garbett. 6s. half-bound.

House Painting.

HOUSE PAINTING, GRAINING, MARBLING, AND SIGN WRITING: a Practical Manual of. With 9 Coloured Plates of Woods and Marbles, and nearly 150 Wood Engravings. By ELLIS A. DAVIDSON, Author of "Building Construction," &c. Third Edition, carefully revised. 12mo, 6s. cloth boards.

"Contains a mass of information of use to the amateur and of value to the practical man."—*English Mechanic*.

Plumbing.

PLUMBING ; a Text-book to the Practice of the Art or Craft of the Plumber. With chapters upon House-drainage, embodying the latest Improvements. By W. P. BUCHAN, Sanitary Engineer. Second Edition, enlarged, with 300 illustrations, 12mo. 4s. cloth.

"The chapters on house-drainage may be usefully consulted, not only by plumbers, but also by engineers and all engaged or interested in house-building."—*Iron.*

Handbook of Specifications.

THE HANDBOOK OF SPECIFICATIONS ; or, Practical Guide to the Architect, Engineer, Surveyor, and Builder, in drawing up Specifications and Contracts for Works and Constructions. Illustrated by Precedents of Buildings actually executed by eminent Architects and Engineers. By Professor THOMAS L. DONALDSON, M.I.B.A. New Edition, in One large volume, 8vo, with upwards of 1000 pages of text, and 33 Plates, cloth, 1l. 11s. 6d.

"In this work forty-four specifications of executed works are given. . . . Donaldson's Handbook of Specifications must be bought by all architects."—*Builder.*

Specifications for Practical Architecture.

SPECIFICATIONS FOR PRACTICAL ARCHITECTURE: A Guide to the Architect, Engineer, Surveyor, and Builder ; with an Essay on the Structure and Science of Modern Buildings. By FREDERICK ROGERS, Architect. 8vo, 15s. cloth.

* * A volume of specifications of a practical character being greatly required, and the old standard work of Alfred Bartholomew being out of print, the author, on the basis of that work, has produced the above.—*Extract from Preface.*

Designing, Measuring, and Valuing.

THE STUDENT'S GUIDE to the PRACTICE of MEASURING and VALUING ARTIFICERS' WORKS ; containing Directions for taking Dimensions, Abstracting the same, and bringing the Quantities into Bill, with Tables of Constants, and copious Memoranda for the Valuation of Labour and Materials in the respective Trades of Bricklayer and Slater, Carpenter and Joiner, Painter and Glazier, Paperhanger, &c. With 43 Plates and Woodcuts. Originally edited by EDWARD DOBSON, Architect. New Edition, re-written, with Additions on Mensuration and Construction, and useful Tables for facilitating Calculations and Measurements. By E. WYNDHAM TARN, M.A., 8vo, 10s. 6d. cloth.

"Well fulfils the promise of its title-page. Mr. Tarn's additions and revisions have much increased the usefulness of the work."—*Engineering.*

Beaton's Pocket Estimator.

THE POCKET ESTIMATOR FOR THE BUILDING TRADES, being an easy method of estimating the various parts of a Building collectively, more especially applied to Carpenters' and Joiners' work, priced according to the present value of material and labour. By A. C. BEATON, Author of "Quantities and Measurements." Second Edition. Waistcoat-pocket size. 1s. 6d.

Beaton's Builders' and Surveyors' Technical Guide.

THE POCKET TECHNICAL GUIDE AND MEASURER FOR BUILDERS AND SURVEYORS: containing a Complete Explanation of the Terms used in Building Construction, Memoranda for Reference, Technical Directions for Measuring Work in all the Building Trades, &c. By A. C. BEATON. Second Edit. Waistcoat-pocket size. 1s. 6d.

Builder's and Contractor's Price Book.

LOCKWOOD & CO.'S BUILDER'S AND CONTRACTOR'S PRICE BOOK, containing the latest prices of all kinds of Builders' Materials and Labour, and of all Trades connected with Building, &c., &c. The whole revised and edited by F. T. W. MILLER, Architect and Surveyor. Fcap. half-bound, 4s.

CARPENTRY, TIMBER, ETC.

Tredgold's Carpentry, new and cheaper Edition.

THE ELEMENTARY PRINCIPLES OF CARPENTRY : a Treatise on the Pressure and Equilibrium of Timber Framing, the Resistance of Timber, and the Construction of Floors, Arches, Bridges, Roofs, Uniting Iron and Stone with Timber, &c. To which is added an Essay on the Nature and Properties of Timber, &c., with Descriptions of the Kinds of Wood used in Building ; also numerous Tables of the Scantlings of Timber for different purposes, the Specific Gravities of Materials, &c. By THOMAS TREDGOLD, C.E. Edited by PETER BARLOW, F.R.S. Fifth Edition, corrected and enlarged. With 64 Plates (11 of which now first appear in this edition), Portrait of the Author, and several Woodcuts. In 1 vol., 4to, published at 2l. 2s., reduced to 1l. 5s. cloth.

"Ought to be in every architect's and every builder's library, and those who do not already possess it ought to avail themselves of the new issue."—*Builder*.

"A work whose monumental excellence must commend it wherever skilful carpentry is concerned. The Author's principles are rather confirmed than impaired by time. The additional plates are of great intrinsic value."—*Building News*.

Grandy's Timber Tables.

THE TIMBER IMPORTER'S, TIMBER MERCHANT'S, and BUILDER'S STANDARD GUIDE. By RICHARD E. GRANDY. Comprising :—An Analysis of Deal Standards, Home and Foreign, with comparative Values and Tabular Arrangements for Fixing Nett Landed Cost on Baltic and North American Deals, including all intermediate Expenses, Freight, Insurance, &c., &c. ; together with Copious Information for the Retailer and Builder. 2nd Edition. Carefully revised and corrected. 12mo, 3s. 6d. cloth.

"Everything it pretends to be : built up gradually, it leads one from a forest to a treenail, and throws in, as a makeweight, a host of material concerning bricks, columns, cisterns, &c.—all that the class to whom it appeals requires."—*English Mechanic*.

Timber Freight Book.

THE TIMBER IMPORTERS' AND SHIPOWNERS' FREIGHT BOOK : Being a Comprehensive Series of Tables for the Use of Timber Importers, Captains of Ships, Shipbrokers, Builders, and all Dealers in Wood whatsoever. By WILLIAM RICHARDSON, Timber Broker. Crown 8vo, 6s. cloth.

Tables for Packing-Case Makers.

PACKING-CASE TABLES ; showing the number of Superficial Feet in Boxes or Packing-Cases, from six inches square and upwards. Compiled by WILLIAM RICHARDSON, Accountant. Second Edition. Oblong 4to, 3s. 6d. cloth.

"Will save much labour and calculation to packing-case makers and those who use packing-cases."—*Grocer*.

"Invaluable labour-saving tables."—*Ironmonger*.

Horton's Measurer.

THE COMPLETE MEASURER; setting forth the Measurement of Boards, Glass, &c.; Unequal-sided, Square-sided, Octagonal-sided, Round Timber and Stone, and Standing Timber. With just allowances for the bark in the respective species of trees, and proper deductions for the waste in hewing the trees, &c.; also a Table showing the solidity of hewn or eight-sided timber, or of any octagonal-sided column. By RICHARD HORTON. Fourth edition, with considerable and valuable additions, 12mo, strongly bound in leather, 5s.

Horton's Underwood and Woodland Tables.

TABLES FOR PLANTING AND VALUING UNDERWOOD AND WOODLAND; also Lineal, Superficial, Cubical, and Decimal Tables, &c. By R. HORTON. 12mo, 2s. leather.

Nicholson's Carpenter's Guide.

THE CARPENTER'S NEW GUIDE; or, BOOK of LINES for CARPENTERS: comprising all the Elementary Principles essential for acquiring a knowledge of Carpentry. Founded on the late PETER NICHOLSON'S standard work. A new Edition, revised by ARTHUR ASHPITEL, F.S.A., together with Practical Rules on Drawing, by GEORGE PYNE. With 74 Plates, 4to, 1l. 1s. cloth.

Dowsing's Timber Merchant's Companion.

THE TIMBER MERCHANT'S AND BUILDER'S COMPANION; containing New and Copious Tables of the Reduced Weight and Measurement of Deals and Battens, of all sizes, from One to a Thousand Pieces, also the relative Price that each size bears per Lineal Foot to any given Price per Petersburg Standard Hundred, &c., &c. Also a variety of other valuable information. By WILLIAM DOWSING, Timber Merchant. Third Edition, Revised. Crown 8vo, 3s. cloth.

"Everything is as concise and clear as it can possibly be made. There can be no doubt that every timber merchant and builder ought to possess it."—*Hull Advertiser*.

Practical Timber Merchant.

THE PRACTICAL TIMBER MERCHANT, being a Guide for the use of Building Contractors, Surveyors, Builders, &c., comprising useful Tables for all purposes connected with the Timber Trade, Essay on the Strength of Timber, Remarks on the Growth of Timber, &c. By W. RICHARDSON. Fcap. 8vo, 3s. 6d. cl.

Woodworking Machinery.

WOODWORKING MACHINERY; its Rise, Progress, and Construction. With Hints on the Management of Saw Mills and the Economical Conversion of Timber. Illustrated with Examples of Recent Designs by leading English, French, and American Engineers. By M. POWIS BALE, M.I.M.E. Large crown 8vo, 12s. 6d. cloth.

[Just published.]

"Mr. Bale is evidently an expert on the subject, and he has collected so much information that his book is all-sufficient for builders and others engaged in the conversion of timber."—*Architect*.

"The most comprehensive compendium of wood-working machinery we have seen. The author is a thorough master of his subject."—*Building News*.

"It should be in the office of every wood-working factory."—*English Mechanic*.

MECHANICS, ETC.

Mechanic's Workshop Companion.

THE OPERATIVE MECHANIC'S WORKSHOP COMPANION, and THE SCIENTIFIC GENTLEMAN'S PRACTICAL ASSISTANT. By W. TEMPLETON. 12th Edit., with Mechanical Tables for Operative Smiths, Millwrights, Engineers, &c.; and an Extensive Table of Powers and Roots, 12mo, 5s. bound.

"As a text-book in which mechanical and commercial demands are judiciously met, TEMPLETON'S COMPANION stands unrivalled."—*Mechanics' Magazine*.

"Admirably adapted to the wants of a very large class. It has met with great success in the engineering workshop, as we can testify; and there are a great many men who, in a great measure, owe their rise in life to this little work."—*Building News*.

Engineer's and Machinist's Assistant.

THE ENGINEER'S, MILLWRIGHT'S, and MACHINIST'S PRACTICAL ASSISTANT; comprising a Collection of Useful Tables, Rules, and Data. Compiled and Arranged, with Original Matter, by WM. TEMPLETON. 6th Edition. 18mo, 2s. 6d. cloth.

"A more suitable present to an apprentice to any of the mechanical trades could not possibly be made."—*Building News*.

Superficial Measurement.

THE TRADESMAN'S GUIDE TO SUPERFICIAL MEASUREMENT. Tables calculated from 1 to 200 inches in length, by 1 to 108 inches in breadth. For the use of Architects, Engineers, Timber Merchants, Builders, &c. By J. HAWKINGS. Fcp. 3s. 6d. cl.

The High-Pressure Steam Engine.

THE HIGH-PRESSURE STEAM ENGINE; an Exposition of its Comparative Merits, and an Essay towards an Improved System of Construction, adapted especially to secure Safety and Economy. By Dr. ERNST ALBAN, Practical Machine Maker, Plau, Mecklenberg. Translated from the German, with Notes, by Dr. POLE, F.R.S., M.I.C.E., &c. With 28 Plates, 8vo, 16s. 6d. cl.

Steam Boilers.

A TREATISE ON STEAM BOILERS: their Strength, Construction, and Economical Working. By R. WILSON, C.E. Fifth Edition. 12mo, 6s. cloth.

"The best work on boilers which has come under our notice."—*Engineering*.

"The best treatise that has ever been published on steam boilers."—*Engineer*.

Power in Motion.

POWER IN MOTION: Horse Power, Toothed Wheel Gearing, Long and Short Driving Bands, Angular Forces, &c. By JAMES ARMOUR, C.E. With 73 Diagrams. 12mo, 3s., cloth.

Mechanics.

THE HANDBOOK OF MECHANICS. By DIONYSIUS LARDNER, D.C.L., formerly Professor of Natural Philosophy and Astronomy in University College, London. New Edition, Edited and considerably Enlarged, by BENJAMIN LOEWY, F.R.A.S., &c., &c. With 378 Illustrations, post 8vo, 6s. cloth.

"The explanations throughout are studiously popular, and care has been taken to show the application of the various branches of physics to the industrial arts, and to the practical business of life."—*Mining Journal*.

MATHEMATICS, TABLES, ETC.

Gregory's Practical Mathematics.

MATHEMATICS for PRACTICAL MEN ; being a Common-place Book of Pure and Mixed Mathematics. Designed chiefly for the Use of Civil Engineers, Architects, and Surveyors. Part I. PURE MATHEMATICS—comprising Arithmetic, Algebra, Geometry, Mensuration, Trigonometry, Conic Sections, Properties of Curves. Part II. MIXED MATHEMATICS—comprising Mechanics in general, Statics, Dynamics, Hydrostatics, Hydrodynamics, Pneumatics, Mechanical Agents, Strength of Materials. With an Appendix of copious Logarithmic and other Tables. By OLINTHUS GREGORY, LL.D., F.R.A.S. Enlarged by HENRY LAW, C.E. 4th Edition, carefully revised and corrected by J. R. YOUNG, formerly Professor of Mathematics, Belfast Coll. With 13 Plates. 8vo, 1*l.* 1*s.* cloth.

"The engineer or architect will here find ready to his hand, rules for solving nearly every mathematical difficulty that may arise in his practice. The rules are in all cases explained by means of examples clearly worked out."—*Builder*.

"One of the most serviceable books for practical mechanics. . . ."—*Building News*.

The Metric System.

A SERIES OF METRIC TABLES, in which the British Standard Measures and Weights are compared with those of the Metric System at present in use on the Continent. By C. H. DOWLING, C.E. 2nd Edit., revised and enlarged. 8vo, 10*s.* 6*d.* cl.

"Their accuracy has been certified by Prof. Airy, Astronomer-Royal."—*Builder*.

Inwood's Tables, greatly enlarged and improved.

TABLES FOR THE PURCHASING of ESTATES, Freehold, Copyhold, or Leasehold ; Annuities, Advowsons, &c., and for the Renewing of Leases held under Cathedral Churches, Colleges, or other corporate bodies ; for Terms of Years certain, and for Lives ; also for Valuing Reversionary Estates, Deferred Annuities, Next Presentations, &c., together with Smart's Five Tables of Compound Interest, and an Extension of the same to Lower and Intermediate Rates. By WILLIAM INWOOD, Architect. The 21st edition, with considerable additions, and new and valuable Tables of Logarithms for the more Difficult Computations of the Interest of Money, Discount, Annuities, &c., by M. FÉDOR THOMAN, of the Société Crédit Mobilier of Paris. 12mo, 8*s.* cloth.

"Those interested in the purchase and sale of estates, and in the adjustment of compensation cases, as well as in transactions in annuities, life insurances, &c., will find the present edition of eminent service."—*Engineering*.

Geometry for the Architect, Engineer, &c.

PRACTICAL GEOMETRY, for the Architect, Engineer, and Mechanic ; giving Rules for the Delineation and Application of various Geometrical Lines, Figures and Curves. By E. W. TARN, M.A., Architect, Author of "The Science of Building," &c. With 164 Illustrations. Demy 8vo. 12*s.* 6*d.* cloth.

Mathematical Instruments.

MATHEMATICAL INSTRUMENTS: Their Construction, Adjustment, Testing, and Use ; comprising Drawing, Measuring, Optical, Surveying, and Astronomical Instruments. By J. F. HEATHER, M.A. Enlarged Edition, for the most part entirely re-written. Numerous Woodcuts. 12mo, 5*s.* cloth.

Compound Interest and Annuities.

THEORY of COMPOUND INTEREST and ANNUITIES; with Tables of Logarithms for the more Difficult Computations of Interest, Discount, Annuities, &c., in all their Applications and Uses for Mercantile and State Purposes. By FÉDOR THOMAN, of the Société Crédit Mobilier, Paris. 3rd Edit., 12mo, 4s. 6d. cl.

"A very powerful work, and the Author has a very remarkable command of his subject."—*Professor A. de Morgan.*

Iron and Metal Trades' Calculator.

THE IRON AND METAL TRADES' COMPANION: Being a Calculator containing a Series of Tables upon a new and comprehensive plan for expeditiously ascertaining the value of any goods bought or sold by weight, from 1s. per cwt. to 112s. per cwt., and from one farthing per lb. to 1s. per lb. Each Table extends from one lb. to 100 tons. By T. DOWNIE. 396 pp., 9s., leather.

"A most useful set of tables, and will supply a want, for nothing like them before existed."—*Building News.*

Iron and Steel.

'IRON AND STEEL': a Work for the Forge, Foundry, Factory, and Office. Containing Information for Ironmasters and their Stocktakers; Managers of Bar, Rail, Plate, and Sheet Rolling Mills; Iron and Metal Founders; Iron Ship and Bridge Builders; Mechanical, Mining, and Consulting Engineers; Architects, Builders, &c. By CHARLES HOARE, Author of 'The Slide Rule,' &c. Eighth Edition. With folding Scales of "Foreign Measures compared with the English Foot," and "fixed Scales of Squares, Cubes, and Roots, Areas, Decimal Equivalents, &c." Oblong, 32mo, 6s., leather, elastic-band.

"For comprehensiveness the book has not its equal."—*Iron.*

Comprehensive Weight Calculator.

THE WEIGHT CALCULATOR; being a Series of Tables upon a New and Comprehensive Plan, exhibiting at one Reference the exact Value of any Weight from 1 lb. to 15 tons, at 300 Progressive Rates, from 1 Penny to 168 Shillings per cwt., and containing 186,000 Direct Answers, which, with their Combinations, consisting of a single addition (mostly to be performed at sight), will afford an aggregate of 10,266,000 Answers; the whole being calculated and designed to ensure Correctness and promote Despatch. By HENRY HARBEN, Accountant, Sheffield. New Edition. Royal 8vo, 1l. 5s., strongly half-bound.

Comprehensive Discount Guide.

THE DISCOUNT GUIDE: comprising several Series of Tables for the use of Merchants, Manufacturers, Ironmongers, and others, by which may be ascertained the exact profit arising from any mode of using Discounts, either in the Purchase or Sale of Goods, and the method of either Altering a Rate of Discount, or Advancing a Price, so as to produce, by one operation, a sum that will realise any required profit after allowing one or more Discounts: to which are added Tables of Profit or Advance from $1\frac{1}{4}$ to 90 per cent., Tables of Discount from $1\frac{1}{4}$ to $98\frac{3}{4}$ per cent., and Tables of Commission, &c., from $\frac{1}{2}$ to 10 per cent. By HENRY HARBEN, Accountant. New Edition, Demy 8vo. £1 5s., half-bound.

SCIENCE AND ART.

Dentistry.

MECHANICAL DENTISTRY. A Practical Treatise on the Construction of the various kinds of Artificial Dentures. Comprising also Useful Formulæ, Tables, and Receipts for Gold Plate, Clasps, Solders, etc., etc. By CHARLES HUNTER. With numerous Wood Engravings. Crown 8vo, 7s. 6d. cloth.

"The work is very practical."—*Monthly Review of Dental Surgery.*

"An authoritative treatise We can strongly recommend Mr. Hunter's treatise to all students preparing for the profession of dentistry, as well as to every mechanical dentist."—*Dublin Journal of Medical Science.*

"The best book on the subject with which we are acquainted."—*Medical Press and Circular.*

Brewing.

A HANDBOOK FOR YOUNG BREWERS. By HERBERT EDWARDS WRIGHT, B.A. Crown 8vo, 3s. 6d. cloth.

"A thoroughly scientific treatise in popular language. It is evident that the author has mastered his subject in its scientific aspects."—*Morning Advertiser.*

"We would particularly recommend teachers of the art to place it in every pupil's hands, and we feel sure its perusal will be attended with advantage."—*Brewer.*

Gold and Gold-Working.

THE GOLDSMITH'S HANDBOOK: containing full instructions for the Alloying and Working of Gold. Including the Art of Alloying, Melting, Reducing, Colouring, Collecting and Refining. The processes of Manipulation, Recovery of Waste, Chemical and Physical Properties of Gold, with a new System of Mixing its Alloys; Solders, Enamels, and other useful Rules and Recipes, &c. By GEORGE E. GEE, Goldsmith and Silversmith. Second Edition, considerably enlarged. 12mo, 3s. 6d. cloth boards.

"A good, sound, technical educator, and will be generally accepted as an authority. It gives full particulars for mixing alloys and enamels, is essentially a book for the workshop, and exactly fulfils the purpose intended."—*Horological Journal.*

"The best work yet printed on its subject for a reasonable price. We have no doubt that it will speedily become a standard book which few will care to be without."—*Jeweller and Metalworker.*

"We consider that the trade owes not a little to Mr. Gee, who has in two volumes compressed almost the whole of its literature, and we doubt not that many a young beginner will owe a part of his future success to a diligent study of the pages which are peculiarly well adapted to his use."—*Clerkenwell Press.*

"It is essentially a practical manual, intended primarily for the use of working jewellers, but is well adapted to the wants of amateurs and apprentices, containing, as it does, trustworthy information that only a practical man can supply."—*English Mechanic.*

Silver and Silver Working.

THE SILVERSMITH'S HANDBOOK, containing full Instructions for the Alloying and Working of Silver, including the different modes of refining and melting the metal, its solders, the preparation of imitation alloys, methods of manipulation, prevention of waste, instructions for improving and finishing the surface of the work, together with other useful information and memoranda. By GEORGE E. GEE, Jeweller, &c. 12mo, 3s. 6d. cloth boards.

"This work is destined to take up as good a position in technical literature as the *Practical Goldworker*, a book which has passed through the ordeal of critical examination and business tests with great success."—*Jeweller and Metalworker.*

"The chief merit of the work is its practical character. The workers in the trade will speedily discover its merits when they sit down to study it."—*English Mechanic.*

"This work forms a valuable sequel to the author's *Practical Goldworker*, and supplies a want long felt in the silver trade."—*Silversmith's Trade Journal.*

Electric Lighting.

ELECTRIC LIGHT : Its Production and Use, embodying plain Directions for the Working of Galvanic Batteries, Electric Lamps, and Dynamo-Electric Machines. By J. W. URQUHART, C. E., Author of "Electroplating : a Practical Handbook." Edited by F. C. WEBB, M.I.C.E., M.S.T.E., With 94 Illustrations. Crown 8vo, 7s. 6d. cloth. *[Just published.]*

"It is the only work at present available, which gives in language intelligible for the most part to the ordinary reader, a general but concise history of the means which have been adopted up to the present time in producing the electric light."—*Metropolitan.*

"An important addition to the literature of the electric light. Students of the subject should not fail to read it."—*Colliery Guardian.*

"As a popular and practical treatise on the subject, the volume may be thoroughly recommended."—*Bristol Mercury.*

Electroplating, etc.

ELECTROPLATING : A Practical Handbook, including the Practice of Electrotyping. By J. W. URQUHART, C.E. With numerous Illustrations. Crown 8vo, 5s. cloth.

"The volume is without a rival in its particular sphere, and the lucid style in which it is written commends it to those amateurs and experimental electrotypers who have but slight, if any, knowledge of the processes of the art to which they turn their attention."—*Design and Work.*

"A large amount of thoroughly practical information."—*Telegraphic Journal.*

"An excellent practical manual."—*Engineering.*

"The information given appears to be based on direct personal knowledge. . . . Its science is sound, and the style is always clear."—*Athenæum.*

"Any ordinarily intelligent person may become an adept in electro-deposition with a very little science indeed, and this is the book to show him or her the way."—*Builder.*

The Military Sciences.

AIDE-MÉMOIRE to the MILITARY SCIENCES. Framed from Contributions of Officers and others connected with the different Services. Originally edited by a Committee of the Corps of Royal Engineers. Second Edition, most carefully revised by an Officer of the Corps, with many additions ; containing nearly 350 Engravings and many hundred Woodcuts. 3 vols. royal 8vo, extra cloth boards, and lettered, 4l. 10s.

"A compendious encyclopædia of military knowledge."—*Edinburgh Review.*

"The most comprehensive work of reference to the military and collateral sciences."—*Volunteer Service Gazette.*

Field Fortification.

A TREATISE on FIELD FORTIFICATION, the ATTACK of FORTRESSES, MILITARY MINING, and RECON-NOITRING. By Colonel I. S. MACAULAY, late Professor of Fortification in the R. M. A., Woolwich. Sixth Edition, crown 8vo, cloth, with separate Atlas of 12 Plates, 12s. complete.

Dye-Wares and Colours.

THE MANUAL of COLOURS and DYE-WARES : their Properties, Applications, Valuation, Impurities, and Sophistications. For the Use of Dyers, Printers, Drysalters, Brokers, &c. By J. W. SLATER. Post 8vo, 7s. 6d. cloth.

"A complete encyclopædia of the *materia tinctoria*. The information is full and precise, and the methods of determining the value of articles liable to sophistication, are practical as well as valuable."—*Chemist and Druggist.*

The Alkali Trade—Sulphuric Acid, etc.

A MANUAL OF THE ALKALI TRADE, including the Manufacture of Sulphuric Acid, Sulphate of Soda, and Bleaching Powder. By JOHN LOMAS, Alkali Manufacturer, Newcastle-upon-Tyne and London. With 232 Illustrations and Working Drawings, and containing 386 pages of text. Super-royal 8vo, 2l 12s. 6d. cloth. [Just published.]

This work provides (1) a Complete Handbook for intending Alkali and Sulphuric Acid Manufacturers, and for those already in the field who desire to improve their plant, or to become practically acquainted with the latest processes and developments of the trade; (2) a Handy Volume which Manufacturers can put into the hands of their Managers and Foremen as a useful guide in their daily rounds of duty.

SYNOPSIS OF CONTENTS.

Chap. I. Choice of Site and General Plan of Works—II. Sulphuric Acid—III. Recovery of the Nitrogen Compounds, and Treatment of Small Pyrites—IV. The Salt Cake Process—V. Legislation upon the Noxious Vapours Question—VI. The Hargreaves' and Jones' Processes—VII. The Balling Process—VIII. Lixiviation and Salting Down—

IX. Carbonating or Finishing—X. Soda Crystals—XI. Refined Alkali—XII. Caustic Soda—XIII. Bi-carbonate of Soda—XIV. Bleaching Powder—XV. Utilisation of Tank Waste—XVI. General Remarks—Four Appendices, treating of Yields, Sulphuric Acid Calculations, Anemometers, and Foreign Legislation upon the Noxious Vapours Question.

"The author has given the fullest, most practical, and, to all concerned in the alkali trade, most valuable mass of information that, to our knowledge, has been published in any language."—*Engineer*.

"This book is written by a manufacturer for manufacturers. The working details of the most approved forms of apparatus are given, and these are accompanied by no less than 232 wood engravings, all of which may be used for the purposes of construction. Every step in the manufacture is very fully described in this manual, and each improvement explained. Everything which tends to introduce economy into the technical details of this trade receives the fullest attention. The book has been produced with great completeness."—*Athenæum*.

"The author is not one of those clever compilers who, on short notice, will 'read up' any conceivable subject, but a practical man in the best sense of the word. We find here not merely a sound and luminous explanation of the chemical principles of the trade, but a notice of numerous matters which have a most important bearing on the successful conduct of alkali works, but which are generally overlooked by even the most experienced technological authors. This most valuable book, which we trust will be generally appreciated, we must pronounce a credit alike to its author and to the enterprising firm who have undertaken its publication."—*Chemical Review*.

Chemical Analysis.

THE COMMERCIAL HANDBOOK of CHEMICAL ANALYSIS; or Practical Instructions for the determination of the Intrinsic or Commercial Value of Substances used in Manufactures, in Trades, and in the Arts. By A. NORMANDY, Author of "Practical Introduction to Rose's Chemistry," and Editor of Rose's "Treatise on Chemical Analysis." *New Edition*. Enlarged, and to a great extent re-written, by HENRY M. NOAD, Ph. D., F.R.S. With numerous Illustrations. Cr. 8vo, 12s. 6d. cloth.

"We recommend this book to the careful perusal of every one; it may be truly affirmed to be of universal interest, and we strongly recommend it to our readers as a guide, alike indispensable to the housewife as to the pharmaceutical practitioner."—*Medical Times*.

"Essential to the analysts appointed under the new Act. The most recent result are given, and the work is well edited and carefully written."—*Nature*.

Dr. Lardner's Museum of Science and Art.

THE MUSEUM OF SCIENCE AND ART. Edited by DIONYSIUS LARDNER, D.C.L., formerly Professor of Natural Philosophy and Astronomy in University College, London. With upwards of 1200 Engravings on Wood. In 6 Double Volumes. Price £1 1s., in a new and elegant cloth binding, or handsomely bound in half morocco, 31s. 6d.

OPINIONS OF THE PRESS.

"This series, besides affording popular but sound instruction on scientific subjects, with which the humblest man in the country ought to be acquainted, also undertakes that teaching of 'common things' which every well-wisher of his kind is anxious to promote. Many thousand copies of this serviceable publication have been printed, in the belief and hope that the desire for instruction and improvement widely prevails; and we have no fear that such enlightened faith will meet with disappointment."—*Times*.

"A cheap and interesting publication, alike informing and attractive. The papers combine subjects of importance and great scientific knowledge, considerable inductive powers, and a popular style of treatment."—*Spectator*.

"The 'Museum of Science and Art' is the most valuable contribution that has ever been made to the Scientific Instruction of every class of society."—*Sir David Brewster in the North British Review*.

"Whether we consider the liberality and beauty of the illustrations, the charm of the writing, or the durable interest of the matter, we must express our belief that there is hardly to be found among the new books, one that would be welcomed by people of so many ages and classes as a valuable present."—*Examiner*.

* * *Separate books formed from the above, suitable for Workmen's Libraries, Science Classes, &c.*

COMMON THINGS EXPLAINED. Containing Air, Earth, Fire, Water, Time, Man, the Eye, Locomotion, Colour, Clocks and Watches, &c. 233 Illustrations, cloth gilt, 5s.

THE MICROSCOPE. Containing Optical Images, Magnifying Glasses, Origin and Description of the Microscope, Microscopic Objects, the Solar Microscope, Microscopic Drawing and Engraving, &c. 147 Illustrations, cloth gilt, 2s.

POPULAR GEOLOGY. Containing Earthquakes and Volcanoes, the Crust of the Earth, etc. 201 Illustrations, cloth gilt, 2s. 6d.

POPULAR PHYSICS. Containing Magnitude and Minuteness, the Atmosphere, Meteoric Stones, Popular Fallacies, Weather Prognostics, the Thermometer, the Barometer, Sound, &c. 85 Illustrations, cloth gilt, 2s. 6d.

STEAM AND ITS USES. Including the Steam Engine, the Locomotive, and Steam Navigation. 89 Illustrations, cloth gilt, 2s.

POPULAR ASTRONOMY. Containing How to Observe the Heavens. The Earth, Sun, Moon, Planets. Light, Comets, Eclipses, Astronomical Influences, &c. 182 Illustrations, 4s. 6d.

THE BEE AND WHITE ANTS: Their Manners and Habits. With Illustrations of Animal Instinct and Intelligence. 135 Illustrations, cloth gilt, 2s.

THE ELECTRIC TELEGRAPH POPULARISED. To render intelligible to all who can Read, irrespective of any previous Scientific Acquirements, the various forms of Telegraphy in Actual Operation. 100 Illustrations, cloth gilt, 1s. 6d.

Dr. Lardner's Handbooks of Natural Philosophy.

*** The following five volumes, though each is Complete in itself, and to be purchased separately, form A COMPLETE COURSE OF NATURAL PHILOSOPHY, and are intended for the general reader who desires to attain accurate knowledge of the various departments of Physical Science, without pursuing them according to the more profound methods of mathematical investigation. The style is studiously popular. It has been the author's aim to supply Manuals such as are required by the Student, the Engineer, the Artisan, and the superior classes in Schools.

THE HANDBOOK OF MECHANICS. Enlarged and almost rewritten by BENJAMIN LOEWY, F.R.A.S. With 378 Illustrations. Post 8vo, 6s. cloth.

"The perspicuity of the original has been retained, and chapters which had become obsolete, have been replaced by others of more modern character. The explanations throughout are studiously popular, and care has been taken to show the application of the various branches of physics to the industrial arts, and to the practical business of life."—*Mining Journal*.

THE HANDBOOK OF HYDROSTATICS and PNEUMATICS. New Edition, Revised and Enlarged by BENJAMIN LOEWY, F.R.A.S. With 236 Illustrations. Post 8vo, 5s. cloth.

"For those 'who desire to attain an accurate knowledge of physical science without the profound methods of mathematical investigation,' this work is not merely intended, but well adapted."—*Chemical News*.

THE HANDBOOK OF HEAT. Edited and almost entirely Rewritten by BENJAMIN LOEWY, F.R.A.S., etc. 117 Illustrations. Post 8vo, 6s. cloth.

"The style is always clear and precise, and conveys instruction without leaving any cloudiness or lurking doubts behind."—*Engineering*.

THE HANDBOOK OF OPTICS. New Edition. Edited by T. OLVER HARDING, B.A. 298 Illustrations. Post 8vo, 5s. cloth.

"Written by one of the ablest English scientific writers, beautifully and elaborately illustrated."—*Mechanics' Magazine*.

THE HANDBOOK OF ELECTRICITY, MAGNETISM, and ACOUSTICS. New Edition. Edited by GEO. CAREY FOSTER, B.A., F.C.S. With 400 Illustrations. Post 8vo, 5s. cloth.

"The book could not have been entrusted to any one better calculated to preserve the terse and lucid style of Lardner, while correcting his errors and bringing up his work to the present state of scientific knowledge."—*Popular Science Review*.

Dr. Lardner's Handbook of Astronomy.

THE HANDBOOK OF ASTRONOMY. Forming a Companion to the "Handbooks of Natural Philosophy." By DIONYSIUS LARDNER, D.C.L., formerly Professor of Natural Philosophy and Astronomy in University College, London. Fourth Edition. Revised and Edited by EDWIN DUNKIN, F.R.S., Royal Observatory, Greenwich. With 38 Plates and upwards of 100 Woodcuts. In 1 vol., small 8vo, 550 pages, 9s. 6d., cloth.

"Probably no other book contains the same amount of information in so compendious and well-arranged a form—certainly none at the price at which this is offered to the public."—*Athenæum*.

"We can do no other than pronounce this work a most valuable manual of astronomy, and we strongly recommend it to all who wish to acquire a general—but at the same time correct—acquaintance with this sublime science."—*Quarterly Journal of Science*.

Dr. Lardner's Handbook of Animal Physics.

THE HANDBOOK OF ANIMAL PHYSICS. By DR. LARDNER. With 520 Illustrations. New edition, small 8vo, cloth, 732 pages, 7s. 6d.

"We have no hesitation in cordially recommending it."—*Educational Times*.

Dr. Lardner's School Handbooks.

NATURAL PHILOSOPHY FOR SCHOOLS. By DR. LARDNER.
328 Illustrations. Sixth Edition. 1 vol. 3s. 6d. cloth.

"Conveys, in clear and precise terms, general notions of all the principal divisions of Physical Science."—*British Quarterly Review*.

ANIMAL PHYSIOLOGY FOR SCHOOLS. By DR. LARDNER.

With 190 Illustrations. Second Edition. 1 vol. 3s. 6d. cloth.

"Clearly written, well arranged, and excellently illustrated."—*Gardeners' Chronicle*.

Dr. Lardner's Electric Telegraph.

THE ELECTRIC TELEGRAPH. By DR. LARDNER. New Edition. Revised and Re-written, by E. B. BRIGHT, F.R.A.S.
140 Illustrations. Small 8vo, 2s. 6d. cloth.

"One of the most readable books extant on the Electric Telegraph."—*Eng. Mechanic*.

Electricity.

A MANUAL OF ELECTRICITY; including Galvanism, Magnetism, Diamagnetism, Electro-Dynamics, Magneto-Electricity, and the Electric Telegraph. By HENRY M. NOAD, Ph.D., F.C.S.
Fourth Edition, with 500 Woodcuts. 8vo, 17. 4s. cloth.

"The accounts given of electricity and galvanism are not only complete in a scientific sense, but, which is a rarer thing, are popular and interesting."—*Lancet*.

Text-Book of Electricity.

THE STUDENT'S TEXT-BOOK OF ELECTRICITY. By HENRY M. NOAD, Ph.D., F.R.S., F.C.S. New Edition, carefully Revised. With an Introduction and Additional Chapters by W. H. PREECE, M.I.C.E., Vice-President of the Society of Telegraph Engineers, &c. With 470 Illustrations. Crown 8vo, 12s. 6d. cloth.

[Just published.]

"A reflex of the existing state of Electrical Science adapted for students."—W. H. Preece, Esq., vide "Introduction."

"We can recommend Dr. Noad's book for clear style, great range of subject, a good index, and a plethora of woodcuts. Such collections as the present are indispensable."—*Athenæum*.

"An admirable text-book for every student—beginner or advanced—of electricity."—*Engineering*.

"A most elaborate compilation of the facts of electricity and magnetism."—*Popular Science Review*.

"May be recommended to students as one of the best text-books on the subject that they can have. . . . Mr. Preece appears to have introduced all the newest inventions in the shape of telegraphic, telephonic, and electric-lighting apparatus."—*English Mechanic*.

"The work contains everything that the student can require, it is well illustrated, clearly written, and possesses a good index."—*Academy*.

"One of the best and most useful compendiums of any branch of science in our literature."—*Iron*.

"Under the editorial hand of Mr. Preece the late Dr. Noad's text-book of electricity has grown into an admirable handbook."—*Westminster Review*.

Geology and Genesis.

THE TWIN RECORDS OF CREATION; or, Geology and Genesis, their Perfect Harmony and Wonderful Concord. By GEORGE W. VICTOR LE VAUX. Numerous Illustrations. Fcap. 8vo, 5s. cloth.

"A valuable contribution to the evidences of revelation, and disposes very conclusively of the arguments of those who would set God's Works against God's Word. No real difficulty is shirked, and no sophistry is left unexposed."—*The Rock*.

Science and Scripture.

SCIENCE ELUCIDATIVE OF SCRIPTURE, AND NOT ANTAGONISTIC TO IT; being a Series of Essays on—1. Alleged Discrepancies; 2. The Theory of the Geologists and Figure of the Earth; 3. The Mosaic Cosmogony; 4. Miracles in general—Views of Hume and Powell; 5. The Miracle of Joshua—Views of Dr. Colenso: The Supernaturally Impossible; 6. The Age of the Fixed Stars, &c. By Prof. J. R. YOUNG. Fcap. 5s. cl.

Geology.

A CLASS-BOOK OF GEOLOGY. Consisting of "Physical Geology," which sets forth the Leading Principles of the Science; and "Historical Geology," which treats of the Mineral and Organic Conditions of the Earth at each successive epoch, especial reference being made to the British Series of Rocks. By RALPH TATE. With more than 250 Illustrations. Fcap. 8vo, 5s. cloth.

Practical Philosophy.

A SYNOPSIS OF PRACTICAL PHILOSOPHY. By Rev. JOHN CARR, M.A., late Fellow of Trin. Coll., Camb. 18mo, 5s. cl.

Mollusca.

A MANUAL OF THE MOLLUSCA; being a Treatise on Recent and Fossil Shells. By Dr. S. P. WOODWARD, A.L.S. With Appendix by RALPH TATE, A.L.S., F.G.S. With numerous Plates and 300 Woodcuts. 3rd Edition. Cr. 8vo, 7s. 6d. cloth.

Clocks, Watches, and Bells.

RUDIMENTARY TREATISE on CLOCKS, and WATCHES, and BELLS. By Sir EDMUND BECKETT, Bart. (late E. B. Denison), LL.D., Q.C., F.R.A.S. Sixth edition, revised and enlarged. Limp cloth (No. 67, Weale's Series), 4s. 6d.; cloth bds. 5s. 6d.

"As a popular and practical treatise it is unapproached."—*English Mechanic*.

"The best work on the subject probably extant. The treatise on bells is undoubtedly the best in the language."—*Engineering*.

"The only modern treatise on clock-making."—*Horological Journal*.

Grammar of Colouring.

A GRAMMAR OF COLOURING, applied to Decorative Painting and the Arts. By GEORGE FIELD. New edition, enlarged. By ELLIS A. DAVIDSON. With new Coloured Diagrams and Engravings. 12mo, 3s. 6d. cloth.

"The book is a most useful résumé of the properties of pigments."—*Builder*.

Pictures and Painters.

THE PICTURE AMATEUR'S HANDBOOK AND DICTIONARY OF PAINTERS: A Guide for Visitors to Picture Galleries, and for Art-Students, including methods of Painting, Cleaning, Re-Lining, and Restoring, Principal Schools of Painting, Copyists and Imitators. By PHILIPPE DARYL, B.A. Cr. 8vo, 3s. 6d. cl.

Woods and Marbles (Imitation of).

SCHOOL OF PAINTING FOR THE IMITATION OF WOODS AND MARBLES, as Taught and Practised by A. R. and P. VAN DER BURG, Directors of the Rotterdam Painting Institution. Illustrated with 24 full-size Coloured Plates; also 12 Plain Plates, comprising 154 Figures. Folio, 2l. 12s. 6d. bound.

Delamotte's Works on Illumination & Alphabets.

A PRIMER OF THE ART OF ILLUMINATION; for the use of Beginners: with a Rudimentary Treatise on the Art, Practical Directions for its Exercise, and numerous Examples taken from Illuminated MSS., printed in Gold and Colours. By F. DELAMOTTE. Small 4to, 9s. Elegantly bound, cloth antique.

"The examples of ancient MSS. recommended to the student, which, with much good sense, the author chooses from collections accessible to all, are selected with judgment and knowledge, as well as taste."—*Athenæum*.

ORNAMENTAL ALPHABETS, ANCIENT and MEDIÆVAL; from the Eighth Century, with Numerals; including Gothic, Church-Text, German, Italian, Arabesque, Initials, Monograms, Crosses, &c. Collected and engraved by F. DELAMOTTE, and printed in Colours. New and Cheaper Edition. Royal 8vo, oblong, 2s. 6d. ornamental boards.

"For those who insert enamelled sentences round gilded chalices, who blazon shop legends over shop-doors, who letter church walls with pithy sentences from the Decalogue, this book will be useful."—*Athenæum*.

EXAMPLES OF MODERN ALPHABETS, PLAIN and ORNAMENTAL; including German, Old English, Saxon, Italic, Perspective, Greek, Hebrew, Court Hand, Engrossing, Tuscan, Riband, Gothic, Rustic, and Arabesque, &c., &c. Collected and engraved by F. DELAMOTTE, and printed in Colours. New and Cheaper Edition. Royal 8vo, oblong, 2s. 6d. ornamental boards.

"There is comprised in it every possible shape into which the letters of the alphabet and numerals can be formed."—*Standard*.

MEDIÆVAL ALPHABETS AND INITIALS FOR ILLUMINATORS. By F. DELAMOTTE. Containing 21 Plates, and Illuminated Title, printed in Gold and Colours. With an Introduction by J. WILLIS BROOKS. Small 4to, 6s. cloth gilt.

THE EMBROIDERER'S BOOK OF DESIGN; containing Initials, Emblems, Cyphers, Monograms, Ornamental Borders, Ecclesiastical Devices, Mediæval and Modern Alphabets, and National Emblems. Collected and engraved by F. DELAMOTTE, and printed in Colours. Oblong royal 8vo, 1s. 6d. in ornamental boards.

Wood-Carving.

INSTRUCTIONS in WOOD-CARVING, for Amateurs; with Hints on Design. By A LADY. In emblematic wrapper, handsomely printed, with Ten large Plates, 2s. 6d.

"The handicraft of the wood-carver, so well as a book can impart it, may be learnt from 'A Lady's' publication."—*Athenæum*.

Popular Work on Painting.

PAINTING POPULARLY EXPLAINED; with Historical Sketches of the Progress of the Art. By THOMAS JOHN GULLICK, Painter, and JOHN TIMBS, F.S.A. Fourth Edition, revised and enlarged. With Frontispiece and Vignette. In small 8vo, 6s. cloth.

* * * This Work has been adopted as a Prize-book in the Schools of Art at South Kensington.

"Contains a large amount of original matter, agreeably conveyed."—*Builder*.

"Much may be learned, even by those who fancy they do not require to be taught, from the careful perusal of this unpretending but comprehensive treatise."—*Art Journal*.

AGRICULTURE, GARDENING, ETC.

Youatt and Burn's Complete Grazier.

THE COMPLETE GRAZIER, and FARMER'S and CATTLE-BREEDER'S ASSISTANT. A Compendium of Husbandry. By WILLIAM YOUATT, ESQ., V.S. 12th Edition, very considerably enlarged, and brought up to the present requirements of agricultural practice. By ROBERT SCOTT BURN. One large 8vo. volume, 860 pp. with 244 Illustrations. 17. 1s. half-bound.

"The standard and text-book, with the farmer and grazier."—*Farmer's Magazine*.

"A treatise which will remain a standard work on the subject as long as British agriculture endures."—*Mark Lane Express*.

History, Structure, and Diseases of Sheep.

SHEEP; THE HISTORY, STRUCTURE, ECONOMY, AND DISEASES OF. By W. C. SPOONER, M.R.V.C., &c. Fourth Edition, with fine engravings, including specimens of New and Improved Breeds. 366 pp., 4s. cloth.

Production of Meat.

MEAT PRODUCTION. A Manual for Producers, Distributors, and Consumers of Butchers' Meat. Being a treatise on means of increasing its Home Production. Also comprehensively treating of the Breeding, Rearing, Fattening, and Slaughtering of Meat-yielding Live Stock; Indications of the Quality; Means for Preserving, Curing, and Cooking of the Meat, etc. BY JOHN EWART. Numerous Illustrations. Cr. 8vo, 5s. cloth.

"A compact and handy volume on the meat question, which deserves serious and thoughtful consideration at the present time."—*Meat and Provision Trades' Review*.

Donaldson and Burn's Suburban Farming.

SUBURBAN FARMING. A Treatise on the Laying Out and Cultivation of Farms adapted to the produce of Milk, Butter and Cheese, Eggs, Poultry, and Pigs. By the late Professor JOHN DONALDSON. With considerable Additions, Illustrating the more Modern Practice, by R. SCOTT BURN. With Illustrations. Crown 8vo, 6s. cloth.

Modern Farming.

OUTLINES OF MODERN FARMING. By R. SCOTT BURN. Soils, Manures, and Crops—Farming and Farming Economy—Cattle, Sheep, and Horses—Management of the Dairy, Pigs, and Poultry—Utilisation of Town Sewage, Irrigation, &c. New Edition. In 1 vol. 1250 pp., half-bound, profusely illustrated, 12s.

"There is sufficient stated within the limits of this treatise to prevent a farmer from going far wrong in any of his operations."—*Observer*.

Amateur Farming.

THE LESSONS OF MY FARM: a Book for Amateur Agriculturists, being an Introduction to Farm Practice, in the Culture of Crops, the Feeding of Cattle, Management of the Dairy, Poultry, Pigs, &c. By R. SCOTT BURN. With numerous Illus. Fcp. 6s. cl.

"A complete introduction to the whole round of farming practice."—*John Bull*.

The Management of Estates.

LANDED ESTATES MANAGEMENT: Treating of the Varieties of Lands, Peculiarities of its Farms, Methods of Farming, the Setting-out of Farms and their Fields, Construction of Roads, Fences, Gates, and Farm Buildings, of Waste or Unproductive Lands, Irrigation, Drainage, Plantation, &c. By R. SCOTT BURN. Numerous Illustrations. Second Edition. 12mo, 3s. cloth.

"A complete and comprehensive outline of the duties appertaining to the management of landed estates."—*Journal of Forestry*.

"A very useful vade-mecum to such as have the care of land."—*Globe*.

The Management of Farms.

OUTLINES OF FARM MANAGEMENT, and the Organization of Farm Labour. Treating of the General Work of the Farm, Field, and Live Stock, Details of Contract Work, Specialties of Labour, Economical Management of the Farmhouse and Cottage, and their Domestic Animals. By ROBERT SCOTT BURN, Author of "Outlines of Modern Farming," &c. With numerous Illustrations. 12mo, 3s. cloth boards. [Just published.]

Management of Estates and Farms.

LANDED ESTATES AND FARM MANAGEMENT. By R. SCOTT BURN, Author of "Outlines of Modern Farming," Editor of "The Complete Grazier," &c. With Illustrations. Consisting of the above Two Works in One vol., 6s. half-bound.

[Just published.]

Kitchen Gardening.

KITCHEN GARDENING MADE EASY. Showing how to prepare and lay out the ground, the best means of cultivating every known Vegetable and Herb, with cultural directions for the management of them all the year round. By GEORGE M. F. GLENNY. With Illustrations, 12mo, 2s. cloth boards.

"As a guide to hardy kitchen gardening, this book will be found trustworthy and useful."—*North British Agriculturist*.

Culture of Fruit Trees.

FRUIT TREES, the Scientific and Profitable Culture of. From the French of DU BREUIL, revised by GEO. GLENNY. 187 Cuts. 12mo, 4s. cloth.

Good Gardening.

A PLAIN GUIDE TO GOOD GARDENING; or, How to Grow Vegetables, Fruits, and Flowers. With Practical Notes on Soils, Manures, Seeds, Planting, Laying-out of Gardens and Grounds, &c. By S. WOOD. Third Edition, with considerable Additions, &c., and numerous Illustrations. Cr. 8vo, 5s. cloth.

"A very good book, and one to be highly recommended as a practical guide. The practical directions are excellent."—*Athenæum*.

Gainful Gardening.

MULTUM-IN-PARVO GARDENING; or, How to make One Acre of Land produce £620 a year, by the Cultivation of Fruits and Vegetables; also, How to Grow Flowers in Three Glass Houses, so as to realise £176 per annum clear Profit. By SAMUEL WOOD. 3rd Edition, revised. Cr. 8vo, 2s. cloth.

"We are bound to recommend it as not only suited to the case of the amateur and gentleman's gardener, but to the market grower."—*Gardener's Magazine*.

Bulb Culture.

THE BULB GARDEN, or, How to Cultivate Bulbous and Tuberous-rooted Flowering Plants to Perfection. A Manual adapted for both the Professional and Amateur Gardener. By SAMUEL WOOD, Author of "Good Gardening," etc. With Coloured Illustrations and Wood Engravings. Cr. 8vo, 3s. 6d. cloth.
 "The book contains practical suggestions as to the arrangement of the flowers, and the growth of flower-roots for the trade, as well as for amusement."—*Saturday Review*.

Tree Planting.

THE TREE PLANTER AND PLANT PROPAGATOR: Being a Practical Manual on the Propagation of Forest Trees, Fruit Trees, Flowering Shrubs, Flowering Plants, Pot Herbs, &c. Numerous Illustrations. By SAMUEL WOOD. 12mo, 2s. 6d. cloth.

Tree Pruning.

THE TREE PRUNER: Being a Practical Manual on the Pruning of Fruit Trees. Including also their Training and Renovation, with the best Method of bringing Old and Worn-out Trees into a state of Bearing; also treating of the Pruning of Shrubs, Climbers, and Flowering Plants. With numerous Illustrations. By SAMUEL WOOD. 12mo, 2s. 6d. cloth. [Just published.

Tree Planting, Pruning, & Plant Propagation.

THE TREE PLANTER, PROPAGATOR, AND PRUNER. By SAMUEL WOOD, Author of "Good Gardening," &c. Consisting of the above Two Works in One Vol., 5s. half-bound.

Potato Culture.

POTATOES, HOW TO GROW AND SHOW THEM: A Practical Guide to the Cultivation and General Treatment of the Potato. By JAMES PINK. With Illustrations. Cr. 8vo, 2s. cl.
 "A well written little volume. The author gives good practical instructions under both divisions of his subject."—*Agricultural Gazette*.

Hudson's Tables for Land Valuers.

THE LAND VALUER'S BEST ASSISTANT: being Tables, on a very much improved Plan, for Calculating the Value of Estates. With Tables for reducing Scotch, Irish, and Provincial Customary Acres to Statute Measure, &c. By R. HUDSON, C.E. New Edition, royal 32mo, leather, gilt edges, elastic band, 4s.

Ewart's Land Improver's Pocket-Book.

THE LAND IMPROVER'S POCKET-BOOK OF FORMULÆ, TABLES, and MEMORANDA, required in any Computation relating to the Permanent Improvement of Landed Property. By JOHN EWART, Land Surveyor and Agricultural Engineer. Royal 32mo, oblong, leather, gilt edges, with elastic band, 4s.

Complete Agricultural Surveyor's Pocket-Book.

THE LAND VALUER'S AND LAND IMPROVER'S COMPLETE POCKET-BOOK; consisting of the above two works bound together, leather, gilt edges, with strap, 7s. 6d.

"We consider Hudson's book to be the best ready-reckoner on matters relating to the valuation of land and crops we have ever seen, and its combination with Mr. Ewart's work greatly enhances the value and usefulness of the latter-mentioned . . . It is most useful as a manual for reference."—*North of England Farmer*.

"A Complete Epitome of the Laws of this Country."

EVERY MAN'S OWN LAWYER; a Handy-Book of the Principles of Law and Equity. By A BARRISTER. New Edition, much enlarged. With Notes and References to the Authorities. Crown 8vo, cloth, price 6s. 8d. (saved at every consultation).

COMPRISING THE RIGHTS AND WRONGS OF INDIVIDUALS, MERCANTILE AND COMMERCIAL LAW, CRIMINAL LAW, PARISH LAW, COUNTY COURT LAW, GAME AND FISHERY LAWS, POOR MEN'S LAW, THE LAWS OF

BANKRUPTCY—BILLS OF EXCHANGE—CONTRACTS AND AGREEMENTS—COPYRIGHT—DOWER AND DIVORCE—ELECTIONS AND REGISTRATION—INSURANCE—LIBEL AND SLANDER—MORTGAGES—

SETTLEMENTS—STOCK EXCHANGE PRACTICE—TRADE MARKS AND PATENTS—TRESPASS, NUISANCES, ETC.—TRANSFER OF LAND, ETC.—WARRANTY—WILLS AND AGREEMENTS, ETC.

Also Law for Landlord and Tenant—Master and Servant—Workmen and Apprentices—Heirs, Devises, and Legatees—Husband and Wife—Executors and Trustees—Guardian and Ward—Married Women and Infants—Partners and Agents—Lender and Borrower—Debtor and Creditor—Purchaser and Vendor—Companies and Associations

—Friendly Societies—Clergymen, Churchwardens—Medical Practitioners, &c.—Bankers—Farmers—Contractors—Stock and Share Brokers—Sportsmen and Gamekeepers—Farriers and Horse-Dealers—Auctioneers, House-Agents—Innkeepers, &c.—Pawnbrokers—Surveyors—Railways and Carriers, &c., &c.

"No Englishman ought to be without this book."—*Engineer.*

"What it professes to be—a complete epitome of the laws of this country, thoroughly intelligible to non-professional readers. The book is a handy one to have in readiness when some knotty point requires ready solution."—*Bell's Life.*

"A concise, cheap, and complete epitome of the English law, so plainly written that he who runs may read, and he who reads may understand."—*Figaro.*

"A useful and concise epitome of the law."—*Law Magazine.*

"Full of information, fitly expressed without the aid of technical expressions, and to the general public will, we doubt not, prove of considerable worth."—*Economist.*

Auctioneer's Assistant.

THE APPRAISER, AUCTIONEER, BROKER, HOUSE AND ESTATE AGENT, AND VALUER'S POCKET ASSISTANT, for the Valuation for Purchase, Sale, or Renewal of Leases, Annuities, and Reversions, and of property generally; with Prices for Inventories, &c. By JOHN WHEELER, Valuer, &c.

Fourth Edition, enlarged, by C. NORRIS. Royal 32mo, cloth, 5s.

"A neat and concise book of reference, containing an admirable and clearly-arranged list of prices for inventories, and a very practical guide to determine the value of furniture, &c."—*Standard.*

Auctioneering.

AUCTIONEERS: THEIR DUTIES AND LIABILITIES.

By ROBERT SQUIBBS, Auctioneer. Demy 8vo, 10s. 6d. cloth.

House Property.

HANDBOOK OF HOUSE PROPERTY: a Popular and Practical Guide to the Purchase, Mortgage, Tenancy, and Compulsory Sale of Houses and Land; including the Law of Dilapidations and Fixtures; with Explanations and Examples of all kinds of Valuations, and useful Information and Advice on Building. By E. L. TARBUCK, Architect and Surveyor. 2nd Edition. 12mo, 3s. 6d. cl.

"We are glad to be able to recommend it."—*Builder.*

"The advice is thoroughly practical."—*Law Journal.*

Bradbury, Agnew, & Co., Printers, Whitefriars, London.

90-B 13468

THE HISTORY OF THE UNITED STATES

OF THE UNITED STATES OF AMERICA, FROM THE FIRST SETTLEMENTS TO THE PRESENT TIME.

BY CHARLES C. SMITH, LL.D.,

OF THE UNIVERSITY OF CHICAGO.

NEW YORK: PUBLISHED BY THE AUTHOR, 10 N. 3RD ST., N.Y.

1884.

THE HISTORY OF THE UNITED STATES, FROM THE FIRST SETTLEMENTS TO THE PRESENT TIME.

BY CHARLES C. SMITH, LL.D.,

OF THE UNIVERSITY OF CHICAGO.

NEW YORK: PUBLISHED BY THE AUTHOR, 10 N. 3RD ST., N.Y.

1884.

THE HISTORY OF THE UNITED STATES, FROM THE FIRST SETTLEMENTS TO THE PRESENT TIME.

BY CHARLES C. SMITH, LL.D.,

OF THE UNIVERSITY OF CHICAGO.

NEW YORK: PUBLISHED BY THE AUTHOR, 10 N. 3RD ST., N.Y.

1884.

THE HISTORY OF THE UNITED STATES, FROM THE FIRST SETTLEMENTS TO THE PRESENT TIME.

BY CHARLES C. SMITH, LL.D.,

A SELECTION FROM WEALE'S SERIES.

Date Due

C			
PN			
T			
CR			
R			
E			
TE			
ti			
TE			
w			
M			
ST			
n			
CL			
B			
ro			
b			
FU			
o			
S			
ti			
F			
C			
MA			
w			
u			
C			
I			
TE			
M			
E			
ST			
a			
"			
S			
c			

PLUMBING: a Text-book to the Practice of the Art or Craft of the Plumber. With Chapters upon House Drainage, embodying the latest improvements. Second Edition, revised and much enlarged. With 300 Illustrations. By W. P. BUCHAN. 3s. 6d.; cloth boards, 4s.

CROSBY LOCKWOOD & CO., 7, STATIONERS' HALL COURT, E.C.

A SELECTION FROM WEALE'S SERIES.

MECHANISM, the Elements of; elucidating the Scientific Principles of the Practical Construction of Machines. With Specimens of Modern Machines by T. BAKER, C.E.; and Remarks on Tools, &c., by J. NASMYTH, C.E. 2s. 6d.; cloth boards, 3s.

LOCOMOTIVE ENGINES. Comprising an Historical Sketch of the Locomotive Engine by G. D. DEMME, C.E. 3s.; cloth boards, 4s. 6d. 687 Ur 64

THE ROYAL
TICAL ENGINEER.
RTHY. 3s. 5434

THE
for
Bu
Co
Notes on Prime
th boards, 2s. 6d.

MO
Ma
Cr
3s.
as applied to
Docks, Bridges,
3s.; cloth boards,

IRO
in
and
C.I.
boards, 3s.

PO
W
By
tion, Toothed-
Angular Forces.
cloth boards, 3s.

THE CON-
ROOFS, AND
Second Edition,
revised. With numerous Illustrations. 2s. 6d.; cloth boards, 3s.

MINING TOOLS. For the use of Mine Managers, Agents, Students, &c. By WILLIAM MORGANS, Bristol School of Mines. 12mo. 2s. 6d.; cloth boards, 3s. With an Atlas of Plates, containing 235 Illustrations. 4to. 4s. 6d.; cloth boards, 6s.

THE WORKMAN'S MANUAL OF ENGINEERING
DRAWING. By JOHN MAXTON, Instructor in Engineering Drawing, Royal Naval College, Greenwich, formerly of R.S.N.A., South Kensington, &c., &c. 3s. 6d.; cloth boards, 4s.

METALLURGY OF IRON, the. Containing Methods of Assay, Processes of Manufacture of Iron and Steel, &c. By H. BAUERMAN, F.G.S., &c. Fourth Edition, revised and enlarged. Numerous Illustrations. 4s. 6d.; cloth boards, 5s.

COAL AND COAL MINING: a Rudimentary Treatise on. By WARINGTON W. SMYTH, M.A., F.R.S., &c., Chief Inspector of the Mines of the Crown and of the Duchy of Cornwall. With numerous Illustrations. 3s. 6d.; cloth boards, 4s.

GETTY CENTER LIBRARY



3 3125 00002 1309

IONERS' HALL COURT, E.C.

